2 Shelf Service Carts with Standard Handle

Model SB - Rugged general use carts for transporting small packages, parts, and more

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Options:

- 2 wheel brakes on swivel casters Code B5
- All swivel casters Code AS
- Floor lock Code F5
- Top shelf lips down (flush) Code FT
- Both shelves lips down (flush) Code FA
- Lockable drawer 5"h x 16"w x 16"d with 2 keys Code DS
- · Vinyl matting on top shelf Code VM
- · Other shelf heights available.

Product Features:

- All welded construction (except casters), with durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- · Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves 25".
- Overall height 35".
- · Powder coated gray finish.

SPECIFICATIONS

WxL	5	Wgt.		
(in)	Urethane	Thermorubber	Steel	(lbs)
18 x 24	SB124-U5	SB124-T5	SB124-L5	74
30	SB130-U5	SB130-T5	SB130-L5	80
36	SB136-U5	SB136-T5	SB136-L5	88
48	SB148-U5	SB148-T5	SB148-L5	102
24 x 24	SB224-U5	SB224-T5	SB224-L5	86
30	SB230-U5	SB230-T5	SB230-L5	96
36	SB236-U5	SB236-T5	SB236-L5	106
48	SB248-U5	SB248-T5	SB248-L5	126
60	SB260-U5	SB260-T5	SB260-L5	146
72	SB272-U5	SB272-T5	SB272-L5	168
30 x 36	SB336-U5	SB336-T5	SB336-L5	124
48	SB348-U5	SB348-T5	SB348-L5	148
60	SB360-U5	SB360-T5	SB360-L5	174
72	SB372-U5	SB372-T5	SB372-L5	198
36 x 48	SB448-U5	SB448-T5	SB448-L5	170
60	SB460-U5	SB460-T5	SB460-L5	200
72	SB472-U5	SB472-T5	SB472-L5	230

2 Shelf Vibration Reduction Carts (Pneumatic Casters)

Model SA - Transporter for items over irregular surfaces

1,200 LB CAPACITY



Options:

- 2 wheel brakes on swivel casters Code BN
- All swivel casters Code AS
- Floor lock Code F8 or FN
- Top shelf lips down (flush) Code FT
- Both shelves lips down (flush) Code FA
- Lockable drawer 5"h x 16"w x 16"d with 2 keys Code DS
- Vinyl matting on top shelf Code VM
- Other shelf heights available.

Product Features:

- All welded construction (except casters), with durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves 25".
- · Overall height 39".
- Powder coated gray finish.

SPECIFICATIONS

WxL	8" Casters Models						
(in)	Semi-Pneumatic	Full Pneumatic	Wgt.(lbs)				
24 x 30	SA230-Z8	SA230-N8	118				
36	SA236-Z8	SA236-N8	128				
48	SA248-Z8	SA248-N8	148				
60	SA260-Z8	SA260-N8	168				
72	SA272-Z8	SA272-N8	190				
30 x 36	SA336-Z8	SA336-N8	146				
48	SA348-Z8	SA348-N8	170				
60	SA360-Z8	SA360-N8	196				
72	SA372-Z8	SA372-N8	220				
36 x 48	SA448-Z8	SA448-N8	192				
60	SA460-Z8	SA460-N8	222				
72	SA472-Z8	SA472-N8	252				

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" \times 3" \times 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic
- Rubber
- Polyurethane
- Thermorubber
- · Steel (semi)
- Full Pneumatic
- · Semi Pneumatic

Brakes

Code

P6

R6

U6

T6

L6

8

Code

P8

R8

U8

T8

L8

Code

N8

N1

Z8

Mill

Code

MP

MS

Size (in)

6 x 2

6 x 2

6 x 2

6 x 2

6 x 2

8 x 2

8 x 2

8 x 2

8 x 2

8 x 2

Size (in)

8 x 3

12 x 4

8 x 3

N Series

Size (in)

Series

Pattern (in)

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

Duty Series

Bolt Hole

Pattern (in)

Pattern (in)

Bolt Hole

Pattern (in)

- Wing Brakes (Toe)
- Floor Lock

- Best rollability, high strength, hardest material.
- Best if floor has debris, quieter roll.
- Best if floor conditions vary, non-marking.
- Gray non-marking, soft rubber for quietest roll and best floor protection.
- High shock and impact resistant.
- Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Same as full pneumatic without maintenance of air.
- On swivel casters only, must be ordered with caster.
- Mount is welded in place, makes models not returnable.

Floor Lock



4 Series





Urethane Thermorubber

5 Series





Urethane Thermorubber





7, 6, & 8 Series





Mold On Rubber





Urethane

Thermorubber



Steel N Series





Full Pneumatic

Semi Pneumatic

Mill Duty Series





Phenolic

Steel

4.0	2.25.2.2			. ,			
4 5	eries—	Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	Bearing	(set of 4)	Locks	Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4
5 Series———————————————————————————————————							
	01100	Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	<u>Bearing</u>	(set of 4)	<u>Locks</u>	<u>Locks</u>
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5
7 Series—							
		Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	<u>Bearing</u>	(set of 4)	<u>Locks</u>	<u>Locks</u>
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7
6 S	eries—	B. 11.11.1.			0		D 1
		Bolt Hole			Capacity	Floor	Brake

Bearing

Roller

Roller

Roller

Roller

Roller

Bearing

Roller

Roller

Roller

Roller

Roller

Bearing

Bearing

Roller

Ball

Ball

Ball

Ball

(set of 4)

4.800 lbs

2,000 lbs

3,600 lbs

2,200 lbs

4,000 lbs

Capacity

(set of 4)

4.800 lbs

2,400 lbs

3,800 lbs

2,400 lbs

4,000 lbs

Capacity

(set of 4)

1,200 lbs

2,200 lbs

2.000 lbs

Capacity

(set of 4)

7,000 lbs

7,000 lbs

Locks

F6

F6

F6

F6

F6

Floor

Locks

F8

F8

F8

F8

F8

Floor

Locks

FN

N/A

F8

Floor

Locks

ML

ML

Locks

B6

B6

B6

B6

B6

Brake

Locks

B8

B8

B8

B8

B8

Brake

Locks

BN

N/A

BN

Brake

Locks

BM

BM

Wheel Material

Polyurethane

Steel (semi)

Thermorubber

Wheel Material

Rubber (Mold-on)

Polyurethane

Steel (semi)

Thermorubber

Wheel Material

Full Pneumatic

Full Pneumatic

Semi Pneumatic

Wheel Material

Phenolic

Steel

Phenolic

Rubber (Mold-on)

Phenolic

Size (in)

8 x 2-1/2

8 x 2-1/2