

3, 4, & 5 Shelf Stock Trucks

Models CC, CD, CE - Versatile heavy duty multiple shelf trucks

3,000 LB CAPACITY*
(*2,000 lb with rubber casters)



3,000 LB CAPACITY*
(*2,000 lb with rubber casters)

Model CC Shown



3,000 LB CAPACITY*
(*2,000 lb with rubber casters)

Model CD Shown



Model CE Shown

Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves - Model CC - 17", Model CD - 15" & Model CE - 13".
- Overall height - Model CC - 48", Model CD - 60" & Model CE - 68".
- Powder coated gray finish.

Options:

- Brakes on swivel casters - **Code B6**
- Floor lock - **Code F6**
- All shelves lips down - **Code FA**
- Fork lift pockets - 3" x 6" (specify center line) - **Code FP**

Model CC - 3 Shelf

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
18 x 36	CC136-P6	CC136-R6	CC136-U6	132
48	CC148-P6	CC148-R6	CC148-U6	154
24 x 36	CC236-P6	CC236-R6	CC236-U6	156
48	CC248-P6	CC248-R6	CC248-U6	186
60	CC260-P6	CC260-R6	CC260-U6	216
72	CC272-P6	CC272-R6	CC272-U6	246
30 x 36	CC336-P6	CC336-R6	CC336-U6	180
48	CC348-P6	CC348-R6	CC348-U6	216
60	CC360-P6	CC360-R6	CC360-U6	252
72	CC372-P6	CC372-R6	CC372-U6	288
36 x 48	CC448-P6	CC448-R6	CC448-U6	246
60	CC460-P6	CC460-R6	CC460-U6	290
72	CC472-P6	CC472-R6	CC472-U6	332

Model CD - 4 Shelf

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
18 x 36	CD136-P6	CD136-R6	CD136-U6	164
48	CD148-P6	CD148-R6	CD148-U6	194
24 x 36	CD236-P6	CD236-R6	CD236-U6	196
48	CD248-P6	CD248-R6	CD248-U6	234
60	CD260-P6	CD260-R6	CD260-U6	274
72	CD272-P6	CD272-R6	CD272-U6	314
30 x 36	CD336-P6	CD336-R6	CD336-U6	226
48	CD348-P6	CD348-R6	CD348-U6	274
60	CD360-P6	CD360-R6	CD360-U6	322
72	CD372-P6	CD372-R6	CD372-U6	370
36 x 48	CD448-P6	CD448-R6	CD448-U6	314
60	CD460-P6	CD460-R6	CD460-U6	372
72	CD472-P6	CD472-R6	CD472-U6	428

Model CE - 5 Shelf

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
18 x 36	CE136-P6	CE136-R6	CE136-U6	194
48	CE148-P6	CE148-R6	CE148-U6	232
24 x 36	CE236-P6	CE236-R6	CE236-U6	232
48	CE248-P6	CE248-R6	CE248-U6	282
60	CE260-P6	CE260-R6	CE260-U6	330
72	CE272-P6	CE272-R6	CE272-U6	380
30 x 36	CE336-P6	CE336-R6	CE336-U6	270
48	CE348-P6	CE348-R6	CE348-U6	330
60	CE360-P6	CE360-R6	CE360-U6	390
72	CE372-P6	CE372-R6	CE372-U6	450
36 x 48	CE448-P6	CE448-R6	CE448-U6	380
60	CE460-P6	CE460-R6	CE460-U6	450
72	CE472-P6	CE472-R6	CE472-U6	520

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber




Steel 7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



Steel N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel