

## 3 Shelf 2,400 lb Reinforced Service Carts

### Model SF - Extra durable carts for transporting heavy items

2,400 LB CAP.\*(\*2,000 lb with Rubber casters)



#### Options:

- 2 wheel brakes on swivel casters - Code B6
- Floor lock - Code F6
- All swivel casters - Code AS
- All shelves lips down (flush) - Code FA
- Vinyl matting on top shelf - Code VM
- Other heights available.

#### Product Features:

- All welded construction (except casters).
- Durable 12 gauge steel shelves with extra under bracing, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid - for easy replacement.
- 1-1/2" top shelf lips down (flush) and other shelves lips up.
- Clearance between shelves - 12"
- Overall height - 36"
- Powder coated gray finish.

#### SPECIFICATIONS

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 30	SF230-P6	SF230-R6	SF230-U6	142
	SF236-P6	SF236-R6	SF236-U6	158
	SF248-P6	SF248-R6	SF248-U6	192
	SF260-P6	SF260-R6	SF260-U6	224
	SF272-P6	SF272-R6	SF272-U6	256
30 x 36	SF336-P6	SF336-R6	SF336-U6	184
	SF348-P6	SF348-R6	SF348-U6	222
	SF360-P6	SF360-R6	SF360-U6	262
	SF372-P6	SF372-R6	SF372-U6	300
36 x 48	SF448-P6	SF448-R6	SF448-U6	254
	SF460-P6	SF460-R6	SF460-U6	300
	SF472-P6	SF472-R6	SF472-U6	346

## 3 Shelf 4,800 lb Reinforced Service Carts

### Model SK - Super heavy duty carts for transporting extra heavy loads

4,800 LB CAPACITY



#### Options:

- 2 wheel brakes on swivel casters - Code B8
- Floor lock - Code F8
- All swivel casters - Code AS
- All shelves lips down (flush) - Code FA
- Vinyl matting on top shelf - Code VM
- Ergonomic handle - Code EH
- Other heights available.

#### Product Features:

- All welded construction (except casters).
- Durable 12 gauge steel shelves with extra under bracing, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid - for easy replacement.
- 1-1/2" top shelf lips down (flush) and other shelves lips up.
- Clearance between shelves - 12"
- Overall height - 39"
- Powder coated gray finish.

#### SPECIFICATIONS

WxL (in)	8" Casters Models		Wgt. (lbs)
	Phenolic		
24 x 30	SK230-P8		172
	SK236-P8		194
	SK248-P8		236
	SK260-P8		278
	SK272-P8		320
30 x 36	SK336-P8		218
	SK348-P8		268
	SK360-P8		318
36 x 48	SK448-P8		298
	SK460-P8		356
	SK472-P8		412

## Casters For Steel Carts

**Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).**

### Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

### Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

### 4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

### 5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

### 7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

### 6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

### 8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

### N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

### Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

### Floor Lock



### 4 Series



Urethane Thermorubber

### 5 Series



Urethane Thermorubber



### Steel 7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



### Steel N Series



Full Pneumatic Semi Pneumatic

### Mill Duty Series



Phenolic Steel