

3 Shelf Reinforced Mobile Tables

Model LC, LD, LE - Heavy duty transporters between work areas

1,200 LB CAP.* (*800 lb. with T5 casters)



Model LC Shown

Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Bolt on casters, 2 swivel & 2 rigid for easy replacement.
- 1-1/2" shelf lips down (flush) on all shelves.
- Clearance between shelves - 9".
- Overall height:
 - Model LC - 30" (34" with 8" casters)
 - Model LD - 31"
 - Model LE - 33"
- Powder coated gray finish.

Options:

- 2 wheel brakes on swivel casters - **Code B5, B6, B8 or BN**
- All swivel casters - **Code AS**
- Floor lock - **Code F5, F6 or F8**
- Tubular push handle - **Code PH**
- Vinyl matting on top shelf - **Code VM**
- Other heights available.

2,400 LB CAP.*(*2,000 lb with Rubber casters)



Model LD Shown

Model LC - 1,200 lb Mobile Table with 3 Shelves

WxL (in)	5" Casters Models			8" Semi Pneumatic		
	Urethane	Thermorubber	Steel	Wgt. (lbs)	Models	Wgt. (lbs)
18 x 30	LC130-U5	LC130-T5	LC130-L5	100	LC130-Z8	124
	36 LC136-U5	LC136-T5	LC136-L5	112	LC136-Z8	136
	48 LC148-U5	LC148-T5	LC148-L5	132	LC148-Z8	156
24 x 30	LC230-U5	LC230-T5	LC230-L5	122	LC230-Z8	146
	36 LC236-U5	LC236-T5	LC236-L5	138	LC236-Z8	162
	48 LC248-U5	LC248-T5	LC248-L5	168	LC248-Z8	192
30 x 36	60 LC260-U5	LC260-T5	LC260-L5	198	LC260-Z8	222
	72 LC272-U5	LC272-T5	LC272-L5	230	LC272-Z8	254
	LC336-U5	LC336-T5	LC336-L5	162	LC336-Z8	186
36 x 48	48 LC348-U5	LC348-T5	LC348-L5	200	LC348-Z8	224
	60 LC360-U5	LC360-T5	LC360-L5	238	LC360-Z8	262
	72 LC372-U5	LC372-T5	LC372-L5	274	LC372-Z8	298
36 x 48	LC448-U5	LC448-T5	LC448-L5	232	LC448-Z8	256
	60 LC460-U5	LC460-T5	LC460-L5	276	LC460-Z8	300
	72 LC472-U5	LC472-T5	LC472-L5	320	LC472-Z8	344

4,800 LB CAPACITY



Model LE Shown

Model LD - 2,400 lb Reinforced Model LE - 4,800 lb Reinforced

WxL (in)	6" Casters Models			8" Casters Models		
	Phenolic	Rubber	Urethane	Wgt. (lbs)	Phenolic	Wgt. (lbs)
24 x 30	LD230-P6	LD230-R6	LD230-U6	142	LE230-P8	172
	36 LD236-P6	LD236-R6	LD236-U6	158	LE236-P8	194
	48 LD248-P6	LD248-R6	LD248-U6	192	LE248-P8	236
	60 LD260-P6	LD260-R6	LD260-U6	224	LE260-P8	278
30 x 36	72 LD272-P6	LD272-R6	LD272-U6	256	LE272-P8	320
	LD336-P6	LD336-R6	LD336-U6	184	LE336-P8	218
	48 LD348-P6	LD348-R6	LD348-U6	224	LE348-P8	268
	60 LD360-P6	LD360-R6	LD360-U6	262	LE360-P8	318
36 x 48	72 LD372-P6	LD372-R6	LD372-U6	302	LE372-P8	366
	LD448-P6	LD448-R6	LD448-U6	256	LE448-P8	300
	60 LD460-P6	LD460-R6	LD460-U6	302	LE460-P8	356
	72 LD472-P6	LD472-R6	LD472-U6	348	LE472-P8	412

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel 7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



Steel N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel