

2 Shelf Reinforced Mobile Tables

Model LX, LW, LM - Heavy duty transporters between work areas

2,400 LB CAP.*(*2,000 lb with Rubber casters)



Model LX Shown

4,800 LB CAPACITY



Model LW Shown

7,000 LB CAPACITY



Model LM Shown

Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves with under bracing**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use. (Models LX & LW).
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips down (flush) on both shelves.
- Clearance between shelves - 20" (Models LX & LW); 17" (Model LM).
- Overall height - 31" (Model LX); 33" (Model LW); 30" (Model LM) .
- Powder coated gray finish.

Other Specifications:

Model LM:

- Durable **12 gauge steel shelves super reinforced with channel underbracing and gusseted 3" angle corners 3/16" thick, 8" x 2" (1/4" thick) tubular caster mounts.**
- Mill duty casters, 8" x 2-1/2," in super heavy rig with roller bearings and grease zerks.
- Tubular handle with smooth radius bend.

Options:

- 2 wheel brakes on swivel casters - **Code B6, B8 or BM**
- All swivel casters - **Code AS**
- Floor lock - **Code F6, F8 or ML**
- Push handle - **Code PH** (Models LX & LW)
- Vinyl matting on top shelf - **Code VM**
- 6 caster option available (2 rigid in middle & 4 swivels on ends). (Model LM only)
- Other heights available.

Model LX - 2,400 lb Reinforced Mobile Table with 2 Shelves

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 30	LX230-P6	LX230-R6	LX230-U6	114
36	LX236-P6	LX236-R6	LX236-U6	126
48	LX248-P6	LX248-R6	LX248-U6	148
60	LX260-P6	LX260-R6	LX260-U6	170
72	LX272-P6	LX272-R6	LX272-U6	192
30 x 36	LX336-P6	LX336-R6	LX336-U6	142
48	LX348-P6	LX348-R6	LX348-U6	170
60	LX360-P6	LX360-R6	LX360-U6	198
72	LX372-P6	LX372-R6	LX372-U6	224
36 x 48	LX448-P6	LX448-R6	LX448-U6	192
60	LX460-P6	LX460-R6	LX460-U6	224
72	LX472-P6	LX472-R6	LX472-U6	256

Model LW - 4,800 lb Reinforced Mobile Table with 2 Shelves

WxL (in)	8" Casters Models		Wgt. (lbs)
	Phenolic		
24 x 30	LW230-P8		134
36	LW236-P8		148
48	LW248-P8		176
60	LW260-P8		204
72	LW272-P8		234
30 x 36	LW336-P8		166
48	LW348-P8		198
60	LW360-P8		232
72	LW372-P8		264
36 x 48	LW448-P8		220
60	LW460-P8		260
72	LW472-P8		296

Model LM - 7,000 lb Mill Duty Mobile Table with 2 Shelves

WxL (in)	8" Casters Models		Wgt. (lbs)
	Phenolic	Steel	
30 x 60	LM360-MP	LM360-MS	394
36 x 72	LM472-MP	LM472-MS	476

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel 7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



Steel N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel