



Model  
SC-3048-6PPY



Model  
SC-A-3048-6PPY

## HEAVY-DUTY

### Mobile Storage Locker

2000 lbs. Capacity

The small 3/4" x 1-1/2" diamond shaped openings and heavy gauge of the flattened expanded metal on this truck provide maximum security for even the smallest items, while still allowing good visibility and air circulation. The double doors swing open a full 270 degrees, back to the sides and out of the way, and have a padlockable slide latch. Interior height 48", overall height 56" with 2 swivel and 2 rigid, 6" x 2" non-marking polyurethane wheels.

Interior* D x W	No Center Shelf Model No.	Wt.	1 Center Shelf Model No.	Wt.	2 Center Shelves Model No.	Wt.
24 x 48	SCN-2448-6PPY	186	SC-2448-6PPY	216	SC2-2448-6PPY	246
24 x 60	SCN-2460-6PPY	196	SC-2460-6PPY	228	SC2-2460-6PPY	266
30 x 48	SCN-3048-6PPY	196	SC-3048-6PPY	230	SC2-3048-6PPY	267
30 x 60	SCN-3060-6PPY	245	SC-3060-6PPY	275	SC2-3060-6PPY	320
36 x 60	SCN-3660-6PPY	292	SC-3660-6PPY	345	SC2-3660-6PPY	420
36 x 72	SCN-3672-6PPY	350	SC-3672-6PPY	392	SC2-3672-6PPY	451

\* Note: For Outside Dimensions- Depth add 3", Width add 1"

## Adjustable Shelf Models

Mobile Storage Locker with one center shelf, adjustable on 3-1/2" centers. Shelf is also removable.

Interior* D x W	Model No.	Wt.
24 x 48	SC-A-2448-6PPY	242
24 x 60	SC-A-2460-6PPY	252
30 x 48	SC-A-3048-6PPY	258
30 x 60	SC-A-3060-6PPY	303

\* Note: For Outside Dimensions- Depth add 3", Width add 1"



Model  
SCN-3048-10SR



Model  
SC-A-3048-10SR

## Job Site Security Box

Heavy-duty security locker with 10" solid rubber tires permit easy rolling over rough surfaces such as construction sites or other less than perfect floors. Fully welded 1-1/2" angle frame and 13 gauge expanded metal secures your tools and supplies while providing good visibility. The doors open a full 270 degrees to allow complete access. Available with fixed height or adjustable height shelves. Padlockable slide latch keeps your items safe. Interior height 48", overall height 60". 1500 pounds total capacity.


Interior* D x W	No Center Shelf Model No.	Wt.	1 Center Shelf Model No.	Wt.	2 Center Shelves Model No.	Wt.
24 x 48	SCN-2448-10SR	198	SC-2448-10SR	228	SC2-2448-10SR	258
24 x 60	SCN-2460-10SR	208	SC-2460-10SR	240	SC2-2460-10SR	278
30 x 48	SCN-3048-10SR	208	SC-3048-10SR	242	SC2-3048-10SR	279

\* Note: For Outside Dimensions- Depth add 3", Width add 1"

## Adjustable Shelf Models

Interior* D x W	Model No.	Wt.
24 x 48	SC-A-2448-10SR	254
24 x 60	SC-A-2460-10SR	264
30 x 48	SC-A-3048-10SR	270

\* Note: For Outside Dimensions- Depth add 3", Width add 1"



## Wheel Selection Guide

### Polyurethane Wheels

**Load Capacity Range:**  
300 – 1,000 lbs.



**Characteristics:** Easier rolling for higher capacities, long lasting, chemical resistant, non-marking and quiet operation.

High strength polyurethane tread liquid cast and mechanically locked to a polymer or cast metal core. A polyurethane tread is superior for industrial, warehouse and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

### Phenolic Wheels

**Load Capacity Range:**  
900 – 1,250 lbs.



**Characteristics:** Best rolling for heavy load capacities, long lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. A cost effective wheel best used for high capacity industrial and warehouse applications. Hard tread wheel offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

### Mold-On Rubber Wheels

**Load Capacity Range:**  
500 – 600 lbs.



**Characteristics:** Better load capacity, long lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that easily and quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

### Solid Rubber Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire over plastic hub that is more stable and easier to roll under heavy loads than pneumatic wheels. Sometimes referred to as a semi-pneumatic tire, these wheels are a rugged, maintenance-free (no air pressure to fill and maintain) and are an alternative to pneumatic wheels.

### Pneumatic Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

Like an automotive tire, an air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress creating greater rolling resistance. Pneumatic wheels are ideal for handling fragile loads over rough surfaces.

### Flat Free Hand Truck Wheels

**Load Capacity Range:**  
300 lbs.



**Characteristics:** All of the benefits of a pneumatic wheel without losing air or going flat. This non-marking tire is composed of a dense microcellular polyurethane foam that performs like a pneumatic tire, cushioning the load and rolling over rough surfaces more easily. Upgraded precision ball bearing improves rollability and extends life.

## Wheel Specifications

Wheel Dia.	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Bearing I.D.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114		
6	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0620 WHMP-0620 WHPL-0620		
8	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0820 WHMP-0820 WHPL-0820		
8	2-1/2	Solid Rubber	3/4" Ball	WHSP-0825	5/8" Ball	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830		
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	5/8" Ball	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	5/8" Ball	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4 Microcellular Foam			5/8" Ball (Precision)	WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250		
12	3-1/2	Pneumatic 4.10/3.50-6 Pneumatic 4.10/3.50-6	5/8" Ball 1" Roller	WHPN-1235 WHPN-1235-RB		
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640		