

Heavy Duty Mobile Workbenches

Models MW, MX, MR, MT - Heavy duty use workbenches

1,200 LB CAP.* (*800 lb. with T5 casters)



Model MW Shown

1,200 LB CAP.* (*800 lb. with T5 casters)



Model MX Shown

1,200 LB CAP.* (*800 lb. with T5 casters)



Model MR Shown

1,200 LB CAP.* (*800 lb. with T5 casters)



Model MT Shown

Product Features:

- All welded construction.
- Durable 12 gauge steel shelves (ideal for mounting vises).
- 2" square tubular corner construction.
- Bolt on casters, 2 swivel with brakes & 2 rigid.
- Powder coated gray finish.
- Flush front, other 3 sides up for retention.
- Lower half shelf has 4" back support.
- Clearance between shelves - 22".
- Work surface height - 34".

Other Specifications:

Model MX:

- Upper tool half shelf 12" deep (14" high).
- 6 outlet power strip with 15 amp circuit breaker and 3 prong grounded 15 ft cord.
- Removable plastic bins (5-1/2"w x 11"d x 5"h) on mounting rail.
Length 60" - 10 Bins Length 72" - 12 Bins

Model MR:

- 14 gauge steel pegboard - 19" high

Model MT:

- 16 gauge louvered panel - 19" high • Bins sold separately.

Options:

- Adjustable heights - 34", 36", 38", 40" work surface - Code AL
- Lockable drawer (left side under top shelf)
5"h x 16"w x 16"d with 2 keys - Code DS
- Vinyl matting on top shelf - Code VM
- Wood capped top - Code WT
- Power strip - Code PS (except Model MX)
- 4' light fixture and frame - Code LF
- Plastic bins: (specify number of bins each size)
Large (8-1/4"w x 11"d x 7"h) - Code RB
Med. (5-1/2"w x 11"d x 5"h) - Code RC
Small (4-1/8"w x 7-1/2"d x 3"h) - Code RD



Optional 4' Light
Fixture & Frame
Code LF

Model MW - Mobile Workbench

DxW (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
30 x 60	MW360-U5-B5	MW360-T5-B5	MW360-L5-B5	172
72	MW372-U5-B5	MW372-T5-B5	MW372-L5-B5	196
36 x 60	MW460-U5-B5	MW460-T5-B5	MW460-L5-B5	188
72	MW472-U5-B5	MW472-T5-B5	MW472-L5-B5	214

Model MX - Mobile Workbench, 1/2 Shelf, Power Strip, Bins

DxW (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
30 x 60	MX360-U5-B5	MX360-T5-B5	MX360-L5-B5	236
72	MX372-U5-B5	MX372-T5-B5	MX372-L5-B5	268
36 x 60	MX460-U5-B5	MX460-T5-B5	MX460-L5-B5	250
72	MX472-U5-B5	MX472-T5-B5	MX472-L5-B5	286

Model MR - Mobile Workbench, Pegboard Panel

DxW (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
30 x 60	MR360-U5-B5	MR360-T5-B5	MR360-L5-B5	218
72	MR372-U5-B5	MR372-T5-B5	MR372-L5-B5	246
36 x 60	MR460-U5-B5	MR460-T5-B5	MR460-L5-B5	240
72	MR472-U5-B5	MR472-T5-B5	MR472-L5-B5	264

Model MT - Mobile Workbench, Louvered Panel

DxW (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
30 x 60	MT360-U5-B5	MT360-T5-B5	MT360-L5-B5	214
72	MT372-U5-B5	MT372-T5-B5	MT372-L5-B5	242
36 x 60	MT460-U5-B5	MT460-T5-B5	MT460-L5-B5	236
72	MT472-U5-B5	MT472-T5-B5	MT472-L5-B5	260

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel 7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



Steel N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel