## Rexford (RX) Series

Profile: Models in this series provide an ergonomic seating solution in a variety of workplace and learning spaces. Standard features are shown below.

Quick Reference Legend

= ESD

#### Work Environments:

- Healthcare
- Industrial
- Laboratory
- Education
- Static Control/ESD





Model shown with 28.7" diameter high-profile wide aluminum (W style) base, low seat height range. Baseline manufacturing code RXW-L-RC



Model shown with 25.6" diameter high-profile reinforced composite (R style) base, low seat height range. Baseline manufacturing code RXR-L-RC



Model shown with 23" diameter tubular steel (S style) base with 21" diameter affixed footring, low seat height range. Baseline manufacturing code RXS-L-RC



#### S Base Standard Affixed Footring Medium Seat Range Manufacturing Code: RXS-M-RC

Standard Affixed Footring High Seat Range Manufacturing Code: RXS-H-RC



#### A Base

on hard floors.

Optional Adjustable Footring Medium Seat Range Manufacturing Code: RXA-M-RC-ATF

user safety by inhibiting seating from rolling away

Optional Adjustable Footring High Seat Range Manufacturing Code: RXA-H-RC-ATF



#### R Base

Optional Adjustable Footring Medium Seat Range Manufacturing Code: RXR-M-RC-ATF

Optional Adjustable Footring High Seat Range Manufacturing Code: RXR-H-RC-ATF



### W Base

Optional Adjustable Footring Medium Seat Range Manufacturing Code: RXW-M-RC-ATF

Optional Adjustable Footring High Seat Range Manufacturing Code: RXW-H-RC-ATF

**Distributed by: Custom Equipment Company** 866-333-0728 sales@custommhs.com www.custommhs.com

# Rexford (RX) Series Options

Optional Com	ponents &	Upholstery	
Category	MFG Code	Description	Notes
Footring	AFP	Adjustable height, 22" diameter, oval tube construction on solid past aluminum spoke	Adjusts easily without knobs or levers; not available with low height models or units with S style base
	ATF	Adjustable height, 20" diameter, cast aluminum	Recommended for medium and high height models with A, W or R bases. Not available with low height models or units with S style base
Casters & Glides	HG	2" high Polyamide glides	
	GFR	Wide, dual-wheel casters for grated floors	Not available with ESD performance packages
	LKRO	Conductive dual-wheel casters that lock when seat is occupied	
	LRO	Dual-wheel casters that lock when seat is occupied	
	MLR	Dual-wheel, soft manual locking	
	RC	Hooded dual-wheel, non-marring resistance casters; lock when sunoccupied – standard on most models	eat is
	RK	Hooded dual-wheel, non-marring resistance casters for ESD app lock when seat is unoccupied	lications; Standard with ESD performance packages
Upholstery	СОМ		Contact BioFit for details
	Grade 2		Comes standard on upholstered models unless otherwise noted
	Grade 3		
	Grade 4		
	Grade 5		
Fire Retardant	C133	Special upholsteries, foam or barriers as needed to meet Califorr Bulletin 133 & Boston Fire Code; upholstery choices may be limit Minimums of Grade 2/3 fabric or Grade 3 vinyl are offered	
Miscellaneous	SW	Skid wrapping	
	VU	Upholstered underwrap to match seat upholstery	

Performance Packages		
Category	Class	MFG Code
ESD		K*
Optional Chrome-plated metal parts		С

<sup>\*</sup> Not available with R style base

# Seat Height Ranges & Manufacturing Codes

Rexford RX ( <b>RXS</b> ) - Tubular Steel			
Seat Height	MFG Code	Seat-Height Adjustment Range	
Low	RXS-L-RC	18"- 22"	
Medium	RXS-M-RC	21"- 28"	
High	RXS-H-RC	25"- 32"	

Rexford RX (RXA) - Cast Aluminum			
Seat Height	MFG Code	Seat-Height Adjustment Range	
Low	RXA-L-RC	17"- 22"	
Medium	RXA-M-RC	19"- 26"	
High	RXA-H-RC	22"- 32"	

Rexford RX (RXR) - Reinforced Composite			
Seat Height	MFG Code	Seat-Height Adjustment Range	
Low	RXR-L-RC	17"- 22"	
Medium	RXR-M-RC	19"- 26"	
High	RXR-H-RC	22"- 32"	

Rexford RX (RXV	<b>V</b> ) - Wide Aluminum	
Seat Height	MFG Code	Seat-Height Adjustment Range
Low	RXW-L-RC	17"- 22"
Medium	RXW-M-RC	19"- 26"
High	RXW-H-RC	22"- 32"