

Post Lift Tables - Hydraulic or Electromechanical

A simple, low-cost device for lifting, work positioning and transporting. Guide posts provide stability for the table top which is raised by a central cylinder. Hydraulic tables operate by foot pump. Electromechanical tables use a linear actuator powered by an onboard battery.



Post Lift Tables

Features

- 1000 - 3000 lb capacities
- Foot-operated hydraulic pump on P series
- 12V DC screw drive linear actuator with push-button control on BP series
- Foot-operated floor lock
- Integrated push/pull handle
- 2 fixed and 2 swivel casters with high-impact polyurethane wheels

Model Number	Load Capacity	Raised Height	Lowered Height	Platform Size	Shipping Weight
P18 Series - Foot-operated Tables					
P18-10	1000 lbs	49"	31"	20 x 30"	290 lbs
P18-20	2000 lbs	49"	31"	24 x 36"	300 lbs
P18-30	3000 lbs	49"	31"	24 x 36"	315 lbs
P12 Series - Foot-operated Tables					
P12-10	1000 lbs	37"	25"	20 x 30"	240 lbs
P12-20	2000 lbs	37"	25"	24 x 36"	250 lbs
P12-30	3000 lbs	37"	25"	24 x 36"	260 lbs
BP18 Series - Battery-operated Tables					
BP18-10	1000 lbs	52"	34"	20 x 30"	370 lbs
BP18-20	2000 lbs	52"	34"	24 x 36"	430 lbs
BP12 Series - Battery-operated Tables					
BP12-10	1000 lbs	37"	25"	20 x 30"	270 lbs
BP12-20	2000 lbs	37"	25"	24 x 36"	310 lbs



Mechanical Post Lift Tables

Four self-locking acme screw posts put the table top at the desired height and hold it there with no drift, even under maximum load (2,000 lb.). Height is adjusted by hand crank. Two crank (high and low speed) studs are located on both ends of the table.

Features

- 42" raised height
- Foot-operated floor lock
- 2 fixed and 2 swivel casters with high-impact polyurethane wheels



Mechanical Post Lift Tables

Model Number	Load Capacity	Raised Height	Lowered Height	Platform Size	Shipping Weight
P Series					
P2436	2000 lbs	42"	24"	24 x 36"	400 lbs
P2448	2000 lbs	42"	24"	24 x 48"	460 lbs
P3036	2000 lbs	42"	24"	30 x 36"	445 lbs
P3060	2000 lbs	42"	24"	30 x 60"	600 lbs

Hydraulic Cantilever Tables

Foot operated hydraulic lifts have an open area between the base legs and table top which allows access to hard to reach machine beds and work areas. The two-stage telescoping lift mechanism has hardened steel rollers to provide smooth lifting and lowering.

Features

- Dual floor locks
- Raised heights up to 60"
- Lowered heights down to 24"
- 2 fixed and 2 swivel casters with high-impact phenolic wheels
- Tip-toe release for lowering



Hydraulic Cantilever Tables

Model Number	Load Capacity	Raised Height	Lowered Height	Platform Size	Shipping Weight
PL Series					
PL36	2000 lbs	36"	24"	24 x 36"	315 lbs
PL48	2000 lbs	48"	30"	24 x 36"	330 lbs
PL60	2000 lbs	60"	36"	24 x 36"	350 lbs

AIS (Always In Stock) and ship within one week.

For More Information: 866-333-0728