

Standard Tilt Tables

These fixed height tilters can be mounted on legs, workbenches or directly on the floor. They are ideal for odd shaped or sized containers or odd loads. They are available with 30°, 45° or 60° of tilt and can handle loads up to 6,000 lbs.

Features

- 1000 - 6000 lb capacities standard
- Internal 1/2 HP 115/1/60 power unit
- Optional power units available
- Powered down cylinders on TT60
- Custom platforms available
- 8" standard lip, optional lips up to 24"
- Hand-held pendant control standard



Shown with optional 12" floor stand



Wide-Base Tilt Tables

Tilt table options on page 27

Model Number	Tilt Capacity	Lowered Height	Degree of Tilt	Standard Base	Standard Platform	Maximum Platform	Lifting Speed	Shipping Weight
TT30 Series								
TT30-10	1000 lbs	6-1/2"	30°	24 x 30"	24 x 36"	36 x 48"	15 sec	310 lbs
TT30-15	1500 lbs	6-1/2"	30°	24 x 30"	24 x 36"	36 x 48"	15 sec	325 lbs
TT30-20	2000 lbs	7-1/2"	30°	24 x 36"	24 x 36"	50 x 50"	10 sec	530 lbs
TT30-40	4000 lbs	7-1/2"	30°	24 x 36"	24 x 36"	50 x 50"	11 sec	520 lbs
TT30-60	6000 lbs	7-1/2"	30°	24 x 36"	24 x 36"	50 x 50"	14 sec	530 lbs
TT45 Series								
TT45-10	1000 lbs	6-1/2"	45°	24 x 30"	24 x 36"	36 x 48"	22 sec	310 lbs
TT45-15	1500 lbs	6-1/2"	45°	24 x 30"	24 x 36"	36 x 48"	22 sec	325 lbs
TT45-20	2000 lbs	7-1/2"	45°	24 x 36"	24 x 36"	50 x 50"	15 sec	510 lbs
TT45-40	4000 lbs	7-1/2"	45°	24 x 36"	24 x 36"	50 x 50"	16 sec	520 lbs
TT45-60	6000 lbs	7-1/2"	45°	24 x 36"	24 x 36"	50 x 50"	20 sec	530 lbs
TT60 Series								
TT60-10	1000 lbs	6-1/2"	60°	24 x 30"	24 x 36"	36 x 48"	30 sec	310 lbs
TT60-15	1500 lbs	6-1/2"	60°	24 x 30"	24 x 36"	36 x 48"	50 sec	325 lbs

Wide-Base Tilt Tables

The 36" wide base provides rigidity and stability making these tilt tables ideal for positioning larger containers or loads where greater side support is required. Platform sizes up to 60" x 60" are available.

Features

- Available with 30°, 45°, 60°, and 90° tilt
- Wide-Base models have an internal 1 HP 115/1/60 power unit
- Optional power units available
- Powered down cylinders on WT60 and WT90 series
- Custom platforms available
- 8" standard lip, optional lips up to 24"
- 12" lip standard on WT60 and WT90
- Can be mounted to the floor, on stands, or on scissor lifts. Please contact Sales
- Hand-held control standard
- Optional foot-control available
- For greater capacity or a larger platform size, custom designs are available

Model Number	Tilt Capacity	Lowered Height	Degree of Tilt	Standard Base	Standard Platform	Maximum Platform	Lifting Speed	Shipping Weight
WT30/45 Series								
WT30/45-20	2000 lbs	7-1/2"	30°/45°	36 x 42"	36 x 42"	60 x 60"	19/29 sec	590 lbs
WT30/45-40	4000 lbs	7-1/2"	30°/45°	36 x 42"	36 x 42"	60 x 60"	20/30 sec	610 lbs
WT30/45-60	6000 lbs	7-1/2"	30°/45°	36 x 42"	36 x 42"	60 x 60"	29/39 sec	630 lbs
WT60 Series								
WT60-20	2000 lbs	8-1/2"	60°	36 x 42"	36 x 42"	60 x 60"	40 sec	730 lbs
WT60-40	4000 lbs	8-1/2"	60°	36 x 42"	36 x 42"	60 x 60"	42 sec	750 lbs
WT60-60	6000 lbs	8-1/2"	60°	36 x 42"	36 x 42"	60 x 60"	55 sec	770 lbs
WT90 Series								
WT90-20	2000 lbs	8-1/2"	90°	36 x 42"	36 x 42"	60 x 60"	60 sec	730 lbs
WT90-40	4000 lbs	8-1/2"	90°	36 x 42"	36 x 42"	60 x 60"	64 sec	750 lbs
WT90-60	6000 lbs	8-1/2"	90°	36 x 42"	36 x 42"	60 x 60"	83 sec	770 lbs

Lift & Tilt Tables

Scissor Lift & Tilt

Lift height and tilt angle are controlled independently allowing operators to position loads precisely at the most comfortable height and working angle. Because the tilt cylinder is set into the lifting platform, the unit's lowered height is reduced.

Features

X3WT and X4WT Series

- One power unit for lift & tilt functions
- Internal 1 HP 115/1/60 power unit
- Standard pedestal controls
- Optional dual foot or hand controls available
- Choose 30° or 45° tilt

XLT Series

- Lift Power: 1 HP 115/1/60
- Tilt Power: 1 HP 115/1/60
- Standard dual hand or foot controls
- Optional pedestal controls available
- Choose 30° or 45° tilt
- 60° and 89° tilt models available



Model X3WT shown with standard pedestal control

Model Number	Load Capacity	Raised Height	Lowered Height	Degree of Tilt	Standard Base	Maximum Platform	Lifting Speed	Tilting Speed	Shipping Weight
X3WT Series									
X3WT36-20	2000 lbs	47-1/2"	11-1/2"	30°/45°	36 x 48"	60 x 60"	42 sec	8 sec	1370 lbs
X3WT36-40	4000 lbs	47-1/2"	11-1/2"	30°/45°	36 x 48"	60 x 60"	43 sec	8 sec	1420 lbs
X4WT Series									
X4WT36-20	2000 lbs	47-1/2"	11-1/2"	30°/45°	48 x 48"	72 x 60"	42 sec	8 sec	1450 lbs
X4WT36-40	4000 lbs	47-1/2"	11-1/2"	30°/45°	48 x 48"	72 x 60"	43 sec	8 sec	1500 lbs
XLT Series									
XLT36-10	1000 lbs	49-3/4"	13-3/4"	30°/45°	24 x 48"	48 x 48"	20 sec	15 sec	1000 lbs
XLT36-20	2000 lbs	50-3/4"	14-3/4"	30°/45°	24 x 48"	50 x 50"	30 sec	15 sec	1100 lbs
XLT36-40	4000 lbs	50-3/4"	14-3/4"	30°/45°	24 x 48"	50 x 50"	44 sec	15 sec	1350 lbs

Lift & Tilt tables are a great product to prevent excessive bending and reaching into containers. For Lift & Tilt applications however, it is always important to know the size of the load, including height, to help determine the load center of gravity as it moves through the tilt application. Please contact your sales coordinator when considering a Lift & Tilt unit for your customer's application.



Upenders

Upenders with 90° tilt are used to re-orient loads from horizontal to vertical positions. They are ideal for changing rolls or coils from "eye-to-the-sky" to "eye-to-horizon" quickly and easily without damage.

Model Number	Load Capacity	Bed/Low Height*	Platen Height*	Degree of Tilt	Maximum Platform	Maximum Platen	Standard Voltage
UT90 Series							
UT90-20	2000 lbs	25"	5"	90°	48 x 84"	48 x 48"	460/3/60
UT90-40	4000 lbs	25"	5"	90°	48 x 84"	48 x 48"	460/3/60
UT90-60	6000 lbs	25"	5"	90°	48 x 84"	48 x 48"	460/3/60

*when parallel to the floor



Upender shown with optional forks and V-cradle

Distributed by:
 Custom Equipment Company
 866-333-0728
 sales@custommhs.com

www.custommhs.com