

APPROX WEIGHT: 490.01 lbs.
DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!!

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ***

48 7/16"

47 5/8"

7"

2-PLACES

21 5/8"

58 13/16"

2"

2-PLACES

CASTERS
8"X2"
(2-SWIVEL
1 W/ LOCK,
2-RIGID)

16 1/4"

9 1/4"

59 1/4"

CENTER OF GRAVITY

LOAD CENTER

38 3/16"

26 7/16"

69"

17 13/16"

22 9/16"

33"

66 3/8"

DUMPED POSITION

DIMENSION TOLERANCE $\pm 1/4"$

*** UNIT MUST BE SECURED TO THE FORK TRUCK WHEN DUMPING ***

STANDARD FEATURES

*** UNIT MUST BE SECURED TO THE
FORK TRUCK WHEN DUMPING ***

MODEL # P-HOP-1.5
CAPACITY: 2,000 LBS.
VOLUME: 1 1/2 CU. YD.
USABLE WORK ENVELOPE: 58 13/16" X 66 3/8" X 69"
DUMP ANGLE: 90°
OVERALL WIDTH: 58 13/16"
OVERALL LENGTH: 59 1/4"
OVERALL HEIGHT: 47 5/8"
FORK POCKETS: 7" WIDE X 2" HIGH
CASTERS: 8"X2" (2-SWIVEL 1 W/ LOCK, 2-RIGID)
TOUGH BAKED IN POWDER COATED BLUE FINISH

NONE

NEVER EXCEED LOAD CENTER RATING PER FORK TRUCK
MANUFACTURER'S GUIDELINES. DO NOT USE THIS FORK TRUCK
ATTACHMENT IF LOAD WILL EXCEED FORK TRUCK
MANUFACTURER'S LOAD CENTER RATING.

**A
P
P
R
O
V
A
L**

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.

ANY MODIFIED UNITS ARE NON-RETURNABLE

☐ As drawn ☐ As marked

Signed: _____ Date: _____

Printed Name: _____

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

DISTRIBUTOR'S NAME:

P.O.#	X
-------	---

VESTIL MANUFACTURING

W.O.#	X
-------	---

DRAWN BY: W. STALEY

DATE: 9/15/08

SALES:	X
--------	---

REFERENCE: X

SCALE: 1:17

7 FILE NAME:

QUOTED LEAD TIME: X

QUOTE #	
X	

37-007-002

FOR INTERNAL USE ONLY
PROJECT SIGN OFF

SALES

ENG.

FAB.

POWER