

Job _____

GARMENT RACKS

Type 304 Stainless Steel and Proven Super Erecta® Construction Throughout.

- Floor-Mountable Upright and Wall Mount versions available.
- Open wire construction promotes laminar air flow.
- Electro-polished, Type 304 Stainless Steel hangers are included. Hangers are spaced at 3" (76mm) intervals.
- Unique hanger capture mechanism provides theft deterrance.
- Easy to assemble.
- Adjustable stainless steel triangular foot plates provided for floor mounting.
- Available in several sizes to suit your requirements.
- Upright unit is non-conductive, but can be made conductive with the addition of aluminum split sleeves (9986Z).

Floor Mount style is 74⁵/₈" tall. Wall Mount style is 7¹/₂" high.





Garment Wire: Wall Mount

| | | | Approx. | | | | Approx. | |
|--------------|----------|----------------|-----------|----------|-------|------------|------------|------|
| Width/Length | | | Model No. | Pkd. Wt. | | Model No. | Pkd. Wt. | |
| (in.) | (mm) | No. of Hangers | Upright | (lbs.) | (kg) | Wall Mount | (lbs.) | (kg) |
| 24x36 | 610x914 | 11 | GRU2436S | 27 | 12.25 | GRW2436S | 20 | 9 |
| 24x48 | 610x1219 | 15 | GRU2448S | 36 | 16.25 | GRW2448S | $22^{1/2}$ | 10.2 |
| 24x60 | 610x1524 | 19 | GRU2460S | 45 | 20.5 | GRW2460S | 271/2 | 12.5 |
| 24x72 | 610x1825 | 23 | GRU2472S | 54 | 24.5 | GRW2472S | 32 | 14.5 |

Distributed by: Custom Equipment Company 866-333-0728 sales@custommhs.com www.custommhs.com



