



# SHELF TRUCKS



**Model  
GL-2448-8MR**



Floor Lock Option, add: **-FL**  
Stops unwanted movement when loading or unloading


## Merchandise Collectors

2000 lbs. to 3600 lbs. Capacity

Shelves are formed from 12 gauge steel with structural angle corners and shelf reinforcements on shelves longer than 36". Shelves are available with 1-1/2" lip, or with flush edges. Raised offset handle includes cross brace hand guard for added safety. These welded units are shipped set up and ready for immediate use, with 2 swivel and 2 rigid casters. Shelf clearance 18" with lipped shelves, 19-1/2" with flush shelves.

Capacity & Wheels	Shelf Size WxL	Lip Edge Shelves Model No.	Flush Edge Shelves Model No.	Wt.
<b>8" x 2" Polyurethane w/Brakes</b> 3600 lbs. Top Shelf 32" H	24 x 36	GL-2436-8PYBK	G-2436-8PYBK	111
	24 x 48	GL-2448-8PYBK	G-2448-8PYBK	136
	30 x 48	GL-3048-8PYBK	G-3048-8PYBK	154
	30 x 60	GL-3060-8PYBK	G-3060-8PYBK	180
<b>8" x 2" Mold-on Rubber Tired</b> 2400 lbs. Top Shelf 32" H	24 x 36	GL-2436-8MR	G-2436-8MR	128
	24 x 48	GL-2448-8MR	G-2448-8MR	153
	30 x 48	GL-3048-8MR	G-3048-8MR	171
	30 x 60	GL-3060-8MR	G-3060-8MR	197
<b>6" x 2" Mold-on Rubber Tired</b> 2000 lbs. Top Shelf 30" H	24 x 36	GL-2436-6MR	G-2436-6MR	120
	24 x 48	GL-2448-6MR	G-2448-6MR	145
	30 x 48	GL-3048-6MR	G-3048-6MR	163
	30 x 60	GL-3060-6MR	G-3060-6MR	189

Flush Shelves



Lip Shelves

### Flush Shelves "G-"

Models have flush shelves for easier loading and unloading of larger, more bulky items.

### Lip Shelves "GL-"

Models feature 1-1/2" lip to retain small parts.



**Model  
G-2448-10SR**



9" x 3" Pneumatic Casters

## Cushion-Load Merchandise Collectors

Cushion-load casters for use over rough or uneven surfaces. Raised offset handle with cross brace hand guard for added safety. Heavy gauge shelves with 1-1/2" lip or flush edges. Shelf clearance 18" with lipped shelves, 19-1/2" with flush shelves. All-welded construction (except casters) with durable powder coated gray finish.

Capacity & Wheels	Shelf Size WxL	Lip Edge Shelves Model No.	Flush Edge Shelves Model No.	Wt.
<b>9" x 3" Pneumatic</b> 1200 lbs. Top Shelf 34" H	24 x 36	GL-2436-9P	G-2436-9P	95
	24 x 48	GL-2448-9P	G-2448-9P	109
	30 x 48	GL-3048-9P	G-3048-9P	127
	30 x 60	GL-3060-9P	G-3060-9P	143
<b>10" x 2.75" Puncture-Proof Rubber</b> 1500 lbs. Top Shelf 34-1/2"H	24 x 36	GL-2436-10SR	G-2436-10SR	104
	24 x 48	GL-2448-10SR	G-2448-10SR	118
	30 x 48	GL-3048-10SR	G-3048-10SR	136
	30 x 60	GL-3060-10SR	G-3060-10SR	152

Floor Lock Option, add: **-FL**



## Wheel Selection Guide

### Polyurethane Wheels

**Load Capacity Range:**  
300 – 1,000 lbs.



**Characteristics:** Easier rolling for higher capacities, long lasting, chemical resistant, non-marking and quiet operation.

High strength polyurethane tread liquid cast and mechanically locked to a polymer or cast metal core. A polyurethane tread is superior for industrial, warehouse and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

### Phenolic Wheels

**Load Capacity Range:**  
900 – 1,250 lbs.



**Characteristics:** Best rolling for heavy load capacities, long lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. A cost effective wheel best used for high capacity industrial and warehouse applications. Hard tread wheel offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

### Mold-On Rubber Wheels

**Load Capacity Range:**  
500 – 600 lbs.



**Characteristics:** Better load capacity, long lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that easily and quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

### Solid Rubber Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire over plastic hub that is more stable and easier to roll under heavy loads than pneumatic wheels. Sometimes referred to as a semi-pneumatic tire, these wheels are a rugged, maintenance-free (no air pressure to fill and maintain) and are an alternative to pneumatic wheels.

### Pneumatic Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

Like an automotive tire, an air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress creating greater rolling resistance. Pneumatic wheels are ideal for handling fragile loads over rough surfaces.

### Flat Free Hand Truck Wheels

**Load Capacity Range:**  
300 lbs.



**Characteristics:** All of the benefits of a pneumatic wheel without losing air or going flat. This non-marking tire is composed of a dense microcellular polyurethane foam that performs like a pneumatic tire, cushioning the load and rolling over rough surfaces more easily. Upgraded precision ball bearing improves rollability and extends life.

## Wheel Specifications

Wheel Dia.	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Bearing I.D.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114		
6	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0620 WHMP-0620 WHPL-0620		
8	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0820 WHMP-0820 WHPL-0820		
8	2-1/2	Solid Rubber	3/4" Ball	WHSP-0825	5/8" Ball	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830		
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	5/8" Ball	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	5/8" Ball	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4 Microcellular Foam			5/8" Ball (Precision)	WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250		
12	3-1/2	Pneumatic 4.10/3.50-6 Pneumatic 4.10/3.50-6	5/8" Ball 1" Roller	WHPN-1235 WHPN-1235-RB		
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640		