



Model
DET4-2448-6PY

2-Sided Shelf Trucks

Expanded metal ends improve visibility, allow 2-way access to material. End panels extend 48" high above deck. All-welded construction with 12 gauge steel shelves. Available in 2, 3 or 4 shelf configurations. Non-marking, quiet 6" polyurethane wheels, 2 swivel 2 rigid. Overall height 57". Capacity 3600 lbs.

| SHELF SIZE | 2 SHELVES 22-1/2" Clearance | | 3 SHELVES 15" Clearance | | 4 SHELVES 12" Clearance | |
|------------|--------------------------------|-----|----------------------------|-----|----------------------------|-----|
| | Model No. | Wt. | Model No. | Wt. | Model No. | Wt. |
| 24 x 48 | DET2-2448-6PY | 154 | DET3-2448-6PY | 196 | DET4-2448-6PY | 238 |
| 24 x 60 | DET2-2460-6PY | 175 | DET3-2460-6PY | 217 | DET4-2460-6PY | 269 |
| 30 x 48 | DET2-3048-6PY | 178 | DET3-3048-6PY | 229 | DET4-3048-6PY | 281 |
| 30 x 60 | DET2-3060-6PY | 204 | DET3-3060-6PY | 268 | DET4-3060-6PY | 332 |

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR** (2000 lbs. Capacity)



Model
DET2-A-2448-6PY

2-Sided Adjustable Shelf Truck

Expanded metal ends extend 48" high above the deck, improve visibility, and allow 2-way access to material. All-welded construction with 12 gauge steel shelves. Standard truck has one upper shelf that is adjustable on 3-1/2" centers, and can be positioned with 1-1/2" lips either up or down. Additional adjustable shelves also available. 2 swivel and 2 rigid casters with quiet, non-marking 6" polyurethane wheels. Overall height 57". Capacity 3600 lbs.

| Size W x D | Model No. | Wt. | Additional Shelf Model No. | Wt. |
|---------------|-----------------|-----|-------------------------------|-----|
| 24 x 48 | DET2-A-2448-6PY | 184 | SHLF-2447 | 43 |
| 24 x 60 | DET2-A-2460-6PY | 205 | SHLF-2459 | 53 |
| 30 x 48 | DET2-A-3048-6PY | 208 | SHLF-3047 | 53 |
| 30 x 60 | DET2-A-3060-6PY | 234 | SHLF-3059 | 65 |

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR** (2000 lbs. Capacity)



Model
PPT-2848-6M

Pick-Pack Truck

with sloped shelves and divider

Upper shelves are sloped, bottom shelf has 1-1/2" retaining lip. 14 gauge shelves have 14" shelf clearance. Diamond caster pattern with 6" x 2" Mold-On rubber casters, 1600 lbs. capacity.

| Size | Model No. | Shelf Size | Wt. |
|---------|-------------|------------|-----|
| 28 x 48 | PPT-2848-6M | 14 x 48 | 225 |
| 28 x 60 | PPT-2860-6M | 14 x 60 | 255 |



High End Truck with Removable Shelf

2000 lbs. Capacity

Narrow 16" wide 12 gauge steel deck is perfect for narrow aisles. Each corner has 5" polyurethane swivel wheels. Two 8" center wheels allow the unit to pivot within its own radius. All wheels are non-marking polyurethane. Two removable handles extend 48" above the deck to contain taller loads. The shelf can be mounted in three different heights (7-1/2", 21-1/2", 35-1/2" from the deck) on the upright cross braces. Shelf capacity 200 lbs.

| Size | Model No. | Wt. |
|---------|------------|-----|
| 16 x 48 | HE-1648-RS | 127 |
| 16 x 60 | HE-1660-RS | 142 |



Model
HE-1660-RS

High End 6-Wheeled Shelf Truck

Narrow width is ideal for busy aisles and two shelves create twice the loading area! 12 gauge shelves have 24" clearance. Six wheel design is fully maneuverable with two 8" x 2" rigid center wheels and four 5" swivel corner wheels. Non-marking polyurethane tread prevents wheel marks on your floor. End panels extend 48" high for extra capacity and are constructed from 1-1/2" x 3/16" slats for extra visibility. Capacity 2000 lbs.

| Size | Model No. | Wt. |
|---------|-----------|-----|
| 16 x 48 | HE2-1648 | 118 |
| 16 x 60 | HE2-1660 | 129 |
| 16 x 72 | HE2-1672 | 152 |
| 24 x 48 | HE2-2448 | 152 |
| 24 x 60 | HE2-2460 | 190 |



Model
HE2-2460

Narrow Aisle Order Picking Truck

2000 lbs. Capacity

Six wheel design creates a versatile two shelf truck that is perfect for use in warehouses and distribution centers where you need large capacity and zero turn maneuverability. The large writing shelf, measuring 21" wide and 12" deep, and storage pocket provide the work surface needed to fill out paperwork while picking orders. Constructed from 12 gauge steel and 1-1/2" angle, this workhorse is built to withstand the rigors of the most demanding facilities. The bottom shelf has 24" clearance and the end panels extend 48" above the deck. 8" rigid and 5" swivel non-marking polyurethane casters provide a smooth ride.

| Size | Model No. | Wt. |
|---------|--------------|-----|
| 24 x 48 | HE2-2448-WSP | 172 |
| 24 x 60 | HE2-2460-WSP | 210 |



Model
HE2-2460-WSP



Wheel Selection Guide

Polyurethane Wheels

Load Capacity Range:
300 – 1,000 lbs.



Characteristics: Easier rolling for higher capacities, long lasting, chemical resistant, non-marking and quiet operation.

High strength polyurethane tread liquid cast and mechanically locked to a polymer or cast metal core. A polyurethane tread is superior for industrial, warehouse and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

Phenolic Wheels

Load Capacity Range:
900 – 1,250 lbs.



Characteristics: Best rolling for heavy load capacities, long lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. A cost effective wheel best used for high capacity industrial and warehouse applications. Hard tread wheel offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

Mold-On Rubber Wheels

Load Capacity Range:
500 – 600 lbs.



Characteristics: Better load capacity, long lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that easily and quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

Solid Rubber Wheels

Load Capacity Range:
300 – 400 lbs.



Characteristics: Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire over plastic hub that is more stable and easier to roll under heavy loads than pneumatic wheels. Sometimes referred to as a semi-pneumatic tire, these wheels are a rugged, maintenance-free (no air pressure to fill and maintain) and are an alternative to pneumatic wheels.

Pneumatic Wheels

Load Capacity Range:
300 – 400 lbs.



Characteristics: Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

Like an automotive tire, an air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress creating greater rolling resistance. Pneumatic wheels are ideal for handling fragile loads over rough surfaces.

Flat Free Hand Truck Wheels

Load Capacity Range:
300 lbs.



Characteristics: All of the benefits of a pneumatic wheel without losing air or going flat. This non-marking tire is composed of a dense microcellular polyurethane foam that performs like a pneumatic tire, cushioning the load and rolling over rough surfaces more easily. Upgraded precision ball bearing improves rollability and extends life.

Wheel Specifications

| Wheel Dia. | Tread Width | Wheel Type | Bearing I.D. | Centered Hub Model No. | Bearing I.D. | Offset Hub Model No. |
|------------|-------------|--|------------------------|-------------------------------------|--------------------------|----------------------|
| 5 | 1-1/4 | Polyurethane | 3/8" Ball | WHMP-05114 | | |
| 6 | 2 | Mold-On Rubber Polyurethane Phenolic | Roller | WHMS-0620 WHMP-0620 WHPL-0620 | | |
| 8 | 2 | Mold-On Rubber Polyurethane Phenolic | Roller | WHMS-0820 WHMP-0820 WHPL-0820 | | |
| 8 | 2-1/2 | Solid Rubber | 3/4" Ball | WHSP-0825 | 5/8" Ball | WHSP-0825-0 |
| 9 | 3 | Pneumatic 2.80/2.50-4 | 5/8" Ball | WHPN-0830 | | |
| 10 | 2-3/4 | Solid Rubber | 5/8" Ball | WHSP-1027P-C | 5/8" Ball | WHSP-1027-P |
| 10 | 3-1/2 | Pneumatic 4.10/3.50-4 | 5/8" Ball | WHPN-1035-C | 5/8" Ball | WHPN-1035 |
| 10 | 3-1/2 | Flat Free 4.10/3.50-4 Microcellular Foam | | | 5/8" Ball (Precision) | WHFF-1035 |
| 12 | 2-1/2 | Mold-On Rubber | 1" Roller | WHMS-12250 | | |
| 12 | 3-1/2 | Pneumatic 4.10/3.50-6 Pneumatic 4.10/3.50-6 | 5/8" Ball 1" Roller | WHPN-1235 WHPN-1235-RB | | |
| 16 | 4 | Pneumatic 4.80/4.00-8 | 1" Roller | WHPN-1640 | | |