

3" Deep Lipped Service Carts (2 & 3 Shelf)

Models LT, EG, LN - Heavy Duty 3" deep lipped carts transporters

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Model LT Shown

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Model EG Shown

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Model LN Shown

Product Features:

- 3" shelf lips up for retention.
- All welded construction (except casters), with durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- Clearance between shelves: 22" (Models LT & EG), 9" (Model LN)
- Overall height (excluding handle) - 35", (39" with 8" casters).
- Powder coated gray finish.

Options:

- 2 wheel brakes on swivel casters - Code B5 or BN
- All swivel casters - Code AS
- Floor lock - Code F5 or F8
- Vinyl matting on top shelf - Code VM
- Writing stand - Code WS (Models LT & LN only)
- Lockable drawer 5"h x 16"w x 16"d with 2 keys - Code DS (Models LT & EG only)
- Other heights available.

Model LT - 2 Shelves, 3" Deep

WxL (in)	5" Casters Models				8" Semi-Pneumatic	
	Urethane	Thermorubber	Steel	Wgt. (lbs)	Models	Wgt. (lbs)
18 x 30	LT130-U5	LT130-T5	LT130-L5	90	LT130-Z8	112
36	LT136-U5	LT136-T5	LT136-L5	100	LT136-Z8	122
24 x 30	LT230-U5	LT230-T5	LT230-L5	106	LT230-Z8	128
36	LT236-U5	LT236-T5	LT236-L5	118	LT236-Z8	140
48	LT248-U5	LT248-T5	LT248-L5	140	LT248-Z8	162

Model EG - 2 Shelves, 3" Deep, Ergonomic Handle

WxL (in)	5" Casters Models				8" Semi-Pneumatic	
	Urethane	Thermorubber	Steel	Wgt. (lbs)	Models	Wgt. (lbs)
18 x 30	EG130-U5	EG130-T5	EG130-L5	92	EG130-Z8	114
36	EG136-U5	EG136-T5	EG136-L5	102	EG136-Z8	124
24 x 30	EG230-U5	EG230-T5	EG230-L5	108	EG230-Z8	130
36	EG236-U5	EG236-T5	EG236-L5	120	EG236-Z8	142
48	EG248-U5	EG248-T5	EG248-L5	142	EG248-Z8	164

Model LN - 3 Shelves, 3" Deep

WxL (in)	5" Casters Models				8" Semi-Pneumatic	
	Urethane	Thermorubber	Steel	Wgt. (lbs)	Models	Wgt. (lbs)
18 x 30	LN130-U5	LN130-T5	LN130-L5	120	LN130-Z8	142
36	LN136-U5	LN136-T5	LN136-L5	132	LN136-Z8	154
24 x 30	LN230-U5	LN230-T5	LN230-L5	142	LN230-Z8	164
36	LN236-U5	LN236-T5	LN236-L5	158	LN236-Z8	180
48	LN248-U5	LN248-T5	LN248-L5	192	LN248-Z8	214

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel
7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



Steel
N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel