

## Mobile Workbenches

**Models SR, ST, SV - Durable utility carts with flush front edge and 2 lockable drawers for repairs and maintenance**

**1,200 LB CAP.\*** (\*800 lb. with T5 casters)



Model SR Shown

**1,200 LB CAP.\*** (\*800 lb. with T5 casters)



Model ST Shown

**1,200 LB CAP.\*** (\*800 lb. with T5 casters)



Model SV Shown

**Product Features:**

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts.
- **Top shelf has front lip down for flush work area** and 3 lips up.
- **2 Lockable drawers** (keyed alike) with 2 keys - 5"h x 16"w x 16"d
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- Bottom shelf lips up for retention.
- Clearance under drawers - 17".
- Work surface height - 34" , (38" with 8" casters).
- Powder coated gray finish.

**Specific Model Features:**

**Model ST**

- 12" deep half shelf adds 14" to work surface height for tool box.

**Model SV**

- Tool tray is 10" deep x cart width.

**Options:**

- 2 wheel brakes on swivel casters - **Code B5 or BN**
- Floor lock - **Code F5 or FN**
- Non-conductive vinyl matting on top shelf - **Code VM**
- 6 outlet power strip with 15 amp circuit breaker and 3 prong grounded 15 ft cord with cord storage - **Code PS**
- Wood top - **Code WT**
- Locks keyed differently - **Code KS**
- Eye level half shelf (12 gauge) riser for Model SV only - **Code RS**

**Model SR - 2 Drawers**

WxL (in)	5" Casters Models				8" Full Pneumatic	
	Urethane	Thermorubber	Steel	Wgt. (lbs)	Models	Wgt. (lbs)
24 x 36	SR236-U5	SR236-T5	SR236-L5	162	SR236-N8	186
48	SR248-U5	SR248-T5	SR248-L5	182	SR248-N8	206
30 x 36	SR336-U5	SR336-T5	SR336-L5	180	SR336-N8	204
48	SR348-U5	SR348-T5	SR348-L5	204	SR348-N8	228

**Model ST - 2 Drawers & 1/2 Shelf**

WxL (in)	5" Casters Models				8" Full Pneumatic	
	Urethane	Thermorubber	Steel	Wgt. (lbs)	Models	Wgt. (lbs)
24 x 36	ST236-U5	ST236-T5	ST236-L5	194	ST236-N8	218
48	ST248-U5	ST248-T5	ST248-L5	220	ST248-N8	244
30 x 36	ST336-U5	ST336-T5	ST336-L5	210	ST336-N8	234
48	ST348-U5	ST348-T5	ST348-L5	242	ST348-N8	266

**Model SV - Tool Tray & 2 Drawers**

WxL (in)	5" Casters Models				8" Full Pneumatic	
	Urethane	Thermorubber	Steel	Wgt. (lbs)	Models	Wgt. (lbs)
24 x 36	SV236-U5	SV236-T5	SV236-L5	172	SV236-N8	196
48	SV248-U5	SV248-T5	SV248-L5	192	SV248-N8	216
30 x 36	SV336-U5	SV336-T5	SV336-L5	190	SV336-N8	214
48	SV348-U5	SV348-T5	SV348-L5	216	SV348-N8	240

## Casters For Steel Carts

**Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).**

### Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

### Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

### 4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

### 5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

### 7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

### 6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

### 8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

### N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

### Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

### Floor Lock



### 4 Series



Urethane Thermorubber

### 5 Series



Urethane Thermorubber



### Steel 7, 6, & 8 Series




Phenolic Mold On Rubber



Urethane Thermorubber



### Steel N Series



Full Pneumatic Semi Pneumatic

### Mill Duty Series



Phenolic Steel