

2 Shelf Order Picking Carts

Model SO - Rugged general use carts with built in writing stand for record keeping

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Product Features:

- All welded construction (except casters).
- **Writing stand** 12" by width of cart (4" above top shelf).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, 12 gauge caster mounts, and tubular handle with smooth radius bend.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves - 25".
- Overall height (excluding handle) - 35".
- Powder coated gray finish.

SPECIFICATIONS

WxL (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
18 x 30	S0130-U5	S0130-T5	S0130-L5	88
	S0136-U5	S0136-T5	S0136-L5	96
	S0148-U5	S0148-T5	S0148-L5	110
24 x 30	S0230-U5	S0230-T5	S0230-L5	106
	S0236-U5	S0236-T5	S0236-L5	116
	S0248-U5	S0248-T5	S0248-L5	136
60	S0260-U5	S0260-T5	S0260-L5	156
	S0272-U5	S0272-T5	S0272-L5	178
	S0336-U5	S0336-T5	S0336-L5	136
48	S0348-U5	S0348-T5	S0348-L5	162
	S0360-U5	S0360-T5	S0360-L5	186
	S0372-U5	S0372-T5	S0372-L5	210
36 x 48	S0448-U5	S0448-T5	S0448-L5	186
	S0460-U5	S0460-T5	S0460-L5	214
	S0472-U5	S0472-T5	S0472-L5	244

Options:

- 2 wheel brakes on swivel casters - **Code B5**
- All swivel casters - **Code AS**
- Floor lock - **Code F5**
- Vinyl matting on top shelf - **Code VM**
- Top shelf lips down (flush) - **Code FT**
- Both shelves lips down (flush) - **Code FA**
- Lockable drawer 5"h x 16"w x 16"d with 2 keys - **Code DS**
- Other heights available.

3 Shelf Order Picking Carts

Model LO - Rugged general use carts with built in writing stand for record keeping

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Product Features:

- All welded construction (except casters).
- **Writing stand** 12" by width of cart (4" above top shelf).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, 12 gauge caster mounts, and tubular handle with smooth radius bend.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves - 12".
- Overall height (excluding handle) - 35".
- Powder coated gray finish.

SPECIFICATIONS

WxL (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
18 x 30	L0130-U5	L0130-T5	L0130-L5	110
	L0136-U5	L0136-T5	L0136-L5	122
	L0148-U5	L0148-T5	L0148-L5	144
24 x 30	L0230-U5	L0230-T5	L0230-L5	134
	L0236-U5	L0236-T5	L0236-L5	150
	L0248-U5	L0248-T5	L0248-L5	180
60	L0260-U5	L0260-T5	L0260-L5	210
	L0272-U5	L0272-T5	L0272-L5	240
	L0336-U5	L0336-T5	L0336-L5	176
48	L0348-U5	L0348-T5	L0348-L5	214
	L0360-U5	L0360-T5	L0360-L5	252
	L0372-U5	L0372-T5	L0372-L5	288
36 x 48	L0448-U5	L0448-T5	L0448-L5	246
	L0460-U5	L0460-T5	L0460-L5	290
	L0472-U5	L0472-T5	L0472-L5	336

Taller order picking carts see page 76

Options:

- 2 wheel brakes on swivel casters - **Code B5**
- All swivel casters - **Code AS**
- Floor lock - **Code F5**
- Vinyl matting on top shelf - **Code VM**
- Top shelf lips down (flush) - **Code FT**
- All shelves lips down (flush) - **Code FA**
- Other heights available.

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel 7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



Steel N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel