# 3 Shelf Service Carts With Standard Handle

# Model SC - Rugged general use carts for transporting small packages, parts, & more

1,200 LB CAP\* (\*800 lb with Thermorubber casters)



## **Options:**

- 2 wheel brakes on swivel casters Code B5
- Floor lock Code F5
- · All swivel casters Code AS
- Top shelf lips down (flush) Code FT
- All shelves lips down (flush) Code FA
- · Vinyl matting on top shelf Code VM
- · Other heights available.

#### **Product Features:**

- · All welded construction (except casters).
- Durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- · Bolt on casters, 2 swivel & 2 rigid for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves 12"
- · Overall height 35".
- · Powder coated gray finish.

### **SPECIFICATIONS**

WxL	5	Wgt.		
(in)	Urethane	Thermorubber	Steel	(lbs)
18 x 24	SC124-U5	SC124-T5	SC124-L5	90
30	SC130-U5	SC130-T5	SC130-L5	102
36	SC136-U5	SC136-T5	SC136-L5	114
48	SC148-U5	SC148-T5	SC148-L5	134
24 x 30	SC230-U5	SC230-T5	SC230-L5	124
36	SC236-U5	SC236-T5	SC236-L5	138
48	SC248-U5	SC248-T5	SC248-L5	170
60	SC260-U5	SC260-T5	SC260-L5	200
72	SC272-U5	SC272-T5	SC272-L5	230
30 x 36	SC336-U5	SC336-T5	SC336-L5	164
48	SC348-U5	SC348-T5	SC348-L5	200
60	SC360-U5	SC360-T5	SC360-L5	238
72	SC372-U5	SC372-T5	SC372-L5	274
36 x 48	SC448-U5	SC448-T5	SC448-L5	232
60	SC460-U5	SC460-T5	SC460-L5	276
72	SC472-U5	SC472-T5	SC472-L5	320

# 3 Shelf Vibration Reduction Carts (Pneumatic Casters)

# Model LH - Transporter for items over irregular surfaces

## 1,200 LB CAPACITY



#### Options:

- · 2 wheel brakes on swivel casters Code BN
- Floor lock Code F8 or FN
- All swivel casters Code AS
- Top shelf lips down (flush) Code FT
- All shelves lips down (flush) Code FA
- Ergonomic handle Code EH
- Vinyl matting on top shelf Code VM
- · Other heights available.

## **Product Features:**

- All welded construction (except casters).
- Durable 12 gauge steel shelves, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- · Bolt on casters, 2 swivel & 2 rigid for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves 12"
- · Overall height 39".
- · Powder coated gray finish.

#### **SPECIFICATIONS**

WxL	8" Casters				
(in)	Semi Models	Full Models	Wgt.(lbs)		
24 x 30	LH230-Z8	LH230-N8	146		
36	LH236-Z8	LH236-N8	162		
48	LH248-Z8	LH248-N8	192		
60	LH260-Z8	LH260-N8	222		
72	LH272-Z8	LH272-N8	252		
30 x 36	LH336-Z8	LH336-N8	186		
48	LH348-Z8	LH348-N8	224		
60	LH360-Z8	LH360-N8	260		
72	LH372-Z8	LH372-N8	298		
36 x 48	LH448-Z8	LH448-N8	254		
60	LH460-Z8	LH460-N8	300		
72	LH472-Z8	LH472-N8	344		

# **Casters For Steel Carts**

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4"  $\times$  3"  $\times$  3" bolt hole patterns (unless otherwise noted).

### **Wheel Characteristics**

- Phenolic
- Rubber
- Polyurethane
- Thermorubber
- · Steel (semi)
- Full Pneumatic
- · Semi Pneumatic

#### **Brakes**

Code

**P6** 

R6

U6

**T6** 

L6

8

Code

**P8** 

R8

U8

**T8** 

L8

Code

N8

N1

**Z8** 

Mill

Code

MP

MS

Size (in)

6 x 2

6 x 2

6 x 2

6 x 2

6 x 2

8 x 2

8 x 2

8 x 2

8 x 2

8 x 2

Size (in)

8 x 3

12 x 4

8 x 3

**N** Series

Size (in)

Series

Pattern (in)

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

**Duty Series** 

**Bolt Hole** 

Pattern (in)

Pattern (in)

**Bolt Hole** 

Pattern (in)

- Wing Brakes (Toe)
- Floor Lock

- Best rollability, high strength, hardest material.
- Best if floor has debris, quieter roll.
- Best if floor conditions vary, non-marking.
- Gray non-marking, soft rubber for quietest roll and best floor protection.
- High shock and impact resistant.
- Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Same as full pneumatic without maintenance of air.
- On swivel casters only, must be ordered with caster.
- Mount is welded in place, makes models not returnable.

# Floor Lock



4 Series





Urethane Thermorubber

5 Series





Urethane Thermorubber





7, 6, & 8 Series





Mold On Rubber





Urethane

Thermorubber



Steel N Series





Full Pneumatic

Semi Pneumatic

Mill Duty Series





Phenolic

Steel

4.0	2.25.2.2			. ,			
4 5	eries—	Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	<b>Bearing</b>	(set of 4)	<b>Locks</b>	<b>Locks</b>
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4
5 Series———————————————————————————————————							
	01100	<b>Bolt Hole</b>			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	<u>Bearing</u>	(set of 4)	<u>Locks</u>	<u>Locks</u>
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5
7 Series———————————————————————————————————							
		Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	<u>Bearing</u>	(set of 4)	<u>Locks</u>	<u>Locks</u>
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7
6 S	eries—	B. 11.11.1.			0		D 1
		Bolt Hole			Capacity	Floor	Brake

**Bearing** 

Roller

Roller

Roller

Roller

Roller

**Bearing** 

Roller

Roller

Roller

Roller

Roller

**Bearing** 

**Bearing** 

Roller

Ball

Ball

Ball

Ball

(set of 4)

4.800 lbs

2,000 lbs

3,600 lbs

2,200 lbs

4,000 lbs

Capacity

(set of 4)

4.800 lbs

2,400 lbs

3,800 lbs

2,400 lbs

4,000 lbs

Capacity

(set of 4)

1,200 lbs

2,200 lbs

2.000 lbs

Capacity

(set of 4)

7,000 lbs

7,000 lbs

**Locks** 

F6

F6

F6

F6

F6

Floor

Locks

F8

F8

F8

F8

F8

**Floor** 

**Locks** 

FN

N/A

F8

**Floor** 

**Locks** 

ML

ML

**Locks** 

**B6** 

**B6** 

B6

**B6** 

**B6** 

Brake

Locks

B8

**B8** 

**B8** 

**B8** 

**B8** 

**Brake** 

**Locks** 

BN

N/A

BN

**Brake** 

Locks

BM

BM

**Wheel Material** 

**Polyurethane** 

Steel (semi)

Thermorubber

**Wheel Material** 

Rubber (Mold-on)

**Polyurethane** 

Steel (semi)

Thermorubber

**Wheel Material** 

**Full Pneumatic** 

**Full Pneumatic** 

Semi Pneumatic

**Wheel Material** 

Phenolic

Steel

Phenolic

Rubber (Mold-on)

Phenolic

Size (in)

8 x 2-1/2

8 x 2-1/2