

Stainless Steel Platforms, Low Profile & Transfer Carts

Models XP, YP, XL, YB - Stainless steel platforms & low profile & transfer carts

Product Features:

- All welded construction (except casters).
- **Stainless with premium polished shelves and decks** in durable **16 gauge**.
- 1-1/2" stainless corner angles (Models XL & YB only), and stainless caster mounts.
- Bolt on casters, 2 swivel & 2 rigid, for superior tracking.
- Caster rigs available in steel or stainless for urethane wheels and steel only for semi pneumatic wheels.
- **Tubular handle** with smooth radius bend for comfort and uniform appearance -30" handle height above platform (XP & YP); raised offset handle (XL).
- 1-1/2" shelf lips down (flush) for easy loading. Model XL bottom shelf has 1-1/2" shelf lips up for retention.

Cart shelf/platform deck dimensions:

| Model | Top Shelf/Deck Height | Clearance Between Shelves |
|-------|-----------------------|---------------------------|
| XP | 9" | N/A |
| YP | 9" | N/A |
| XL | 27" | 17" |
| YB | 30" | 20" |

*Add 4" to height for Z8 casters

Options:

- 2 wheel brakes on swivel casters - Caster Type**Brake Code**
 - U5.....**B5**
 - S5.....**BX**
 - Z8.....**BN**
- All swivel casters - **Code AS**
- Vinyl matting on top shelf - **Code VM**
- Front leg "L" bumpers (XL&YB only) - **Code LB**
- Middle shelf (YB only) - **Code SM**
- Thermorubber casters available.

Model XP - Platform - Removable Handle

| WxL (in) | 5" Urethane Casters Model | | | 8" Casters Model | |
|----------|---------------------------|---------------|------------|------------------|------------|
| | Steel Rig | Stainless Rig | Wgt. (lbs) | Semi Pneumatic | Wgt. (lbs) |
| 18 x 30 | XP130-U5 | XP130-S5 | 46 | XP130-Z8 | 70 |
| 36 | XP136-U5 | XP136-S5 | 48 | XP136-Z8 | 72 |
| 24 x 36 | XP236-U5 | XP236-S5 | 54 | XP236-Z8 | 78 |
| 48 | XP248-U5 | XP248-S5 | 60 | XP248-Z8 | 84 |
| 30 x 48 | XP348-U5 | XP348-S5 | 68 | XP348-Z8 | 92 |
| 60 | XP360-U5 | XP360-S5 | 74 | XP360-Z8 | 98 |

Model YP - Platform - 2 Removable Handles

| WxL (in) | 5" Urethane Casters Model | | | 8" Casters Model | |
|----------|---------------------------|---------------|------------|------------------|------------|
| | Steel Rig | Stainless Rig | Wgt. (lbs) | Semi Pneumatic | Wgt. (lbs) |
| 18 x 30 | YP130-U5 | YP130-S5 | 52 | YP130-Z8 | 76 |
| 36 | YP136-U5 | YP136-S5 | 54 | YP136-Z8 | 78 |
| 24 x 36 | YP236-U5 | YP236-S5 | 60 | YP236-Z8 | 84 |
| 48 | YP248-U5 | YP248-S5 | 66 | YP248-Z8 | 90 |
| 30 x 48 | YP348-U5 | YP348-S5 | 74 | YP348-Z8 | 98 |
| 60 | YP360-U5 | YP360-S5 | 80 | YP360-Z8 | 104 |

Model XL - Low Profile - Raised Offset Handle

| WxL (in) | 5" Urethane Casters Model | | | 8" Casters Model | |
|----------|---------------------------|---------------|------------|------------------|------------|
| | Steel Rig | Stainless Rig | Wgt. (lbs) | Semi Pneumatic | Wgt. (lbs) |
| 18 x 30 | XL130-U5 | XL130-S5 | 56 | XL130-Z8 | 80 |
| 36 | XL136-U5 | XL136-S5 | 60 | XL136-Z8 | 84 |
| 24 x 36 | XL236-U5 | XL236-S5 | 70 | XL236-Z8 | 94 |
| 48 | XL248-U5 | XL248-S5 | 82 | XL248-Z8 | 106 |
| 30 x 48 | XL348-U5 | XL348-S5 | 94 | XL348-Z8 | 118 |
| 60 | XL360-U5 | XL360-S5 | 108 | XL360-Z8 | 132 |

Model YB - Transfer Cart

| WxL (in) | 5" Urethane Casters Model | | | 8" Casters Model | |
|----------|---------------------------|---------------|------------|------------------|------------|
| | Steel Rig | Stainless Rig | Wgt. (lbs) | Semi Pneumatic | Wgt. (lbs) |
| 18 x 24 | YB124-U5 | YB124-S5 | 50 | YB124-Z8 | 74 |
| 30 | YB130-U5 | YB130-S5 | 54 | YB130-Z8 | 78 |
| 36 | YB136-U5 | YB136-S5 | 58 | YB136-Z8 | 82 |
| 24 x 36 | YB236-U5 | YB236-S5 | 68 | YB236-Z8 | 92 |
| 48 | YB248-U5 | YB248-S5 | 80 | YB248-Z8 | 104 |
| 30 x 48 | YB348-U5 | YB348-S5 | 92 | YB348-Z8 | 116 |
| 60 | YB360-U5 | YB360-S5 | 106 | YB360-Z8 | 130 |

1,200 LB CAPACITY



Model XP Shown

1,200 LB CAPACITY



Model YP Shown

1,200 LB CAPACITY



Model XL Shown

1,200 LB CAPACITY



Model YB Shown