

Stainless Steel 2 & 3 Shelf Standard & Ergonomic Handle Carts

Models XB, XA, XS, XT - Stainless steel standard & ergonomic handles

1,200 LB CAPACITY



Model XB Shown

1,200 LB CAPACITY



Model XA Shown

1,200 LB CAPACITY



Model XS Shown

1,200 LB CAPACITY



Model XT Shown

Product Features:

- All welded construction (except casters).
- **Stainless with premium polished shelves in durable 16 gauge.**
- 1-1/2" stainless corner angles, and stainless caster mounts.
- Bolt on casters, 2 swivel & 2 rigid, for superior tracking.
- Caster rigs available in steel or stainless for urethane wheels and steel only for semi pneumatic wheels.
- **Tubular handle with smooth radius bend - standard (XA & XB), raised ergonomic (XS & XT).**
- 1-1/2" shelf lips up for retention.
- Overall height (excluding handle) is 35", 39" (with 8" casters).
- Clearance between shelves - 25" (Models XB & XS); 11" (Models XA & XT).

Options:

- 2 wheel brakes on swivel casters -
Caster Type Brake Code
U5 B5
S5 BX
Z8 BN
- All swivel casters - **Code AS**
- Vinyl matting on top shelf - **Code VM**
- Front leg "L" bumpers - **Code LB**
- Lockable stainless drawer (4-1/4" h x 16" w x 16" d) with 2 keys (Models XB & XS) - **Code DZ**

Model XB - Standard Handle - 2 Shelf

WxL (in)	5" Urethane Casters Model			8" Casters Model	
	Steel Rig	Stainless Rig	Wgt. (lbs)	Semi Pneumatic	Wgt. (lbs)
18 x 24	XB124-U5	XB124-S5	52	XB124-Z8	76
30	XB130-U5	XB130-S5	56	XB130-Z8	80
36	XB136-U5	XB136-S5	60	XB136-Z8	84
24 x 36	XB236-U5	XB236-S5	70	XB236-Z8	94
48	XB248-U5	XB248-S5	82	XB248-Z8	106
30 x 48	XB348-U5	XB348-S5	94	XB348-Z8	118
60	XB360-U5	XB360-S5	108	XB360-Z8	132

Model XA - Standard Handle - 3 Shelf

WxL (in)	5" Urethane Casters Model			8" Casters Model	
	Steel Rig	Stainless Rig	Wgt. (lbs)	Semi Pneumatic	Wgt. (lbs)
18 x 24	XA124-U5	XA124-S5	60	XA124-Z8	84
30	XA130-U5	XA130-S5	66	XA130-Z8	90
36	XA136-U5	XA136-S5	72	XA136-Z8	96
24 x 36	XA236-U5	XA236-S5	86	XA236-Z8	110
48	XA248-U5	XA248-S5	104	XA248-Z8	128
30 x 48	XA348-U5	XA348-S5	122	XA348-Z8	146
60	XA360-U5	XA360-S5	142	XA360-Z8	166

Model XS - Ergonomic Handle - 2 Shelf

WxL (in)	5" Urethane Casters Model			8" Casters Model	
	Steel Rig	Stainless Rig	Wgt. (lbs)	Semi Pneumatic	Wgt. (lbs)
18 x 24	XS124-U5	XS124-S5	48	XS124-Z8	72
30	XS130-U5	XS130-S5	54	XS130-Z8	78
36	XS136-U5	XS136-S5	60	XS136-Z8	84
24 x 36	XS236-U5	XS236-S5	70	XS236-Z8	94
48	XS248-U5	XS248-S5	82	XS248-Z8	106
30 x 48	XS348-U5	XS348-S5	94	XS348-Z8	118
60	XS360-U5	XS360-S5	108	XS360-Z8	132

Model XT - Ergonomic Handle - 3 Shelf

WxL (in)	5" Urethane Casters Model			8" Casters Model	
	Steel Rig	Stainless Rig	Wgt. (lbs)	Semi Pneumatic	Wgt. (lbs)
18 x 24	XT124-U5	XT124-S5	60	XT124-Z8	84
30	XT130-U5	XT130-S5	68	XT130-Z8	92
36	XT136-U5	XT136-S5	76	XT136-Z8	100
24 x 36	XT236-U5	XT236-S5	88	XT236-Z8	112
48	XT248-U5	XT248-S5	106	XT248-Z8	130
30 x 48	XT348-U5	XT348-S5	124	XT348-Z8	148
60	XT360-U5	XT360-S5	144	XT360-Z8	168

Casters For Stainless Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Rig	Wheel Material	Bearing	Capacity (set of 4)	Brake Locks
T4	4 x 1-1/4	1-3/4 x 3	Steel	Thermorubber	Ball	800 lbs	B4
S4	4 x 1-1/4	1-3/4 x 3	Stainless	Thermorubber	Ball	800 lbs	BV

4 Series



Urethane Thermorubber

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Rig	Wheel Material	Bearing	Capacity (set of 4)	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Steel	Polyurethane	Ball	1,200 lbs	B5
T5	5 x 1-1/4	1-3/4 x 3	Steel	Thermorubber	Ball	800 lbs	B5
S5	5 x 1-1/4	1-3/4 x 3	Stainless	Polyurethane	Ball	1,200 lbs	BX
ST	5 x 1-1/4	1-3/4 x 3	Stainless	Thermorubber	Ball	800 lbs	BX

5 Series



Urethane Thermorubber

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Rig	Wheel Material	Bearing	Capacity (set of 4)	Brake Locks
U6	6 x 2	3 x 3	Steel	Polyurethane	Roller	3,600 lbs	B6
T6	6 x 2	3 x 3	Steel	Thermorubber	Roller	2,200 lbs	B6
S6	6 x 2	3 x 3	Stainless	Polyurethane	Roller	3,600 lbs	BY

6 Series



Urethane Thermorubber

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Rig	Wheel Material	Bearing	Capacity (set of 4)	Brake Locks
N8	8 x 3	3 x 3	Steel	Pneumatic	Roller	1,200 lbs	BN
Z8	8 x 3	3 x 3	Steel	Thermorubber	Ball	2,200 lbs	BN

N Series



Full Pneumatic Semi Pneumatic