

## 4 Shelf 3 Sided Mesh Trucks

### Model ZD - Heavy duty trucks with visual sides for large packages

**3,000 LB CAPACITY\***

(\*2,000 lb with rubber casters)



Model ZD Shown

**Options:**

- 2 wheel brakes on swivel casters - **Code B6**
- Floor lock (centered on handle end) - **Code F6**
- Three sides flattened 13 gauge expanded mesh 5' high - **Code SF**
- Ergonomic handle - **Code EH**
- All shelves lips down (flush) - **Code FA**
- Fork lift pockets - 3" x 6" (specify center line) - **Code FP**

**Product Features:**

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- **Limited access one side.**
- **Three sides flattened 13 gauge expanded mesh 4' high.**
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves - 13".
- Overall height - 57".
- Powder coated gray finish.

**SPECIFICATIONS**

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 36	ZD236-P6	ZD236-R6	ZD236-U6	226
48	ZD248-P6	ZD248-R6	ZD248-U6	270
60	ZD260-P6	ZD260-R6	ZD260-U6	314
72	ZD272-P6	ZD272-R6	ZD272-U6	360
30 x 48	ZD348-P6	ZD348-R6	ZD348-U6	316
60	ZD360-P6	ZD360-R6	ZD360-U6	368
72	ZD372-P6	ZD372-R6	ZD372-U6	422
36 x 48	ZD448-P6	ZD448-R6	ZD448-U6	360
60	ZD460-P6	ZD460-R6	ZD460-U6	422
72	ZD472-P6	ZD472-R6	ZD472-U6	484

## Adjustable Shelf 3 Sided Mesh Trucks

### Model ZR - Adjustable shelf trucks with visual sides for large packages

**3,000 LB CAPACITY\***

(\*2,000 lb with rubber casters)



Model ZR Shown  
With Option FA

**Options:**

- 2 wheel brakes on swivel casters - **Code B6**
- Floor lock (centered on handle end) - **Code F6**
- Three sides flattened 13 gauge expanded mesh 5' high - **Code SF**
- Ergonomic handle - **Code EH**
- Fork lift pockets - 3" x 6" (specify center line) - **Code FP**
- Additional adjustable shelves - **Code AT**

**Product Features:**

- All welded construction (except casters and adjustable shelf).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- **Limited access one side.**
- **Three sides flattened 13 gauge expanded mesh 4' high.**
- **Adjustable middle shelf** is standard - adjustable on 3-1/2" centers.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention on bottom shelf only, adjustable shelf is flush only.
- Overall height - 57".
- Powder coated gray finish.

**SPECIFICATIONS**

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 36	ZR236-P6	ZR236-R6	ZR236-U6	184
48	ZR248-P6	ZR248-R6	ZR248-U6	208
60	ZR260-P6	ZR260-R6	ZR260-U6	234
72	ZR272-P6	ZR272-R6	ZR272-U6	258
30 x 48	ZR348-P6	ZR348-R6	ZR348-U6	236
60	ZR360-P6	ZR360-R6	ZR360-U6	264
72	ZR372-P6	ZR372-R6	ZR372-U6	292
36 x 48	ZR448-P6	ZR448-R6	ZR448-U6	262
60	ZR460-P6	ZR460-R6	ZR460-U6	294
72	ZR472-P6	ZR472-R6	ZR472-U6	328

## Casters For Steel Carts

**Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).**

### Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

### Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

### 4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

### 5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

### 7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

### 6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

### 8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

### N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

### Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

### Floor Lock



### 4 Series



Urethane Thermorubber

### 5 Series



Urethane Thermorubber



### Steel 7, 6, & 8 Series




Phenolic Mold On Rubber



Urethane Thermorubber



### Steel N Series



Full Pneumatic Semi Pneumatic

### Mill Duty Series



Phenolic Steel