

Adjustable Sheet & Panel Trucks

Models PG, TE, PO - Heavy duty steel transporters for upright panels and sheets

2,000 LB CAPACITY



Model PG Shown

2,000 LB CAPACITY



Model TE Shown

2,000 LB CAPACITY



Model PO Shown

Product Features:

- All welded construction (except casters and removable dividers).
- Durable **12 gauge steel platform**, and 12 gauge caster mounts for long lasting use.
- **6 removable 1-1/4" tubular dividers** with smooth radius bend for safety and uniform appearance.
2 each: 12" high, 24" high, 36" high.
- **7 divider sockets** at each end.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- Platform flush for easy load and unload.
- Deck height - 9", (12" with 8" casters)
- Model TE - carpeted rails add 2" to deck height
- Model PO - wood cap adds 1" to deck height
- Overall height - 45", (48" with 8" casters).
- Powder coated gray finish.

Other Specifications:

Model TE

- Durable 12 gauge steel platform, with - 3" x 2" carpeted rails.

Model PO

- Durable 12 gauge steel platform, capped with 3/4" sealed plywood.

Options:

- 2 wheel brakes on swivel casters - **Code B6 or BN**
- All swivel casters - **Code AS**
- Floor lock - **Code F6 or F8**

Model PG - Steel Deck

| WxL (in) | 6" Casters Models | | | | 8" Semi Pneumatic | |
|----------|-------------------|----------|----------|------------|-------------------|------------|
| | Phenolic | Rubber | Urethane | Wgt. (lbs) | Models | Wgt. (lbs) |
| 24 x 36 | PG236-P6 | PG236-R6 | PG236-U6 | 142 | PG236-Z8 | 152 |
| 48 | PG248-P6 | PG248-R6 | PG248-U6 | 166 | PG248-Z8 | 176 |
| 60 | PG260-P6 | PG260-R6 | PG260-U6 | 190 | PG260-Z8 | 200 |
| 72 | PG272-P6 | PG272-R6 | PG272-U6 | 214 | PG272-Z8 | 224 |
| 30 x 36 | PG336-P6 | PG336-R6 | PG336-U6 | 150 | PG336-Z8 | 160 |
| 48 | PG348-P6 | PG348-R6 | PG348-U6 | 176 | PG348-Z8 | 186 |
| 60 | PG360-P6 | PG360-R6 | PG360-U6 | 204 | PG360-Z8 | 214 |
| 72 | PG372-P6 | PG372-R6 | PG372-U6 | 230 | PG372-Z8 | 240 |
| 36 x 48 | PG448-P6 | PG448-R6 | PG448-U6 | 188 | PG448-Z8 | 198 |
| 60 | PG460-P6 | PG460-R6 | PG460-U6 | 216 | PG460-Z8 | 226 |
| 72 | PG472-P6 | PG472-R6 | PG472-U6 | 246 | PG472-Z8 | 256 |

Model TE - Steel Deck, Carpeted Rails

| WxL (in) | 6" Casters Models | | | | 8" Semi Pneumatic | |
|----------|-------------------|----------|----------|------------|-------------------|------------|
| | Phenolic | Rubber | Urethane | Wgt. (lbs) | Models | Wgt. (lbs) |
| 30 x 36 | TE336-P6 | TE336-R6 | TE336-U6 | 156 | TE336-Z8 | 166 |
| 48 | TE348-P6 | TE348-R6 | TE348-U6 | 184 | TE348-Z8 | 194 |
| 60 | TE360-P6 | TE360-R6 | TE360-U6 | 210 | TE360-Z8 | 220 |
| 72 | TE372-P6 | TE372-R6 | TE372-U6 | 236 | TE372-Z8 | 246 |

Model PO - Steel Deck, Wood Capped

| WxL (in) | 6" Casters Models | | | | 8" Semi Pneumatic | |
|----------|-------------------|----------|----------|------------|-------------------|------------|
| | Phenolic | Rubber | Urethane | Wgt. (lbs) | Models | Wgt. (lbs) |
| 24 x 36 | P0236-P6 | P0236-R6 | P0236-U6 | 156 | P0236-Z8 | 166 |
| 48 | P0248-P6 | P0248-R6 | P0248-U6 | 184 | P0248-Z8 | 194 |
| 30 x 60 | P0360-P6 | P0360-R6 | P0360-U6 | 234 | P0360-Z8 | 244 |
| 36 x 60 | P0460-P6 | P0460-R6 | P0460-U6 | 260 | P0460-Z8 | 270 |
| 72 | P0472-P6 | P0472-R6 | P0472-U6 | 290 | P0472-Z8 | 300 |

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

4 Series

| Code | Size (in) | Bolt Hole Pattern (in) | Wheel Material | Bearing | Capacity (set of 4) | Floor Locks | Brake Locks |
|------|-----------|------------------------|----------------|---------|---------------------|-------------|-------------|
| U4 | 4 x 1-1/4 | 1-3/4 x 3 | Polyurethane | Ball | 1,200 lbs | N/A | B4 |
| T4 | 4 x 1-1/4 | 1-3/4 x 3 | Thermorubber | Ball | 800 lbs | N/A | B4 |

5 Series

| Code | Size (in) | Bolt Hole Pattern (in) | Wheel Material | Bearing | Capacity (set of 4) | Floor Locks | Brake Locks |
|------|-----------|------------------------|----------------|---------|---------------------|-------------|-------------|
| U5 | 5 x 1-1/4 | 1-3/4 x 3 | Polyurethane | Ball | 1,200 lbs | F5 | B5 |
| T5 | 5 x 1-1/4 | 1-3/4 x 3 | Thermorubber | Ball | 800 lbs | F5 | B5 |
| L5 | 5 x 1-1/4 | 1-3/4 x 3 | Steel (semi) | Plain | 1,200 lbs | F5 | B5 |

7 Series

| Code | Size (in) | Bolt Hole Pattern (in) | Wheel Material | Bearing | Capacity (set of 4) | Floor Locks | Brake Locks |
|------|-----------|------------------------|------------------|---------|---------------------|-------------|-------------|
| P7 | 5 x 2 | 3 x 3 | Phenolic | Roller | 4,000 lbs | F7 | B7 |
| R7 | 5 x 2 | 3 x 3 | Rubber (Mold-on) | Roller | 1,800 lbs | F7 | B7 |
| U7 | 5 x 2 | 3 x 3 | Polyurethane | Roller | 3,000 lbs | F7 | B7 |
| T7 | 5 x 2 | 3 x 3 | Thermorubber | Roller | 2,000 lbs | F7 | B7 |
| L7 | 5 x 2 | 3 x 3 | Steel (semi) | Roller | 4,000 lbs | F7 | B7 |

6 Series

| Code | Size (in) | Bolt Hole Pattern (in) | Wheel Material | Bearing | Capacity (set of 4) | Floor Locks | Brake Locks |
|------|-----------|------------------------|------------------|---------|---------------------|-------------|-------------|
| P6 | 6 x 2 | 3 x 3 | Phenolic | Roller | 4,800 lbs | F6 | B6 |
| R6 | 6 x 2 | 3 x 3 | Rubber (Mold-on) | Roller | 2,000 lbs | F6 | B6 |
| U6 | 6 x 2 | 3 x 3 | Polyurethane | Roller | 3,600 lbs | F6 | B6 |
| T6 | 6 x 2 | 3 x 3 | Thermorubber | Roller | 2,200 lbs | F6 | B6 |
| L6 | 6 x 2 | 3 x 3 | Steel (semi) | Roller | 4,000 lbs | F6 | B6 |

8 Series

| Code | Size (in) | Bolt Hole Pattern (in) | Wheel Material | Bearing | Capacity (set of 4) | Floor Locks | Brake Locks |
|------|-----------|------------------------|------------------|---------|---------------------|-------------|-------------|
| P8 | 8 x 2 | 3 x 3 | Phenolic | Roller | 4,800 lbs | F8 | B8 |
| R8 | 8 x 2 | 3 x 3 | Rubber (Mold-on) | Roller | 2,400 lbs | F8 | B8 |
| U8 | 8 x 2 | 3 x 3 | Polyurethane | Roller | 3,800 lbs | F8 | B8 |
| T8 | 8 x 2 | 3 x 3 | Thermorubber | Roller | 2,400 lbs | F8 | B8 |
| L8 | 8 x 2 | 3 x 3 | Steel (semi) | Roller | 4,000 lbs | F8 | B8 |

N Series

| Code | Size (in) | Bolt Hole Pattern (in) | Wheel Material | Bearing | Capacity (set of 4) | Floor Locks | Brake Locks |
|------|-----------|------------------------|----------------|---------|---------------------|-------------|-------------|
| N8 | 8 x 3 | 3 x 3 | Full Pneumatic | Roller | 1,200 lbs | FN | BN |
| N1 | 12 x 4 | 3 x 3 | Full Pneumatic | Ball | 2,200 lbs | N/A | N/A |
| Z8 | 8 x 3 | 3 x 3 | Semi Pneumatic | Ball | 2,000 lbs | F8 | BN |

Mill Duty Series

| Code | Size (in) | Bolt Hole Pattern (in) | Wheel Material | Bearing | Capacity (set of 4) | Floor Locks | Brake Locks |
|------|-----------|------------------------|----------------|---------|---------------------|-------------|-------------|
| MP | 8 x 2-1/2 | 3 x 3 | Phenolic | Ball | 7,000 lbs | ML | BM |
| MS | 8 x 2-1/2 | 3 x 3 | Steel | Ball | 7,000 lbs | ML | BM |

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



Steel N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel