



Model  
G-2448-10SR

## Cushion-Load Merchandise Collectors

1200 lbs. to 1500 lbs. Capacity

Cushion-load casters for use over rough or uneven surfaces. Heavy gauge shelves with 1-1/2" lip or flush edges. Shelf clearance 18" with lipped shelves, 19-1/2" with flush shelves. Durable powder coated gray finish.

Capacity & Wheels	Shelf Size WxL	LIP SHELVES Model No.	FLUSH SHELVES Model No.	Wt.
9" x 3" Pneumatic 1200 lbs. Top Shelf 34" H	24 x 36	GL-2436-9P	G-2436-9P	95
	24 x 48	GL-2448-9P	G-2448-9P	109
	30 x 48	GL-3048-9P	G-3048-9P	127
10" x 2.75" Puncture-Proof Rubber 1500 lbs. Top Shelf 34-1/2"H	24 x 36	GL-2436-10SR	G-2436-10SR	104
	24 x 48	GL-2448-10SR	G-2448-10SR	118
	30 x 48	GL-3048-10SR	G-3048-10SR	136
	30 x 60	GL-3060-10SR	G-3060-10SR	152



Model  
2G-2448-6PHBK

## Heavy-Duty Shelf Truck

3600 lbs. Capacity

12 gauge shelves handle the heaviest of loads. Shelves available with flush edges, or with 1-1/2" retaining lips. 2 swivel and 2 rigid casters with 6" x 2" hard tread phenolic wheels for added maneuverability under heavy loads. Swivel casters have wheel brakes to stop unwanted movement when loading and unloading. 36" overall height.



Model  
3G-2436-6PHBK

	W x L x H	LIP SHELVES 24" Clearance	FLUSH SHELVES 25-1/2" Clearance	Wt.
2 Shelf	24 x 36 x 36	2GL-2436-6PHBK	2G-2436-6PHBK	112
	24 x 48 x 36	2GL-2448-6PHBK	2G-2448-6PHBK	138
	30 x 48 x 36	2GL-3048-6PHBK	2G-3048-6PHBK	154
	30 x 60 x 36	2GL-3060-6PHBK	2G-3060-6PHBK	182
	W x L x H	LIP SHELVES 11" Clearance	FLUSH SHELVES 12" Clearance	Wt.
3 Shelf	24 x 36 x 36	3GL-2436-6PHBK	3G-2436-6PHBK	156
	24 x 48 x 36	3GL-2448-6PHBK	3G-2448-6PHBK	185
	30 x 48 x 36	3GL-3048-6PHBK	3G-3048-6PHBK	201
	30 x 60 x 36	3GL-3060-6PHBK	3G-3060-6PHBK	251

For 6" Mold-on Rubber with Brakes, add wheel code: **-6MRBK** (2000 lbs. Capacity)

For 6" Polyurethane with Brakes, add wheel code: **-6PYBK** (3600 lbs. Capacity)

Floor Lock Option, add: **-FL**



Model  
2GL6W-2448-6PH

## 6 Wheeled Heavy-Duty Shelf Truck

3600 lbs. Capacity

Designed for improved mobility, this all-welded shelf truck features 12 gauge steel shelves available flush or with 1-1/2" retaining lips. 4 swivel and 2 rigid 6" x 2" hard tread phenolic casters provide high maneuverability with a tighter turning radius. Durable powder coated gray finish. 36" Top Shelf Height.



Model  
3G6W-2448-6PH

	Shelf Size	LIP SHELVES 24" Clearance Model No.	Wt.	FLUSH SHELVES 25-1/2" Clearance	Wt.
2 Shelf	24 x 36	2GL6W-2436-6PH	132	2G6W-2436-6PH	132
	24 x 48	2GL6W-2448-6PH	158	2G6W-2448-6PH	158
	30 x 48	2GL6W-3048-6PH	176	2G6W-3048-6PH	176
	30 x 60	2GL6W-3060-6PH	204	2G6W-3060-6PH	204
	Shelf Size	LIP SHELVES 11" Clearance Model No.	Wt.	FLUSH SHELVES 12" Clearance	Wt.
3 Shelf	24 x 36	3GL6W-2436-6PH	176	3G6W-2436-6PH	176
	24 x 48	3GL6W-2448-6PH	205	3G6W-2448-6PH	205
	30 x 48	3GL6W-3048-6PH	231	3G6W-3048-6PH	231
	30 x 60	3GL6W-3060-6PH	273	3G6W-3060-6PH	273



## Wheel Selection Guide

### Polyurethane Wheels

**Load Capacity Range:**  
300 – 1,000 lbs.



**Characteristics:** Easier rolling for higher capacities, long-lasting, chemical resistant, non-marking and quiet operation.

A polyurethane tread is superior for industrial, warehouse, and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

### Phenolic Wheels

**Load Capacity Range:**  
900 – 1,250 lbs.



**Characteristics:** Best rolling for heavy load capacities, long-lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. Offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

### Mold-On Rubber Wheels

**Load Capacity Range:**  
500 – 600 lbs.



**Characteristics:** Better load capacity, long-lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

### Solid Rubber Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire that is more stable and easier to roll under heavy loads than pneumatic wheels. These wheels are a rugged, maintenance-free (no air pressure to maintain) alternative to pneumatic wheels.

### Pneumatic Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

An air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress, creating greater rolling resistance. Ideal for handling fragile loads over rough surfaces.

### Flat Free Hand Truck Wheels

**Load Capacity Range:**  
400 lbs.



**Characteristics:** Wide rubber tread disperses the load better over irregular or softer surfaces. Less tread compression than pneumatic or solid rubber tires and ball bearings improve rollability of heavier loads.

## Wheel Specifications

Wheel Diameter	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114	-
6	2	Mold-On Rubber	3/4" Roller	WHMS-0620	-
		Polyurethane	1/2" Ball	WHMP-0620	-
		Phenolic	3/4" Roller	WHPL-0620	-
8	2	Mold-On Rubber	3/4" Roller	WHMS-0820	-
		Polyurethane	1/2" Ball	WHMP-0820	-
		Phenolic	3/4" Roller	WHPL-0820	-
8	2-1/2	Solid Rubber	5/8" Ball	-	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830	-
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4	5/8" Ball		WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250	-
12	3-1/2	Pneumatic 4.10/3.50-6	5/8" Ball	WHPN-1235	-
		Pneumatic 4.10/3.50-6	1" Roller	WHPN-1235-RB	-
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640	-