

Mobile Tables

1000 lbs. Capacity

All-welded steel construction means years of rugged service and no assembly. This single shelf model with open style cross-arm base serves as a workbench where seating is required. This mobile table has a 34" overall height and features 4 swivel casters for increased mobility and 5" non-marking polyurethane wheels with wheel brakes.

Size	Model No.	Wt.
18 x 32	IP-1832RM-BRK	59
24 x 36	IP-2436RM-BRK	65
24 x 48	IP-2448RM-BRK	77
24 x 60	IP-2460RM-BRK	94
30 x 48	IP-3048RM-BRK	92
30 x 60	IP-3060RM-BRK	104
30 x 72	IP-3072RM-BRK	118



Available with Total Lock Casters replace -BRK with -TL

Model
IP-2448RM-BRK



Mobile Tables – 2 Shelf

1000 lbs. and 3600 lbs. Capacity

All-welded, 12 gauge steel construction. Available with either 5" or 6" non-marking polyurethane casters. 4 swivel casters provide increased mobility. 34" overall height. Available in a 1200 lb. capacity (24-1/2" shelf clearance) or 3600 lb. capacity (23" shelf clearance). Durable gray powder coated finish. Ships set up and ready for immediate use.

Size	1200 LBS. CAPACITY 4 Swivel Casters		3600 LBS. CAPACITY 4 Swivel Casters		3600 LBS. CAPACITY 2 Rigid 2 Swivel/w Floor Lock	
	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
18 x 32	IP-1832-2	67	-	-	-	-
24 x 36	IP-2436-2	87	IP-2436-2-6PY	113	IP2436-2R-6PYFL	118
24 x 48	IP-2448-2	107	IP-2448-2-6PY	133	IP2448-2R-6PYFL	138
24 x 60	IP-2460-2	127	IP-2460-2-6PY	144	IP2460-2R-6PYFL	164
30 x 48	IP-3048-2	125	IP-3048-2-6PY	154	IP3048-2R-6PYFL	159
30 x 60	IP-3060-2	151	IP-3060-2-6PY	179	IP3060-2R-6PYFL	184
30 x 72	IP-3072-2	177	IP-3072-2-6PY	193	IP3072-2R-6PYFL	223
36 x 72	-	-	IP-3672-2-6PY	233	IP3672-2R-6PYFL	238

Wheel Brakes: 5" add: -BRK; 6" add: -BK

Total Lock Casters: add: -TL (5" only)



Model
IP-2448-2-6PY



Model
IP2448-2R-6PYFL

Mobile Tables – 3 Shelf


All-welded, heavy-duty, 12 gauge construction, this mobile table is built to last. 3 shelves for plenty of additional storage. Available with 5" or 6" non-marking polyurethane wheels. 4 swivel casters provide greater maneuverability. Available in a 1200 lb. capacity (11" shelf clearance) or 3600 lb. capacity (10-1/2" shelf clearance). 34" overall height with durable powder coated finish.

Size	1200 LBS. CAPACITY 4 Swivel Casters		3600 LBS. CAPACITY 4 Swivel Casters		3600 LBS. CAPACITY 2 Rigid 2 Swivel/w Floor Lock	
	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
24 x 36	3IP-2436-5PY	124	3IP-2436-6PY	150	3IP2436-2R6PYFL	155
24 x 48	3IP-2448-5PY	154	3IP-2448-6PY	180	3IP2448-2R6PYFL	185
24 x 60	3IP-2460-5PY	186	3IP-2460-6PY	203	3IP2460-2R6PYFL	208
30 x 48	3IP-3048-5PY	182	3IP-3048-6PY	210	3IP3048-2R6PYFL	215
30 x 60	-	-	3IP-3060-6PY	249	3IP3060-2R6PYFL	254

Wheel Brakes: 5" add: -BRK; 6" add: -BK



Model
3IP-2448-6PY



Model
IPH-3060-8PHBK

Extra-Heavy-Duty 7 Gauge Mobile Table

5000 lbs. Capacity

Top is formed from 7 gauge steel and reinforced with 2" angle iron to withstand the most punishing applications. 2" angle corner posts and additional side braces increase stability. Special heavy service casters to handle extra capacity. Maneuvers on 4 swivel casters with 8" x 2" phenolic wheels and wheel brakes. Overall height 34".

W x L	Model No.	Wt.
30 x 48	IPH-3048-8PHBK	211
30 x 60	IPH-3060-8PHBK	237
36 x 60	IPH-3660-8PHBK	261
36 x 72	IPH-3672-8PHBK	290




Model
IPG2448-8PHFLPL

Heavy-Duty Mobile Table

5000 lbs. Capacity

Formed 12 gauge shelves with extra reinforcement are welded to 2" x 2" corner angles. Special heavy-duty king-pinless casters. Four swivel casters provide maximum maneuverability. Two 4-position swivel locks on one end will convert swivel casters into rigid. Floor lock on other end prevents unwanted movement when necessary. Overall height 36". Powder coated finish.

Overall W x D	Model No.	Wt.
24 x 36	IPG2436-8PHFLPL	160
24 x 48	IPG2448-8PHFLPL	175
24 x 60	IPG2460-8PHFLPL	185
30 x 48	IPG3048-8PHFLPL	193
30 x 60	IPG3060-8PHFLPL	219
30 x 72	IPG3072-8PHFLPL	259
36 x 72	IPG3672-8PHFLPL	280



4 Position Swivel Lock



Floor Lock



Model
IP-2448-9PM

Mobile Instrument Table

1200 lbs. Capacity

Maneuvers over rough surfaces with 4 swivel casters and 9" pneumatic wheels. Available with non-slip vinyl shelf surfaces, or smooth steel. Welded construction for maximum durability. Top shelf height 34", shelf clearance 19-1/2". Powder coated gray finish.

Shelf Size	Model No.	Wt.
Non-Slip Vinyl Shelf Surfaces		
24 x 36	IP-2436-9PM	96
24 x 48	IP-2448-9PM	112
30 x 48	IP-3048-9PM	131
Without Vinyl Shelf Surfaces		
24 x 36	IP-2436-9P	92
24 x 48	IP-2448-9P	107
30 x 48	IP-3048-9P	124

Wheel brakes on swivel casters option, add: **-BK**



Wheel Selection Guide

Polyurethane Wheels

Load Capacity Range:
300 – 1,000 lbs.

Characteristics: Easier rolling for higher capacities, long-lasting, chemical resistant, non-marking and quiet operation.

A polyurethane tread is superior for industrial, warehouse, and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.



Mold-On Rubber Wheels

Load Capacity Range:
500 – 600 lbs.

Characteristics: Better load capacity, long-lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.



Pneumatic Wheels

Load Capacity Range:
300 – 400 lbs.

Characteristics: Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

An air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress, creating greater rolling resistance. Ideal for handling fragile loads over rough surfaces.



Phenolic Wheels

Load Capacity Range:
900 – 1,250 lbs.

Characteristics: Best rolling for heavy load capacities, long-lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. Offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.



Solid Rubber Wheels

Load Capacity Range:
300 – 400 lbs.

Characteristics: Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire that is more stable and easier to roll under heavy loads than pneumatic wheels. These wheels are a rugged, maintenance-free (no air pressure to maintain) alternative to pneumatic wheels.



Flat Free Hand Truck Wheels

Load Capacity Range:
400 lbs.

Characteristics: Wide rubber tread disperses the load better over irregular or softer surfaces. Less tread compression than pneumatic or solid rubber tires and ball bearings improve rollability of heavier loads.



Wheel Specifications

Wheel Diameter	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114	-
6	2	Mold-On Rubber	3/4" Roller	WHMS-0620	-
		Polyurethane	1/2" Ball	WHMP-0620	-
		Phenolic	3/4" Roller	WHPL-0620	-
8	2	Mold-On Rubber	3/4" Roller	WHMS-0820	-
		Polyurethane	1/2" Ball	WHMP-0820	-
		Phenolic	3/4" Roller	WHPL-0820	-
8	2-1/2	Solid Rubber	5/8" Ball	-	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830	-
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4	5/8" Ball		WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250	-
12	3-1/2	Pneumatic 4.10/3.50-6	5/8" Ball	WHPN-1235	-
		Pneumatic 4.10/3.50-6	1" Roller	WHPN-1235-RB	-
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640	-