

Item #	

Job \_\_\_\_\_

### PRINTED CIRCUIT **BOARD CARRIERS**

- Safe and Practical: Printed circuit board carriers provide a safe and efficient handling system for delicate circuit boards. 5/8" (13mm) slide spacing on center permits flexibility in separating boards for proper protection. Slides accommodate boards up to 1/8" (9mm) thick.
- Adjustable: Slide panels are adjustable to exact width of boards to be handled. Moveable retaining bars enable boards to be put in or taken out from either side.
- Stackable: Two or three carriers of the same size can be stacked vertically to save floor space.
- Large Capacity: Up to 20 full-size boards can be accommodated in each of the different carriers. With the addition of double-sided center panels, two or more boards can be carried on each level, so carriers can hold from 40 to 60 12"x6" (305x152mm) boards.
- Easily Transported and Stored: PCB carriers can be transported and stored in a variety of modified and standard products made by InterMetro:
  - In PT Series tote box carriers;
  - In enclosed mobile cabinets;
  - In adjustable undershelf slides made to fit standard Super Erecta Shelf® shelf carts and trucks.
- Conductive: Made of chrome-plated carbon steel.







# PRINTED CIRCUIT BOARD CARRIERS







Three CBC11C's in PT1C-5M Tote **Box Carrier** (Capacity six CBC11C's. Twoand three-bay Tote Box Carriers also available).

## **Dimensions**

Length/Width/Height		Approx. Pkd. Wt. Per Unit		Maximum Board Size		Capacity with Full-Size	Capacity with 12"x6" (305x150mm)	
Model No.	(in.)	(mm)	(lbs.)	(kg)	(in.)	(mm)	Boards	Boards
CBC11C	17 <sup>1</sup> / <sub>2</sub> x12 <sup>1</sup> / <sub>2</sub> x18 <sup>3</sup> / <sub>16</sub>	445x315x460	10	4.53	13x12	330x305	20	40 (1 Center Panel)
CBC13C	24 <sup>1</sup> / <sub>4</sub> x12 <sup>1</sup> / <sub>2</sub> x18 <sup>3</sup> / <sub>16</sub>	615x315x460	103/4	4.87	19 <sup>1</sup> / <sub>4</sub> x12	489x305	20	60 (2 Center Panels)

### **Center Panel with Double Slide**

		Approx.		
		Pkd. Wt.		
	Length/Wid	Per Unit		
Model No.	(in.)	(mm)	(lbs.)	(kg)
CBCP2C	<sup>7</sup> /8x12 <sup>1</sup> /2x15 <sup>1</sup> /8	22x317x384	6	2.7

Load Rating: 5 lbs. (2kg) per slide, not to exceed 75 lbs. (34kg) per carrier.

