

MAX-M22 Medium Duty Lift Table

2,200 lb Capacity
36" Vertical Travel
7.25" Lowered
43" Raised

Magnetic-backed control box or optional foot control allows operator to position the load at the ideal height



Motors and controls are easily accessible



Optional Foot Control

4 Standard
Tops Available
(others upon request)

**High Quality
Camrollers, Pivot Pins
and Bearings**

**Integral, retractable
maintenance safety
bars**

**All welded
construction
meets AWS
standard
service**

**Tables conform to or exceed ANSI
MH 29.1-1994/2008**

The best value in lift tables! Reduces awkward bending and lifting since the work load is always at the correct level. The productivity is increased. The MAX-M22 table line offers the following standard features.

- **Trapped top and bottom scissor arms**
- **Built-in safety bars**
- **Life Time Lubricated Bearings**
- **Magnetic backed control box**
- **High quality fit and finish**

LIFT PRODUCTS INC.

INNOVATIONS IN ERGONOMICS

MAX-M22

Model M22-36



Capacity	2,200 lbs
Edge Load Capacity *	1,500 lbs
Table Size Standard *	24" x 48"
Base Size	24" x 48"
Lowered Height	7.25"
Raised Height	43.25"
Vertical Travel	36"
Motor	1 HP
Voltage	115 V Single Phase

* Capacity is based on uniform load.

- Internally mounted 1 HP, 115V TENV motor
- 115V operating control voltage
- NEMA constant pressure
- Magnet-backed up/down push button control station with 10 ft. straight cord
- NEMA-I prewired controls and electrical connectors
- Control box contains contactor and control transformer
- All controller components meet UL and/or CSA specifications
- Cylinders with internal stops
- 10 ft. power cord (connector not included)
- Hard, chrome-plated, polished shafting hydraulic cylinder piston rods
- Surfaces degreased, descaled and finished with safety yellow and blue enamel
- Smooth steel top with yellow and black safety stripes
- S.A.E. hoses and fittings
- Integral safety restraint maintenance bars
- Internal gear pump with check valve, relief valve, solenoid valve
- Includes hydraulic oil and filter

Limited Warranty

- 90-day repair or replacement on total product
- 90-day on electrical components, except motors
- 1-year on motors, pumps structure and cylinders
- 5-years or 100,000 cycles on bearing
- 5-years on structural components

Standard Options Available

- T1 – 36" X 48" Top
- T2 – 48" x 48" Top
- T3 – 42" x 60" Top
- Foot Controls
- Casters 2 Rigid / 2 Swivel with Brakes
- Semi-Live Dolly Jack Handle and Casters
- Accordion Safety Skirting
- Custom Top Sizes

Distributed by:
 Custom Equipment Company
 866-333-0728
 sales@custommhs.com
 www.custommhs.com