

Spring Scissor Tables

Spring Scissor Tables are ideal for distributing and shipping facilities. The unit allows the user to transfer products from work space to work space, while holding an ergonomically friendly position. The frame is designed of a steel construction, which allows for strength and durability. Uniform capacity is 400 to 4,500 pounds. The scissor mechanism raises the unit to the desired height, while the internal spring provides support when unit is being loaded and unloaded. Service range is 9" to 2734". The 435%" diameter top can be manually rotated 360 degrees for improved packaging and handling capabilities. Base size measures 36"W x 3634"L with 634"W x 112"H fork pockets.

Model SST-45-PSS is constructed of partially stainless steel base frame, spring, legs. Model SST-45-PSS-ST is constructed of partially stainless steel as above and a solid top.

MODEL Number	**** = ==			
SST-45	STEEL CONSTRUCTION, OPEN TOP	432		
SST-45-PSS	PARTIALLY STAINLESS STEEL, OPEN TOP	432		
SST-45-PSS-ST	PARTIALLY STAINLESS STEEL, SOLID TOP	432		
MODEL SST-45 WITH AC	CORDION SKIRT			
SST-45-ACC-4-CI	CUSTOMER INSTALLED SKIRT ON MODEL SST-45	474		
SST-45-ACC-4-FI	FACTORY INSTALLED SKIRT ON MODEL SST-45	474		



Auto-Hite Carts

The Auto-Hite Carts raise or lower as materials are removed or added to the platform, keeping material at an ergonomic work height. Increase efficiency, while reducing potentially harmful bending and twisting motions. Carts utilize tension springs, which can be adjusted in order to fit each particular application. All steel construction with removable handle. Polyurethane casters are 5" x 2", two (2) rigid and two (2) swivel with brake. *Approximate ratio.

MODEL	PLATFORM	UNIFORM	SERVICE	MOVEMENT*	WEIGHT
NUMBER	SIZE (W x L)	CAPACITY	RANGE	LB. / INCH	(POUND)
SCSC-500-2040	20 ³ / ₈ " x 40 ³ / ₈ "	500 lb.	14" to 34"	25# / 1"	300
SCSC-500-4242	42" x 42"	500 lb.	14" to 34"	25# / 1"	404
SCSC-750-2040	20 ³ / ₈ " x 40 ³ / ₈ "	750 lb.	14" to 34"	38# / 1"	320
SCSC-1000-4242	42" x 42"	1,000 lb.	14" to 34"	50# / 1"	413
SCSC-1000-4848	48" x 48"	1,000 lb.	14" to 34"	50# / 1"	435
SCSC-2000-4242	42" x 42"	2,000 lb.	14" to 34"	100# / 1"	477
SCSC-2000-4848	48" x 48"	2,000 lb.	14" to 34"	100# / 1"	497

STATIONARY KIT OPTION, model SCSC-SL5-RF

Self-Elevating Lift Carts

Automatic height adjustment provides ergonomic work positioning to increase productivity and decrease work related repetitive motion injuries. Model SCSC-400-2032 has one spring, while the SCSC-800-2040 has two springs. Heavy-duty steel construction with removable bolt-on handle. Two (2) rigid and two (2) swivel 5" x 1" poly-on-poly casters with brake standard.

MODEL NUMBER	PLATFORM Size (W x L)	UNIFORM CAPACITY	SERVICE Range	OVERALL SIZE (W x L x H)	WEIGHT (POUND)
SCSC-400-2032®	20" x 32"	400 lb.	13¾" to 303/8"	19¾" x 40" x 30½"	213
SCSC-800-2040⊛	20" x 40"	800 lb.	14½" to 311/8"	20½" x 48½" x 35½"	288

Self-Elevating Spring Tables

Designed to automatically raise or lower as materials are removed or added to the platform, keeping material at an ergonomic work height. Increase productivity, while reducing potentially harmful bending and twisting motions. The counter balance springs can easily be added or removed to adjust weight-to-height sensitivity. This feature allows the user to conveniently set the table to fit each application. The ETS-230/460 has poly-on-poly casters, while the ETS-840/1120 rolls smoothly on mold-on-rubber casters.

MODEL Number	PLATFORM Size (W x L)	UNIFORM Capacity	SERVICE Range	CASTER Size	OVERALL SIZE (W x L)	WEIGHT (POUND)
ETS-230	20" x 20"	230 lb.	11" to 33"	4" x 1¼"	21" x 323/8"	168
ETS-460	20" x 20"	460 lb.	11" to 33"	4" x 1¼"	21" x 323/8"	184
ETS-840-30	30" x 30"	840 lb.	15" to 38"	4" x 2"	30 ⁵ /8" x 43 ⁵ /16"	448
ETS-1120-18	18" x 18"	1,120 lb.	15" to 38"	4" x 2"	18 ⁵ /8" x 31 ⁷ /16"	322
ETS-1120-24	24" x 24"	1,120 lb.	15" to 38"	4" x 2"	24 ⁵ /8" x 37 ⁷ /16"	332

