

Jumbo Steel Bollards

Oversized steel pipe for maximum protection and strength. Bollards can be used both indoors and outdoors to protect work areas, racking, and personnel. Base plate includes four pre-drilled mounting holes. Welded steel cap. Heavy-duty welded steel construction. Baked-in powder-coated toughness.

MODEL NUMBER	HEIGHT	OUTSIDE DIAMETER	BASE PLATE DIAMETER	WEIGHT (POUND)
JBOL-36-12	36 ^{3/16} "	12"	16 ^{29/32} "	64
JBOL-42-12	42 ^{9/16} "	12"	16 ^{29/32} "	72
JBOL-48-12	48 ^{3/16} "	12"	16 ^{29/32} "	81
AS-344 Ⓢ	ANCHOR BOLTS FOR CONCRETE (1) 3/4" x 4"			1
AS-344-4PK Ⓢ	ANCHOR BOLTS FOR CONCRETE (4) 3/4" x 4"			4



JUMBO STEEL BOLLARD
model JBOL-36-12

Surface Mounted Removable Steel Pipe Safety Bollards

Bollards can be used both indoors and outdoors to protect work areas, racking, and personnel. Surface mounted steel base plate allows for quick and easy bollard removal. Steel base plate is bolted in place (padlock not included). Guard is easily inserted into base plate, then secured in place. A padlock may be added to prevent unauthorized removal. Base plate measures 10^{1/4}"W x 10^{1/2}"L x 2"H and include four (4) pre-drilled mounting holes. Plastic top caps are removable. Baked-in powder-coated toughness. Welded steel construction.

MODEL NUMBER	DESCRIPTION	HEIGHT	OUTSIDE DIAMETER	WEIGHT (POUND)
BOL-RF-24-4.5 Ⓢ	SURFACE MOUNTED BOLLARD	24"	4 ^{1/2} "	30
BOL-RF-36-4.5 Ⓢ	SURFACE MOUNTED BOLLARD	36"	4 ^{1/2} "	32
BOL-RF-42-4.5 Ⓢ	SURFACE MOUNTED BOLLARD	42"	4 ^{1/2} "	35
BOL-RF-48-4.5 Ⓢ	SURFACE MOUNTED BOLLARD	48"	4 ^{1/2} "	37
BOL-RF-24-5.5 Ⓢ	SURFACE MOUNTED BOLLARD	24"	5 ^{1/2} "	33
BOL-RF-36-5.5 Ⓢ	SURFACE MOUNTED BOLLARD	36"	5 ^{1/2} "	35
BOL-RF-42-5.5 Ⓢ	SURFACE MOUNTED BOLLARD	42"	5 ^{1/2} "	37
BOL-RF-48-5.5 Ⓢ	SURFACE MOUNTED BOLLARD	48"	5 ^{1/2} "	41
BOL-RF-BASE Ⓢ	REMOVABLE BOLLARD BASE (ADDITIONAL)			10
AS-124 Ⓢ	ANCHOR BOLTS FOR CONCRETE (1) 1/2" x 4" (4 ^{1/2} " UNITS)			1
AS-124-4PK Ⓢ	ANCHOR BOLTS FOR CONCRETE (4) 1/2" x 4" (4 ^{1/2} " UNITS)			4
AS-125 Ⓢ	ANCHOR BOLTS FOR CONCRETE (1) 1/2" x 5" (5 ^{1/2} " UNITS)			1
AS-125-4PK Ⓢ	ANCHOR BOLTS FOR CONCRETE (4) 1/2" x 5" (5 ^{1/2} " UNITS)			4



48 Hours
to Ship

CA Residents see
WARNING A, Pg. 459



model BOL-RF-42-4.5

Movable Bollards

Movable Bollards provide a portable visual barrier when an area needs temporary protection. Ideal for use when keeping traffic out of a temporarily hazardous area or area under repair. Can be used indoors or outdoors. Units are 42" high with a diameter of 5^{1/2}". 10" mold-on-rubber wheels standard. Yellow baked-in powder-coated toughness for high visibility. Series BOL-MB-JK has a removable plastic top cap, which exposes four chain slots. Series BOL-MB-JKS has a removable bolt-on steel top cap with socket set-screw.

MODEL NUMBER	DESCRIPTION	WEIGHT (POUND)
BOL-MB-42-5.5	MOVABLE BOLLARD WITH REMOVABLE CAP & NO SLOTS	53
BOL-MB-JK-42-5.5	REMOVABLE PLASTIC CAP WITH SLOTS	53
BOL-MB-JKS-42-5.5	REMOVABLE BOLT-ON STEEL CAP WITH SLOTS	53
BOL-JK-CN6 Ⓢ	PROOF COIL CHAIN, 3/16" x 6'L	2
BOL-JK-CN15 Ⓢ	PROOF COIL CHAIN, 3/16" x 15'L	5



model
BOL-MB-42-5.5



BOL-MB-JK-42-5.5



BOL-MB-JKS-42-5.5

Offset Steel Bollards

Unique design features offset base plate that won't interfere with traffic. The 8" x 8" base plate includes four (4) pre-drilled mounting holes (mounting hardware sold separately). Removable plastic top cap and black/yellow safety tape included. Heavy-duty welded steel construction with baked-in powder-coated toughness.

MODEL NUMBER	HEIGHT	OUTSIDE DIAMETER	BASE PLATE	WEIGHT (POUND)
OBOL-35-4.5	36 ^{1/8} "	4 ^{1/2} "	8" x 8"	29
OBOL-47-4.5	48 ^{1/8} "	4 ^{1/2} "	8" x 8"	33
OBOL-53-4.5	54 ^{1/8} "	4 ^{1/2} "	8" x 8"	39
AS-344 Ⓢ	ANCHOR BOLTS FOR CONCRETE (1) 3/4" x 4"			1
AS-344-4PK Ⓢ	ANCHOR BOLTS FOR CONCRETE (4) 3/4" x 4"			4



OFFSET STEEL BOLLARD
model OBOL-47-4.5