Steel Pallets with Hot-Dipped Galvanized Finish

Heavy-duty non-reversible welded steel pallets. Usable fork openings are 37%" high. Model SPL-3636 has 4-way entry allowing access for both fork and pallet trucks. Models SPL-4048, SPL-4248 and SPL-4848 have 2-way entry and allow access for fork trucks only. Hot-dipped galvanized finish offers rust resistance.

		UNIFORM SUPPORTED WEIGHT CAPACITY			
MODEL NUMBER	OVERALL SIZE (W x D x H)	FLOOR (STATIC)	FORK (DYNAMIC)	UNSUPPORTED PALLET RACK	WEIGHT (POUND)
SPL-3636®	36" x 36" x 4¾"	8,000 lb.	4,000 lb.	2,200 lb.	80
SPL-4048®	40" x 48" x 4¾"	8,000 lb.	4,000 lb.	2,200 lb.	100
SPL-4248®	42" x 48" x 4¾"	8,000 lb.	4,000 lb.	2,200 lb.	103
SPL-4848®	48" x 48" x 4¾"	8,000 lb.	4,000 lb.	2,200 lb.	114

Heavy Duty Solid Deck Steel Pallet

The heavy-duty non-reversible welded steel Solid Deck Pallet are ideal to transport and store products within your facility and/or to transport them between facilities. Galvanized finish for rust resistance. Usable fork pockets are $8\frac{1}{2}$ "W x $2\frac{1}{2}$ "H. Open end usable size is 35"W x $3\frac{3}{4}$ "H.

		UNIFORM SUPPORTED WEIGHT CAPACITY			
MODEL	OVERALL SIZE	FLOOR	FORK	UNSUPPORTED	WEIGHT
NUMBER	(W x D x H)	(STATIC)	(DYNAMIC)	PALLET RACK	(POUND)
SDSP-4048®	47" x 39½" x 6½"	4,000 lb.	3,500 lb.	2,500 lb.	118

Galvanized Welded Wire Pallets

Galvanized Welded Wire Pallets will stand up to heavy-duty use. Design allows for stacking. Four-way access with pallet truck, and fork trucks. Open decking features 2" x 4" grid pattern. Usable height on open end is 3". Usable height on stringer end is 2¾". Understructure supports are made from 12 gauge steel. Decking is made from welded steel wire. Welded steel construction with galvanized finish.

		UNIFORM SUPPORTED WEIGHT CAPACITY			
MODEL	OVERALL SIZE	FLOOR	FORK	UNSUPPORTED	WEIGHT
NUMBER	(W x D x H)	(STATIC)	(DYNAMIC)	PALLET RACK	(POUND)
WMP-4048®	40" x 48" x 4"	4,000 lb.	2,500 lb.	NOT RATED	84
WMP-4848 ®	48" x 48" x 4"	4,000 lb.	2,500 lb.	NOT RATED	98

Aluminum Pallets

This is the pallet the food and chemical industries have always wanted. Easy to clean with a power washer. Stands up to high-power steam, brushes, or pads. Features a non-skid surface for easy transportation of all products. Top boards are 4¾" wide. Available in two-way and four-way entry for pallet and fork truck use. Durable and re-usable. Heavy-duty welded aluminum construction.

	UNIFORM SUPPORTED WEIGHT CAPACITY				
MODEL NUMBER	OVERALL SIZE (W x D x H)	FLOOR (STATIC)	FORK (DYNAMIC)	UNSUPPORTED Pallet Rack	WEIGHT (POUND)
2-WAY ENTRY					
AP-4048	401⁄8" x 48" x 6"	6,000 lb.	4,000 lb.	6,000 lb.	84
AP-4248	421⁄8" x 48" x 6"	6,000 lb.	4,000 lb.	6,000 lb.	86
AP-4848	481⁄8" x 48" x 6"	6,000 lb.	4,000 lb.	6,000 lb.	89
4-WAY ENTRY					
AP-4048-4W	40" x 47%" x 5 ¹ / ₁₆ "	6,000 lb.	4,000 lb.	4,000 lb.	85
AP-4248-4W	42" x 47%" x 5 ¹ / ₁₆ "	6,000 lb.	4,000 lb.	4,000 lb.	87
AP-4848-4W	47%" x 47%" x 5 ¹ /16"	6,000 lb.	4,000 lb.	4,000 lb.	90
SKID BOTTOM					
AP-4048-SB	40" x 47%" x 5 ¹ / ₁₆ "	6,000 lb.	4,000 lb.	4,000 lb.	85
AP-4248-SB	42" x 47%" x 5 ¹ /16"	6,000 lb.	4,000 lb.	4,000 lb.	87
AP-4848-SB	47%" x 47%" x 5 ¹ / ₁₆ "	6,000 lb.	4,000 lb.	4,000 lb.	90











AP-4248

Distributed by: Custom Equipment Company 866-333-0728 sales@custommhs.com www.custommhs.com