# **STORAGE LOCKERS & BIKE RACKS**

# WireCrafters



# WIRE MESH STORAGE SOLUTIONS IDEAL FOR

Apartments | Condominiums | Commercial | Existing Buildings







# RAPIDWIRE STORAGE LOCKERS



# Locker Specs

#### **Mesh Wire**

2"x2" square 10 GA welded wire mesh

#### **Doors**

Framed in 1-1/4" x 1-1/4" x 13 GA steel angle & pre-hung at the factory. All doors supplied with door strikes, padlock hasps & 2-1/2" x 2-1/2" spun-pin hinges welded into place.

#### **Side Panels**

Framed with 1-1/4" x 1-1/4" x 13 GA steel angle.

## **Styles**

Single Tier & Double Tier styles available.

#### **Hardware**

Standard grade 3/8" plated nuts and bolts will be supplied for assembly, 3/8" mechanical anchors for wall and floor mount.

#### **Finish**

Standard finish for all non-plated parts is polyester-epoxy hybrid powder coat. Product is finished for interior applications. All lockers are shipped knocked down, ready for assembly.

## Standard Sizes Available

\*Other sizes available - consult your local sales representative.

## 3' Wide

3'-0" Deep x 7'-6" High

4'-0" Deep x 7'-6" High

5'-0" Deep x 7'-6" High

### 4' Wide

3'-0" Deep x 7'-6" High

4'-0" Deep x 7'-6" High

5'-0" Deep x 7'-6" High

## 5' Wide

3'-0" Deep x 7'-6" High

4'-0" Deep x 7'-6" High


5'-0" Deep x 7'-6" High

## Storage Locker Options



Ceilings

Constructed of the same material 16 GA formed galvanized steel. as the standard locker.



Shelves / Bottoms



**Back Panels** 16 GA galvanized sheet metal or

2" x 2" 10 GA Welded Wire.

# COMMERCIAL STORAGE ROOMS



When larger cages or key locks are required, we recommend our modular partition system. Panels bolt directly to support posts. Standard 3/8" wedge anchors hold partition firmly in place. Baseplates welded on posts allow direct floor anchoring.

## Ideal For:

- Superintendents cages
- · Limiting access to electrical panels & pipes
- Stairwell doors
- Commercial storage
- Colocation cages IT & telecom equipment
- Package room storage
- Building supply storage



Secure & limit access to electrical panels; backflow, mechanical & elevator equipment; meters & pipes.

# GARAGE & SOLID METAL LOCKERS



Storage for limited space. Typically 8' wide, 3' deep & 3' high. Hinged, double hinged or slide doors with padlock lugs are available.



16 GA solid metal lockers are typically used when privacy is the main concern.