For More Information: 866-333-0728

# SUPER ERECTA PRO® SHELVING





Epoxy coated Super Erecta-style frames with removable polymer shelf mats.

# Stays cleaner between cleanings.

Polymer shelf mats and Metroseal 3 epoxy coated shelf frames and posts have built in Microban<sup>®</sup> antimicrobial product protection.



Super Erecta Pro<sup>™</sup> Durable & cleanable. The original — reinnovated.



# Easy to clean.

Lift-off mats can be easily removed and washed by hand or in a wash machine.

# Prolonged durability.

Polymer shelf mats withstand daily abuse from containers and sharp edges. Robust design provides the strength and rigidity of Super Erecta...holds up to 800 lbs. (363kg) per shelf.





# Interchangeable.

Super Erecta Pro shelves can be configured with traditional shelf and accessory options on the same unit for maximum flexibility.



# Super Erecta Pro®

### Durable and Cleanable. The original - reinnovated.

Corrosion resistant shelving constructed of removable polymer open grid shelf mats over a wire shelf frame. Shelf frames and posts have Metroseal epoxy coating over an electroplated substrate. Shelves with polymer mats offer a 15 year limited warranty against corrosion, while posts offer a 12 year warranty against corrosion. Microban® antimicrobial product protection is built into the frames, shelf mats, and posts. Shelf has a rigid four-sided frame with center truss(es). Robust corner provides complete 360° capture of the split sleeves and post for added stability. Stationary units have maximum capacity of 2,000 lbs. (907kg) evenly distributed. Mobile units (with stem casters) offer a maximum total unit load of 900 lbs. (408kg). Units assemble easily — shelves mount on split sleeves along grooved, numbered posts and adjust on 1" (25mm) increments.

- **Prolonged durability:** Polymer shelf mats are corrosion proof and impact resistant. They will not chip, rust, or corrode.
- Easy to clean: Removable polymer shelf mats can easily be lifted off the shelf frames for cleaning in sinks or wash/dish machines.
- **Strong and robust:** Steel corners, side and center supports assure a sturdy and stable weight bearing surface. Weight capacities for evenly distributed loads:

800 lbs. (363kg) per shelf for lengths of 24" to 48" (610 to 1220mm) 600 lbs. (275kg) per shelf for lengths of 54" (1370mm) or longer 2,000 lbs. (907kg) maximum per stationary unit.

- Interchangeable: Super Erecta Pro shelves are compatible on the same shelving units with other Super Erecta shelving options: Super Erecta wire, Super Adjustable Super Erecta, Solid Super Erecta shelves, Dunnage shelves, Cantilever shelves. Super Erecta Pro shelves can be used with Post-Type Wall Mounts, Direct Wall Mounts, SmartWall Wall Mounts, Security Units, Top Track, and qwikTRAK systems.
- **Microban Product Protection:** Microban antimicrobial product protection is built into the shelf mats and the Metroseal 3 epoxy coating to protect the product from bacteria, mold, mildew, and fungus that cause odors and product degradation. Microban protection keeps the product "cleaner between cleanings".
- Efficient use of storage space: Shelves can be adjusted at 1" (25mm) increments along the post to maximize the use of available vertical storage space.
- **Open Grid Shelf Mats:** Open grid shelves promote air circulation and light penetration.
- Fast, Easy Assembly: Super Erecta Pro units assemble easily in minutes, without tools. SiteSelect posts have numbered grooves and feature unique double grooves every 8" (203mm) to help position the shelves.
- Warranty against rust and corrosion: Shelves with polymer shelf mats 15 years. Posts 12 years. Shelf mats are constructed of polypropylene and will never rust.





\*MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban Products Company, Huntersville, NC.

All Metro Catalog Sheets are available on our website: www.metro.com









# Super Erecta Pro<sup>®</sup> Shelves


#### Specifications

- Shelf frames: Carbon steel with Metroseal 3 epoxy coating.
- Polymer Shelf mats: polypropylene.
- Microban antimicrobial product protection is built into the polymer shelf mats and Metroseal 3 epoxy coating.
- NSF listed for all environments.
- Continuous Temperature: Super Erecta Pro Shelves can be used continuously within a range of -20/120° F (-29/49° C) with intermittent exposure to 200° F (93° C). NOTE: Not suitable for cart wash applications.

#### **Standard Shelves**

· Part number includes shelf with removable polymer shelf mats and one bag of split sleeves

	ominal h/Length (mm)	App Pkd. (Ibs.)		Model No. Super Erecta Pro Metroseal 3
18x24	457x610	6.0	2.7	PR1824NK3
18x30	457x760	7.8	3.5	PR1830NK3
18x36	457x914	9.5	4.2	PR1836NK3
18x42	457x1060	11.3	5.0	PR1842NK3
18x48	457x1219	13.0	5.8	PR1848NK3
18x54	457x1372	14.8	6.6	PR1854NK3
18x60	457x1524	16.5	7.4	PR1860NK3
18x72	457x1829	19.8	8.8	PR1872NK3
21x24	530x610	8.0	3.6	PR2124NK3
21x30	530x760	9.5	4.2	PR2130NK3
21x36	530x914	11.3	5.0	PR2136NK3
21x42	530x1060	12.5	5.6	PR2142NK3
21x48	530x1219	14.3	6.4	PR2148NK3
21x54	530x1372	16.5	7.4	PR2154NK3
21x60	530x1524	18.3	8.1	PR2160NK3
21x72	530x1829	21.5	9.6	PR2172NK3
24x24	610x610	9.5	4.2	PR2424NK3
24x30	610x760	11.3	5.0	PR2430NK3
24x36	610x914	13.0	5.8	PR2436NK3
24x42	610x1060	14.0	6.3	PR2442NK3
24x48	610x1219	15.5	6.9	PR2448NK3
24x54	610x1372	18.3	8.1	PR2454NK3
24x60	610x1524	20.0	8.9	PR2460NK3
24x72	610x1829	23.3	10.4	PR2472NK3



Actual Dimensions: Width: Add 1/4" (6mm) to nominal size. Length: Subtract 1/4" (6mm) from nominal size.

Note: Polymer Shelf mats are designed to fit Super Erecta Pro shelves and cannot be retrofitted to Super Erecta wire shelves. **Replacement Split Sleeves** 

Model No. 9985 Bag of four sets.

#### SiteSelect Posts

Stationary post height includes leveling bolt.

NOTE: Special length posts are available. Consult your Metro representative.

STATIC	ONARY	App	rox.			I	MOBIL	<b>E</b> (For	use w <sub>App</sub>		em casters	)
Actual	Height (mm)	Pkd.	Wt.	Model No. Metroseal 3	Model No. Stainless		Actual (in.)	Height (mm)	Pkd. (lbs.)		Model No. Metroseal 3	Model No. Stainless
(in.) 14 <sup>1</sup> /2	370	(lbs.) 1.0	(kg) 0.5	13PK3	13PS	1	13 <sup>3</sup> /4	349	1.0	0.5	13UPK3	13UPS
34 <sup>1</sup> / <sub>2</sub>	875	2.0	0.9	33PK3	33PS		33 <sup>3</sup> /4	857	2.0	0.9	33UPK3	33UPS
54 <sup>9</sup> /16	1385	3.0	1.4	54PK3	54PS		5313/16	1366	3.0	1.4	54UPK3	54UPS
62 <sup>9</sup> /16	1590	3.5	1.6	63PK3	63PS		61 <sup>13</sup> /16	1570	3.5	1.6	63UPK3	63UPS
—	—		—	_	_		69 <sup>3</sup> /4	1772	3.8	1.7	70UPK3	
74 <sup>5</sup> /8	1895	4.0	1.8	74PK3	74PS		737/8	1876	4.0	1.8	74UPK3	74UPS
865/8	2200	5.0	2.3	86PK3	86PS		85 <sup>7</sup> /8	2181	5.0	2.3	86UPK3	86UPS

KITS (Four shelves and four split posts ship in one carton)

0									
3	Nominal Width/Length		Hei	Approx. Height Pkd. Wt.					
3	(in.)	(mm)	(lbs.)	(kg)	(lbs.)	(kg)	Model No.		
3	18x36	457x914	74-5/8	1895	58.0	26.3	EZPR1836NK3-4		
3	18x48	457x1219	74-5/8	1895	73.0	33.1	EZPR1848NK3-4		
3	24x36	610x914	74-5/8	1895	72.0	32.6	EZPR2436NK3-4		
3	24x48	610x1219	74-5/8	1895	83.0	37.6	EZPR2448NK3-4		

"S" Hook: Used to "add on" one or multiple Super Erecta Pro shelving units while eliminating the cost of two posts per unit. Can be used to join units end-to-end, back-to-back, at right angles, etc. Two "S" hooks are required for each shelf. Model No. Q9995Z

#### Notes about "add-on" units.

- Add-on (Adjacent) units must be configured entirely of one style of shelf. (Example: Adjacent unit may be configured entirely of Super Erecta Pro OR entirely of Super Erecta Wire/Super Adjustable shelves.)
- To connect an adjacent Super Erecta or Super Adjustable Super Erecta wire shelving unit to a Super Erecta Pro unit using S-hooks, the adjacent unit must use S-hook model number Q9995Z.
- A mixed shelving unit having a combination of Super Erecta Pro, Super Erecta wire, and Super Adjustable cannot be connected to another unit with "S" Hooks.





Super Erecta Pro<sup>®</sup> Shelves

an Ali Group Company



Distributed by: Custom Equipment Company 866-333-0728 sales@custommhs.com www.custommhs.com



# SUPER ERECTA PRO® SHELVING



SiteSelect<sup>™</sup> Posts — {10.80} Stationary Super Erecta SiteSelect posts are fitted with adjustable leveling bolts to compensate for uneven surfaces. Mobile posts come without leveling bolt assembly to accommodate stem casters. Special length posts are available. See page 50 for stem caster options.



SiteSelect posts provide a visual guide for positioning and adjusting shelves, saving considerable time during assembly and adjustment. An easy-to-identify double groove, every 8" (203mm), offers a quick way to align all shelves.

### **Stationary Posts**

Hei (in.)	ight (mm)	Appr Pkd. (Ibs.)		Cat. No. Metroseal 3	Cat. No. Stainless
14 <sup>1</sup> /2	370	1	0.5	13PK3	13PS
<b>34</b> <sup>1</sup> / <sub>2</sub>	875	2	0.9	33PK3	33PS
54 <sup>9</sup> /16	1385	3	1.4	54PK3	54PS
62 <sup>9</sup> /16	1590	<b>3</b> <sup>1</sup> / <sub>2</sub>	1.6	63PK3	63PS
74 <sup>5</sup> /8	1895	4	1.8	74PK3	74PS
865/8	2200	5	2.3	86PK3	86PS

# **Mobile Posts**

Heig	aht	Appi Pkd.		Cat. No.	Cat. No.
(in.)	, (mm)	(lbs.)	(kg)	Metroseal 3	Stainless
<b>13</b> <sup>3</sup> / <sub>4</sub>	349	1	0.5	13UPK3	13UPS
<b>33</b> <sup>3</sup> / <sub>4</sub>	857	2	0.9	33UPK3	33UPS
5313/16	1366	3	1.4	54UPK3	54UPS
<b>61</b> <sup>13</sup> / <sub>16</sub>	1570	<b>3</b> <sup>1</sup> / <sub>2</sub>	1.6	63UPK3	63UPS
<b>69</b> <sup>3</sup> / <sub>4</sub>	1772	3.8	1.7	70UPK3	-
73 <sup>7</sup> /8	1876	4	1.8	74UPK3	74UPS
85 <sup>7</sup> /8	2181	5	2.3	86UPK3	86UPS

# Accessories - {10.81}

**Note:** These accessories are designed to attach to a Super Erecta Pro Shelf. Accessories for basic Super Erecta wire shelves can be found on pages 55-63. For a complete list of compatible accessories for Super Erecta Pro shelves, please refer to spec sheet 10.81 for more information.

### "S" Hooks

Eliminates the need for adjacent posts. Two required for each storage level. Cat. No. Q9995Z

### **Standard Divider**

<ul> <li>Corro</li> </ul>	sion	proof
---------------------------	------	-------

Nominal Len	gth	Approx. Pkd. Wt.						
(in.) (mm	Fits Shelf Depth	(lbs.)	(kg)	Cat. No.				
18 457	18", 21" (457, 530mm)	1.3	0.6	MQD18-8				
24 610	24" (610mm)	1.6	0.7	MQD24-8				

### Shelf-to-Shelf Divider

- Connects between two shelves
- Corrosion proof

Nominal Height		Compatible with Shelf Depths		Appr Pkd.		
(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)	Cat. No.
16	406	18, 21	457, 530	2.3	1.0	MD18-16
20	508	18, 21	457, 530	2.5	1.1	MD18-20
24	610	18, 21	457, 530	3.8	1.7	MD18-24
16	406	24	610	2.8	1.2	MD24-16
20	508	24	610	3.0	1.3	MD24-20
24	610	24	610	4.4	2.0	MD24-24

### **Color Shelf Marker**

- 6" (152mm) Length
- Fits Super Erecta Pro Shelf
- Attach easily to shelf to identify contents stored.

				rox.		
		Len	gth	Pkd.	Wt.	
	Color	(in.)	(mm)	(lbs.)	(kg)	Cat. No.
I	Blue	6	152	0.05	0.02	CSM6-BQ
	Green	6	152	0.05	0.02	CSM6-GQ
	Red	6	152	0.05	0.02	CSM6-RQ
	Tan	6	152	0.05	0.02	CSM6-TQ
	White	6	152	0.05	0.02	CSM6-WQ
	Yellow	6	152	0.05	0.02	CSM6-YQ
	Gray	6	152	0.05	0.02	CSM6-GRQ









### Label Holders

- Fits Super Erecta Pro Shelf
- Plastic holders snap into place to accommodate 1" (25mm) tall adhesive label.

Cat. No. MQ04LH

