

GUARDIAN STANDARD SCISSOR LIFT TABLE



The Guardian Standard Scissor Lift Table (LPB) is an ergonomically designed workstation that ensures the operator's health, safety, and comfort. The Guardian Standard Table features load capacities of 1,100lb and is available with several different platform sizes and vertical travels.

Specifications

Model	Vertical Travel	Capacity (lbs)	Height		Platform Size	Base Frame	Lift Speed
			Lower	Raised			
LPB-10-0	23.25"	1,100	7.875"	31"	31.5" x 39.375"	29.5" x 39.375"	9 sec
LPB-10-1	31.5"	1,100	7.875"	39.375"	31.5" x 49.25"	29.5" x 49.25"	11 sec
LPB-10-2	31.5"	1,100	7.875"	39.375"	39.375" x 49.25"	29.5" x 49.25"	11 sec
LPB-10-3	39.375"	1,100	8.625"	48"	31.5" x 59"	29.5" x 59"	15 sec
LPB-10-4	39.375"	1,100	8.625"	48"	39.375" x 59"	29.5" x 59"	15 sec

Standard Features

- Upper Platform Fitted with an Aluminum Safety Bar to Prevent Obstruction Descent
- Low Tension 24V Controls with Up/Down Buttons, Including Re-Set Button
- Internal Power Pack Equipped with a Relief Valve Against Overloading and Compensated Flow Valve for Controlled Lowering Speed. An Electronic System controls the Electric Circuit
- Single-Acting Cylinders with Drainage System and Check Valve to Stop the Lift from Lowering in Case of Hose Burst
- Safety Clearance Between Scissors to Prevent Trapping During Operations
- Self-Lubricating Bushings on Pivot Points
- Mechanical Block Bars for Maintenance Safety
- Removable Lifting Eye to Facilitate Handling and Installation of the Lift Table
- Quality Fit and Finish

Options



Foot Controls

For More Information: 866-333-0728

GUARDIAN LOW PROFILE SCISSOR LIFT TABLE



The Guardian Low Profile Scissor Lift Table (LPBL) represents the best in lift table safety with standard features that surpass other competitive lift tables. This low-profile table features load capacities of 1,100lb to 3,300lbs and a lowered height of 3.25" / 3.625", providing flexibility for any operator height differences and tall pallet applications.

Specifications

Model	Vertical Travel	Capacity (lbs)	Height		Platform Size	Lift Speed (sec)
			Lower	Raised		
LPBL-10-1	30.75"	1,100	3.25"	34"	31.5" X 55"	10
LPBL-10-2	30.75"	1,100	3.25"	34"	39.5" X 55"	10
LPBL-20-1	30.75"	2,200	3.25"	34"	31.5" X 55"	18
LPBL-20-2	30.75"	2,200	3.25"	34"	39.5" X 55"	18
LPBL-30-1	29.5"	3,300	3.625"	33.125"	31.5" X 61"	25
LPBL-30-2	29.5"	3,300	3.625"	33.125"	39.5" X 61"	25

Standard Features

- Upper Platform Fitted with an Aluminum Safety Bar To Prevent Obstruction Descent
- Low Tension 24V Controls with Up/Down Buttons, Including Re-Set Button
- External Power Pack Equipped with a Relief Valve Against Overloading and Compensated Flow Valve for Controlled Lowering Speed
- An Electronic System Controls Electric Circuits. The Power Pack is Supplied with 8' Long Hoses.
- Quality Fit and Finish
- Single-Acting Cylinders with Drainage System and Check Valve to Stop the Lift From Lowering in Case of Hose Burst
- Safety Clearance Between Scissors to Prevent Trapping During Operations
- Self-Lubricating Bushings on Pivot Points
- Mechanical Block Bars for Maintenance Safety
- Removable Lifting Eye to Facilitate Handling and Installation of the Lift Table

Options



Foot Controls