



# **Double End Rack Platform Truck**

#### 3600 lbs. Capacity

- 12 gauge reinforced steel deck
- Two removable end racks
- Also available with removable side rack
- 6" x 2" non-marking polyurethane wheels
- Two rigid and two swivel casters

Deck Size	Model No.	Wt.
24 x 48	DR-2448-6PY	108
24 x 60	DR-2460-6PY	121
30 x 48	DR-3048-6PY	123
30 x 60	DR-3060-6PY	138
30 x 72	DR-3072-6PY	153

Floor Lock Option, add: -FL

# **Double End Rack Platform Truck** with Side Rack

#### 3600 lbs. Capacity

- Two removable end racks
- Removable side rack
- 6" x 2" non-marking polyurethane wheels

Deck Size	Model No.	Wt.
24 x 48	DRB-2448-6PY	126
24 x 60	DRB-2460-6PY	142
30 x 48	DRB-3048-6PY	142
30 x 60	DRB-3060-6PY	159

Floor Lock Option, add: -FL



DR6W-3048-6PY

# 6-Wheel Double End Rack Platform Truck

#### 3600 lbs. Capacity

- 12 gauge reinforced steel deck
- Two removable end racks
- Also available with removable side rack
- 6" x 2" non-marking polyurethane
- · Four rigid and two swivel casters wheels

	End Racks		End Racks & Side Rack		
Deck Size	Model No.	Wt.	Model No.	Wt.	
24 x 48	DR6W-2448-6PY	113	DRB6W-2448-6PY	126	
24 x 60	DR6W-2460-6PY	126	DRB6W-2460-6PY	142	
30 x 48	DR6W-3048-6PY	130	DRB6W-3048-6PY	142	
30 x 60	DR6W-3060-6PY	145	DRB6W-3060-6PY	159	
30 x 72	DR6W-3072-6PY	160	_	-	

#### For More Information: 866-333-0728

Optional Floor Lock

Model DRB-3048-6PY





# **High-End Truck**

- 2000 lbs. Capacity
- 12 gauge steel shelves
- Six wheel design for easy maneuverability and zero-turn radius
- Two 8" rigid center wheels, and four 5" corner mounted swivel casters
- 12 gauge reinforced steel deck
- Non-marking polyurethane wheels
- Two removable pipe handles extend 48" above deck
- Also available with a removable shelf (200 lbs. shelf capacity)

	High End Truck		With Removable Shelf	
Deck Size	Model No.	Wt.	Model No.	Wt.
16 x 48	HE-1648	105	HE-1648-RS	127
16 x 60	HE-1660	115	HE-1660-RS	142
16 x 72	HE-1672	124	-	-
24 x 48	HE-2448	124	-	-
24 x 60	HE-2460	188	-	-



# **High-End Truck with Fixed Shelf**

#### 2000 lbs. Capacity

- 12 gauge steel shelves
- Six wheel design for easy maneuverability and zero-turn radius
- Two 8" rigid center wheels, and four 5" corner mounted swivel casters
- Non-marking polyurethane wheels
- End panels extend 48" high
- Shelf clearance: 24"

Size	Model No.	Wt.
16 x 48	HE2-1648	118
16 x 60	HE2-1660	129
16 x 72	HE2-1672	152
24 x 48	HE2-2448	152
24 x 60	HE2-2460	190

# Model HE2-2460

# **Narrow-Aisle Order Picking Truck**

#### 2000 lbs. Capacity

- 21" wide x 12" deep writing shelf with storage pocket
- 12 gauge steel shelves
- End panels extend 48" above deck
- Non-marking polyurethane wheels
- Two 8" rigid center wheels, and four 5" corner mounted swivel casters

Size	Model No.	Wt.
24 x 48	HE2-2448-WSP	172
24 x 60	HE2-2460-WSP	210









# 2-Sided Multi-Shelf Truck

3600 lbs. Capacity

- Expanded metal end panels extend 48" above deck
- 12 gauge steel shelves
- Available in two, three, or four shelf configurations
- 6" non-marking polyurethane wheels
- Two rigid and two swivel casters
- Deck available with flush edges or 1-1/2" retaining lips
- All-welded construction

Shelf Size	2 SHELVES 23-1/4" Clearance Model No.	Wt.	3 SHELVES 15" Clearance Model No.	Wt.	4 SHELVES 12" Clearance Model No.	Wt.
	FI	USH	SHELVES – 57" O	AH		
24 x 48	DET2-2448-6PY	154	DET3-2448-6PY	196	DET4-2448-6PY	238
24 x 60	DET2-2460-6PY	175	DET3-2460-6PY	217	DET4-2460-6PY	269
30 x 48	DET2-3048-6PY	178	DET3-3048-6PY	229	DET4-3048-6PY	281
30 x 60	DET2-3060-6PY	204	DET3-3060-6PY	268	DET4-3060-6PY	332
	LIP	UP S	HELVES - 58-1/2"	' OAH		
24 x 48	DET2L-2448-6PY	154	DET3L-2448-6PY	196	DET4L-2448-6PY	238
24 x 60	DET2L-2460-6PY	175	DET3L-2460-6PY	217	DET4L-2460-6PY	269
30 x 48	DET2L-3048-6PY	178	DET3L-3048-6PY	229	DET4L-3048-6PY	281
30 x 60	DET2L-3060-6PY	204	DET3L-3060-6PY	268	DET4L-3060-6PY	332





DET3L-3048-8MRRD

# 2-Sided Towable Multi-Shelf Truck

2000 lbs. Capacity

- Expanded metal end panels extend 48" above deck
- 12 gauge steel shelves
- Available in two, three, or four shelf configurations
- 1-1/2" retaining lips
- 8" kingpinless mold-on rubber wheels
- Two rigid and two swivel casters
- Can be used independently or connected to other units
- Ring drawbar stays in upright position for manual operation
- Pin and clevis rear hitch
- All-welded construction
- 58-1/2" OAH

s					4 SHELVES 12" Clearance		
S	ize	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
3	0 x 48	DET2L3048-8MRRD	208	DET3L3048-8MRRD	259	DET4L3048-8MRRD	311
3	0 x 60	DET2L3060-8MRRD	234	DET3L3060-8MRRD	298	DET4L3060-8MRRD	362





# 2-Sided Adjustable Shelf Truck

#### 3600 lbs. Capacity

- End panels extend 48" above deck
- Available with expanded metal, solid steel, or open ends
- Available with 1 or 2 adjustable shelves on 3-1/2" centers
- Additional adjustable shelves are available
- Shelf lips can be positioned up or down
- Two rigid and two swivel casters
- 6" non-marking polyurethane wheels
- Overall height: 57"
- All-welded construction

#### **Expanded Metal End Panels**

Size	1 Adjustable Shelf	1 Adjustable Shelf		
W x D	Model No.	Wt.	Model No.	Wt.
24 x 48	DET2-A-2448-6PY	184	DET3-A-2448-6PY	226
24 x 60	DET2-A-2460-6PY	205	DET3-A-2460-6PY	257
30 x 48	DET2-A-3048-6PY	208	DET3-A-3048-6PY	259
30 x 60	DET2-A-3060-6PY	234	DET3-A-3060-6PY	297





#### **Open Angle End Panels**

Size	1 Adjustable Shelf		2 Adjustable Shelves		
W x D	Model No.	Wt.	Model No.	Wt.	
24 x 48	DETO2A-2448-6PY	171	DETO3A-2448-6PY	213	
24 x 60	DETO2A-2460-6PY	192	DETO3A-2460-6PY	244	
30 x 48	DETO2A-3048-6PY	195	DETO3A-3048-6PY	246	
30 x 60	DETO2A-3060-6PY	218	DETO3A-3060-6PY	281	



#### **Solid Steel End Panels**

Size	1 Adjustable Shelf		2 Adjustable Shelves	
W x D	Model No.	Wt.	Model No.	Wt.
24 x 48	DETS2A-2448-6PY	241	DETS3A-2448-6PY	283
24 x 60	DETS2A-2460-6PY	262	DETS3A-2460-6PY	314
30 x 48	DETS2A-3048-6PY	283	DETS3A-3048-6PY	334
30 x 60	DETS2A-3060-6PY	306	DETS3A-3060-6PY	369







# **3-Sided Bulk Truck -Tubular Steel Sides**

#### 3600 lbs. Capacity

- 12 gauge reinforced steel deck
- Deck available with flush edges or 1-1/2" retaining lips
- Pushbar handle on swivel caster end
- Two rigid and two swivel casters
- 6" x 2" non-marking polyurethane wheels
- Interior height: 48"
- 57" OAH for flush, 58-1/2" OAH for lip up
- 14 gauge tubular steel sides

Deck Size	Flush Edge Deck	1-1/2" Lip Edge Deck	
D x W	Model No.	Model No.	Wt.
24 x 36	OT-2436-6PPY	OTL-2436-6PPY	108
24 x 48	OT-2448-6PPY	OTL-2448-6PPY	126
24 x 60	OT-2460-6PPY	OTL-2460-6PPY	143
30 x 48	OT-3048-6PPY	OTL-3048-6PPY	139
30 x 60	OT-3060-6PPY	OTL-3060-6PPY	157



S1-2448-6PPY





Adjustable Shelf S2-A-2448-6PPY

# **3-Sided Bulk Truck -Slat-Type Sides**

#### 3600 lbs. Capacity

- 12 gauge reinforced steel deck
- Deck available with flush edges or 1-1/2" retaining lips
- Pushbar handle on swivel caster end
- 6" x 2" non-marking polyurethane wheels
- Interior height: 48"
- 57" OAH for flush, 58-1/2" OAH for lip up

	Deck Size W x L	Flush Edge Deck Model No.	1-1/2" Lip Edge Deck Model No.	Wt.
	24 x 48	S1-2448-6PPY	S1L-2448-6PPY	156
Single Shelf	24 x 60	S1-2460-6PPY	S1L-2460-6PPY	174
(Deck Only)	30 x 48	S1-3048-6PPY	S1L-3048-6PPY	182
	30 x 60	S1-3060-6PPY	S1L-3060-6PPY	208

#### 2 or 3 Welded Shelf Models

	Deck Size	Flush Edge Deck	1-1/2" Lip Edge Deck	
	WxL	Model No.	Model No.	Wt.
2 Shelves	24 x 48	S2-2448-6PPY	S2L-2448-6PPY	156
23-1/4"	24 x 60	S2-2460-6PPY	S2L-2460-6PPY	174
Z3-1/4 Clearance	30 x 48	S2-3048-6PPY	S2L-3048-6PPY	182
Clearance	30 x 60	S2-3060-6PPY	S2L-3060-6PPY	208
0 Chalusa	24 x 48	S3-2448-6PPY	S3L-2448-6PPY	156
3 Shelves 15"	24 x 60	S3-2460-6PPY	S3L-2460-6PPY	174
	30 x 48	S3-3048-6PPY	S3L-3048-6PPY	182
Clearance	30 x 60	S3-3060-6PPY	S3L-3060-6PPY	208

#### **Adjustable Shelf Models**

Deck Size	1 Adjustable Shelf		2 Adjustable Shelves	
DxW	Model No.	Wt.	Model No.	Wt.
24 x 48	S2-A-2448-6PPY	218	S3-A-2448-6PPY	260
24 x 60	S2-A-2460-6PPY	256	S3-A-2460-6PPY	308
30 x 48	S2-A-3048-6PPY	263	S3-A-3048-6PPY	317
30 x 60	S2-A-3060-6PPY	297	S3-A-3060-6PPY	369



Model CA-2448-8PPY

#### 3600 lbs. Capacity

- Three-sided bulk truck with mesh sides
- 12 gauge steel deck
- Two rigid and two swivel casters
- 8" x 2" non-marking polyurethane wheels
- Pushbar handle
- Interior height: 36"
- Also available with a removable drop-gate panel

Deck Size	3 Sided Bulk Truck		With Removable Drop	Gate
D x W	Model No.	Wt.	Model No.	Wt.
24 x 48	CA-2448-8PPY	140	CARD-2448-8PPY	166
24 x 60	CA-2460-8PPY	159	CARD-2460-8PPY	191
30 x 48	CA-3048-8PPY	160	CARD-3048-8PPY	186
30 x 60	CA-3060-8PPY	175	CARD-3060-8PPY	206

Drop-Gate removed

# **Easy-Access Box Truck**

#### 3600 lbs. Capacity

- 12 gauge reinforced steel deck
- Two rigid and two swivel casters
- 6" x 2" non-marking polyurethane wheels
- Pushbar handle
- Expanded metal side panels
- Front panel extends 17-3/4" above deck
- Side and back panels extend 36" above deck

Size	Model No.	Wt.
24 x 48	CAW-2448-6PY	145
24 x 60	CAW-2460-6PY	203
30 x 48	CAW-3048-6PY	165
30 x 60	CAW-3060-6PY	218

# Welded Drop Gate Truck

#### 3600 lbs. Capacity

- 12 gauge reinforced steel deck
- Two rigid and two swivel casters
- 6" x 2" non-marking polyurethane wheels
- Pushbar handle
- Expanded metal side panels
- Front drop-gate with slide-bolt latches
- Side and back panels extend 36" above deck

Size	Model No.	Wt.
24 x 48	CAWD-2448-6PY	160
24 x 60	CAWD-2460-6PY	185
30 x 48	CAWD-3048-6PY	180
30 x 60	CAWD-3060-6PY	200





Model

CARD-2448-8PPY







T1L-2448-6PYFP





# **3-Sided Bulk Trucks –** 48" Interior Height

#### 3600 lbs. Capacity

- 12 gauge reinforced steel deck
- Deck available with flush edges or 1-1/2" retaining lips
- Pushbar handle on swivel caster end
- 6" x 2" non-marking polyurethane wheels
- Powder coated gray finish
- Interior height: 48"
- 57" OAH for flush, 58-1/2" OAH for lip up
- Also available with two 6" x 3-1/2" fork pockets on 24" centers with 1-1/2" steel grab bar

#### **Lower Platform Only**

	Deck Size	Flush Edge Dec	k	1-1/2" Lip Edge Deck	
	D x W	Model No.	Wt.	Model No.	Wt.
	24 x 48	T1-2448-6PY	137	T1L-2448-6PY	137
Bulk	24 x 60	T1-2460-6PY	155	T1L-2460-6PY	155
Truck	30 x 48	T1-3048-6PY	152	T1L-3048-6PY	152
	30 x 60	T1-3060-6PY	163	T1L-3060-6PY	163
with Fork	24 x 48	T1-2448-6PYFP	173	T1L-2448-6PYFP	157
Pockets	30 x 48	T1-3048-6PYFP	190	T1L-3048-6PYFP	177

#### **2 Fixed Shelf Models**

• Shelf clearance: 23-1/4"

	Deck Size	Flush Edge Dec	k	1-1/2" Lip Edge Deck	
	D x W	Model No.	Wt.	Model No.	Wt.
	24 x 48	T2-2448-6PY	179	T2L-2448-6PY	179
Bulk Truck	24 x 60	T2-2460-6PY	198	T2L-2460-6PY	198
BUIK ITUCK	30 x 48	T2-3048-6PY	205	T2L-3048-6PY	205
	30 x 60	T2-3060-6PY	226	T2L-3060-6PY	226
with Fork	24 x 48	T2-2448-6PYFP	215	T2L-2448-6PYFP	199
Pockets	30 x 48	T2-3048-6PYFP	264	T2L-3048-6PYFP	228

#### **3 Fixed Shelf Models**

Shelf clearance: 15"

	Deck Size	Flush Edge Dec	k	1-1/2" Lip Edge Deck	
	D x W	Model No.	Wt.	Model No.	Wt.
	24 x 48	T3-2448-6PY	221	T3L-2448-6PY	221
Bulk Truck	24 x 60	T3-2460-6PY	250	T3L-2460-6PY	250
BUIK ITUCK	30 x 48	T3-3048-6PY	256	T3L-3048-6PY	256
	30 x 60	T3-3060-6PY	293	T3L-3060-6PY	293
with Fork	24 x 48	T3-2448-6PYFP	257	T3L-2448-6PYFP	241
Pockets	30 x 48	T3-3048-6PYFP	293	T3L-3048-6PYFP	280

#### **Adjustable Shelf Models**

Deck Size	1 Adjustable Shelf		2 Adjustable Shelves	
D x W	Model No.	Wt.	Model No.	Wt.
24 x 48	T2-A-2448-6PY	203	T3-A-2448-6PY	245
24 x 60	T2-A-2460-6PY	228	T3-A-2460-6PY	280
30 x 48	T2-A-3048-6PY	230	T3-A-3048-6PY	284
30 x 60	T2-A-3060-6PY	259	T3-A-3060-6PY	322





# **Forkliftable Order Picking Truck**

3600 lbs. Capacity

- Two 6" x 3-1/2" fork pockets on 24" centers with 1-1/2" steel grab bar
- Two rigid and two swivel casters
- 6" polyurethane wheels
- Available with 2 or 3 shelves
  - 2 shelf version: 29-1/4" shelf clearance
  - 3 shelf version: 19" shelf clearance
- Overall height: 69"
- Custom configurations available

Model T3-2448-6PYFP60



	Deck Size	Flush Edge Deck		1-1/2" Lip Edge Deck	
	D x W	Model No.	Wt.	Model No.	Wt.
2	24 x 48	T2-2448-6PYFP60	229	T2L2448-6PYFP60	204
Shelves	30 x 48	T2-3048-6PYFP60	259	T2L3048-6PYFP60	235
3	24 x 48	T3-2448-6PYFP60	271	T3L2448-6PYFP60	246
Shelves	30 x 48	T3-3048-6PYFP60	310	T3L3048-6PYFP60	286

Model T2-2448-6PYFP60

# Forkliftable Order Picking Truck with Shelf Dividers

#### 3600 lbs. Capacity

- Three shelves with 2 center dividers on each shelf for 3 total compartments per shelf
- Compartment width: 15"
- 12 gauge steel shelves
- Two 6" x 3-1/2" fork pockets on 24" centers with 1-1/2" steel grab bar
- Shelf clearance: 19"
- Overall height: 69"
- Two rigid, and two swivel casters
- 6" polyurethane wheels

Deck Size D x W	Model No.	Wt.
30 x 48	T3D330486PYFP60	385

# Model

T3D330486PYFP60

# Towable Forkliftable Order Picking Truck

#### 2000 lbs. Capacity

- Ring drawbar
- Three-shelf truck
- Two 6" x 3-1/2" fork pockets on 24" centers with 1-1/2" steel grab bar
- Two rigid and two swivel casters
- 8" mold-on rubber wheels
- Shelf clearance: 19"
- Overall height: 71"

	Deck Size	1-1/2" Lip Edge Deck	
	D x W	Model No.	Wt.
3	24 x 48	T3L2488MRRDFP60	265
Shelves	30 x 48	T3L3088MRRDFP60	306







# **Drop-Shelf Truck**

3600 lbs. Capacity

- Upper shelf can drop down or be removed completely
- Sides extend 48" above deck
- Drop-shelf positioned 30" above deck
- Drop-shelf capacity not to exceed 500 lbs
- 6" x 2" non-marking polyurethane wheels
- Two rigid and two swivel casters

#### Mesh Sides - 13 gauge expanded metal

#### Slat-Type Sides - 1-1/2" x 3/16" slats

	Deck Size W x L	Shelf Size W x L	Model No.	Wt.
Mesh	24 x 48	21 x 44	T1-2448-6PY-DS	181
Sides	24 x 60	21 x 56	T1-2460-6PY-DS	206
	30 x 48	27 x 44	T1-3048-6PY-DS	209
	30 x 60	27 x 56	T1-3060-6PY-DS	237
Slat	24 x 48	21 x 44	S1-2448-6PY-DS	198
Sides	24 x 60	21 x 56	S1-2460-6PY-DS	225
	30 x 48	27 x 44	S1-3048-6PY-DS	234
	30 x 60	27 x 56	S1-3060-6PY-DS	271



# **Pick-Pack Truck**

2000 lbs. Capacity

- Upper shelves are sloped
- Bottom shelf has 1-1/2" retaining lip
- 14 gauge steel shelves
- Diamond caster pattern
- 6" x 2" polyurethane wheels

Size	Model No.	Shelf Size	Wt.
28 x 48	PPT-2848-6PY	14 x 48	217
28 x 60	PPT-2860-6PY	14 x 60	247

For 6" mold-on rubber wheels, use wheel code: -6MR (1600 lbs. capacity)

Distributed by: Custom Equipment Company 866-333-0728 tom@custommhs.com www.custommhs.com



	ection Gui	de T	ypical Factory Floor Rough/Unev		neven/Outdoor
How to choose • Load capacity • Push start force • Rolling/Floor co • Durability/Duty r	nditions		Polyurethane Phenolic Mold-On Rubl	ber	Pneumatic Solid Rubber Flat-Free
Phenolic	Polyurethane	Mold-On Rubber	Solid Rubber	Flat-Free	Pneumatic
Most	<load capacity=""></load>	Least	Least	<maintenance></maintenance>	Most
$\bigcirc$		R	R		C
Least	<cushion></cushion>	Most	Least	<cushion></cushion>	Most
Load Capacity Range per Caster Set (4): <b>3600-5000 Ibs.</b>	Load Capacity Range per Caster Set (4): <b>1200-4000 Ibs.</b>	Load Capacity Range per Caster Set (4): <b>2000-2400 Ibs.</b>	Load Capacity Range per Caster Set (4): 1200-1600 Ibs.	Load Capacity Range per Caster Set (4): <b>1600 Ibs.</b>	Load Capacity Range per Caster Set (4): <b>1200-4000/bs.</b>
Chemical Resistant High Temperature Non-marking	Non-marking Tread Chemical Resistant Quiet Operation	Cushion Tread Absorbs shock/vibration Floor Protection	Cushioned rubber tire that is more stable and easier to roll under heavy loads than	Wide Rubber tread disperses the load better over irregular or softer surfaces. Less	Air Filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps.
Applications: Least rolling resistance, but does not absorb vibrations	Applications: Industrial, Warehouse, Institutional	Quiet Operation Applications: Industrial & Warehouse	pneumatic. Rugged and maintenance free.	tread compression than pneumatic or solid rubber tires. Only available with off-set hub.	Requires air pressure.

#### **Swivel vs. Rigid Caster**



For More Information: 866-333-0728



# WHEELS

# 1

# **Wheel Selection Guide**

#### **Polyurethane Wheels**

Load Capacity Range: 300 – 1,000 lbs.



Characteristics: Easier rolling for higher capacities, long-lasting, chemical resistant, non-marking and quiet operation.

A polyurethane tread is superior for industrial, warehouse, and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

#### **Phenolic Wheels**

Load Capacity Range: 900 – 1,250 lbs.



**Characteristics:** Best rolling for heavy load capacities, long-lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. Offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

#### Mold-On Rubber Wheels

Load Capacity Range: 500 – 600 lbs.

**Characteristics:** Better load capacity, long-lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

#### Solid Rubber Wheels

Load Capacity Range: 300 – 400 lbs.

Characteristics: Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire that is more stable and easier to roll under heavy loads than pneumatic wheels. These wheels are a rugged, maintenancefree (no air pressure to maintain) alternative to pneumatic wheels.



#### **Pneumatic Wheels**

Load Capacity Range: 300 – 400 lbs.



Characteristics: Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

An air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress, creating greater rolling resistance. Ideal for handling fragile loads over rough surfaces.

#### Flat Free Hand Truck Wheels Load Capacity Range: 400 lbs.



Characteristics: Wide rubber tread disperses the load better over irregular or softer surfaces. Less tread compression than pneumatic or solid rubber tires and precision ball bearings improve rollability of heavier loads.

# **Wheel Specifications**

Wheel Diameter	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114	-
	2	Mold-On Rubber	3/4" Roller	WHMS-0620	-
		Polyurethane	1/2" Ball	WHMP-0620	-
		Phenolic	3/4" Roller	WHPL-0620	-
8	2	Mold-On Rubber	3/4" Roller	WHMS-0820	-
		Polyurethane	1/2" Ball	WHMP-0820	-
		Phenolic	3/4" Roller	WHPL-0820	-
8	2-1/2	Solid Rubber	5/8" Ball	-	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830	-
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	WHPN-1035
10	3-1/2	Flat Free	5/8" Ball		WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250	-
12	3-1/2	Pneumatic 4.10/3.50-6	5/8" Ball	WHPN-1235	-
		Pneumatic 4.10/3.50-6	1" Roller	WHPN-1235-RB	-
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640	-