

## Adjustable Sheet & Panel Trucks

**Models PG, TE, PO - Heavy duty steel transporters for upright panels and sheets**

**2,000 LB CAPACITY**



Model PG Shown

**2,000 LB CAPACITY**



Model TE Shown

**2,000 LB CAPACITY**



Model PO Shown

**Product Features:**

- All welded construction (except casters and removable dividers).
- Durable **12 gauge steel platform**, and 12 gauge caster mounts for long lasting use.
- **6 removable 1-1/4" tubular dividers** with smooth radius bend for safety and uniform appearance.  
2 each: 12" high, 24" high, 36" high.
- **7 divider sockets** at each end.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- Platform flush for easy load and unload.
- Deck height - 9", (12" with 8" casters)
  - Model TE - carpeted rails add 2" to deck height
  - Model PO - wood cap adds 1" to deck height
- Overall height - 45", (48" with 8" casters).
- Powder coated gray finish.

**Other Specifications:**

**Model TE**

- Durable 12 gauge steel platform, with - **3" x 2" carpeted rails**.

**Model PO**

- Durable 12 gauge steel platform, capped with **3/4" sealed plywood**.

**Options:**

- 2 wheel brakes on swivel casters - **Code B6 or BN**
- All swivel casters - **Code AS**
- Floor lock - **Code F6 or F8**

**Model PG - Steel Deck**

WxL (in)	6" Casters Models				8" Semi Pneumatic	
	Phenolic	Rubber	Urethane	Wgt. (lbs)	Models	Wgt. (lbs)
24 x 36	PG236-P6	PG236-R6	PG236-U6	142	PG236-Z8	152
48	PG248-P6	PG248-R6	PG248-U6	166	PG248-Z8	176
60	PG260-P6	PG260-R6	PG260-U6	190	PG260-Z8	200
72	PG272-P6	PG272-R6	PG272-U6	214	PG272-Z8	224
30 x 36	PG336-P6	PG336-R6	PG336-U6	150	PG336-Z8	160
48	PG348-P6	PG348-R6	PG348-U6	176	PG348-Z8	186
60	PG360-P6	PG360-R6	PG360-U6	204	PG360-Z8	214
72	PG372-P6	PG372-R6	PG372-U6	230	PG372-Z8	240
36 x 48	PG448-P6	PG448-R6	PG448-U6	188	PG448-Z8	198
60	PG460-P6	PG460-R6	PG460-U6	216	PG460-Z8	226
72	PG472-P6	PG472-R6	PG472-U6	246	PG472-Z8	256

**Model TE - Steel Deck, Carpeted Rails**

WxL (in)	6" Casters Models				8" Semi Pneumatic	
	Phenolic	Rubber	Urethane	Wgt. (lbs)	Models	Wgt. (lbs)
30 x 36	TE336-P6	TE336-R6	TE336-U6	156	TE336-Z8	166
48	TE348-P6	TE348-R6	TE348-U6	184	TE348-Z8	194
60	TE360-P6	TE360-R6	TE360-U6	210	TE360-Z8	220
72	TE372-P6	TE372-R6	TE372-U6	236	TE372-Z8	246

**Model PO - Steel Deck, Wood Capped**

WxL (in)	6" Casters Models				8" Semi Pneumatic	
	Phenolic	Rubber	Urethane	Wgt. (lbs)	Models	Wgt. (lbs)
24 x 36	P0236-P6	P0236-R6	P0236-U6	156	P0236-Z8	166
48	P0248-P6	P0248-R6	P0248-U6	184	P0248-Z8	194
30 x 60	P0360-P6	P0360-R6	P0360-U6	234	P0360-Z8	244
36 x 60	P0460-P6	P0460-R6	P0460-U6	260	P0460-Z8	270
72	P0472-P6	P0472-R6	P0472-U6	290	P0472-Z8	300

## Casters For Steel Carts

**Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).**

### Wheel Characteristics

- Phenolic - Best rollability, high strength, hardest material.
- Rubber - Best if floor has debris, quieter roll.
- Polyurethane - Best if floor conditions vary, non-marking.
- Thermorubber - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi) - High shock and impact resistant.
- Full Pneumatic - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic - Same as full pneumatic without maintenance of air.

### Brakes

- Wing Brakes (Toe) - On swivel casters only, must be ordered with caster.
- Floor Lock - Mount is welded in place, makes models not returnable.

### 4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

### 5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

### 7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

### 6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

### 8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

### N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

### Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

### Floor Lock



### 4 Series



Urethane Thermorubber

### 5 Series



Urethane Thermorubber



### 7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber




### Steel N Series



Full Pneumatic Semi Pneumatic

### Mill Duty Series



Phenolic Steel