



# SHELF TRUCKS



Model  
LGL-2436-BRK



Model  
3LGL-2436-BRK



Model  
LG-2436-BK-2DR



Model  
LG-2436-6PY

## Welded Service Carts

1200 lbs. or 2000 lbs. Capacity

Little Giant durability in an economical shelf truck. These all-welded units ship fully assembled. Heavy 12 gauge shelves. Bottom shelf has retaining lip for small parts. Top shelf is available with lip up or down (flush top). Available in either 1200 lbs. or 2000 lbs. Capacity. Durable powder coated finish.

### 1200 lbs. Capacity

5" Non-marking polyurethane casters; OAH 35".

	Shelf Size	LIP SHELVES	FLUSH TOP (& MIDDLE)	Wt.
2 SHELF 25" Shelf Clearance	18 x 24	LGL-1824-BRK	LG-1824-BRK	55
	18 x 32	LGL-1832-BRK	LG-1832-BRK	65
	24 x 36	LGL-2436-BRK	LG-2436-BRK	84
	24 x 48	LGL-2448-BRK	LG-2448-BRK	103
	30 x 48	LGL-3048-BRK	LG-3048-BRK	125
	30 x 60	LGL-3060-BRK	LG-3060-BRK	152
3 SHELF 11-3/4" Clearance	18 x 24	3LGL-1824-BRK	3LG-1824-BRK	72
	18 x 32	3LGL-1832-BRK	3LG-1832-BRK	87
	24 x 36	3LGL-2436-BRK	3LG-2436-BRK	115
	24 x 48	3LGL-2448-BRK	3LG-2448-BRK	150
	30 x 48	3LGL-3048-BRK	3LG-3048-BRK	177

Standard with 2 swivel casters with brakes and 2 rigid casters. Also available with 4 swivel casters with brakes, add: **-S-BRK**.

### With Storage Drawer 1200 lbs. Capacity


Accessory drawer with cylinder lock and 2 keys measures 13" wide x 17" deep x 4-1/2" high, offers secure storage.

	Shelf Size	LIP SHELVES	FLUSH TOP	Wt.
1 Drawer	24 x 36	LGL-2436-BK-DR	LG-2436-BK-DR	97
	24 x 48	LGL-2448-BK-DR	LG-2448-BK-DR	116
2 Drawer	24 x 36	LGL-2436-BK-2DR	LG-2436-BK-2DR	84
	24 x 48	LGL-2448-BK-2DR	LG-2448-BK-2DR	103

### 2000 lbs. Capacity

6" Non-marking polyurethane casters; OAH 36-1/2".

	Shelf Size	LIP SHELVES	FLUSH TOP (& MIDDLE)	Wt.
2 SHELF 25" Shelf Clearance	24 x 36	LGL-2436-6PY	LG-2436-6PY	97
	24 x 48	LGL-2448-6PY	LG-2448-6PY	116
	30 x 48	LGL-3048-6PY	LG-3048-6PY	138
	30 x 60	LGL-3060-6PY	LG-3060-6PY	165
3 SHELF 11-3/4" Clearance	24 x 36	3LGL-2436-6PY	3LG-2436-6PY	128
	24 x 48	3LGL-2448-6PY	3LG-2448-6PY	163
	30 x 48	3LGL-3048-6PY	3LG-3048-6PY	190
	30 x 60	3LGL-3060-6PY	3LG-3060-6PY	230



## Wheel Selection Guide

### Polyurethane Wheels

**Load Capacity Range:**  
300 – 1,000 lbs.



**Characteristics:** Easier rolling for higher capacities, long lasting, chemical resistant, non-marking and quiet operation.

High strength polyurethane tread liquid cast and mechanically locked to a polymer or cast metal core. A polyurethane tread is superior for industrial, warehouse and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

### Phenolic Wheels

**Load Capacity Range:**  
900 – 1,250 lbs.



**Characteristics:** Best rolling for heavy load capacities, long lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. A cost effective wheel best used for high capacity industrial and warehouse applications. Hard tread wheel offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

### Mold-On Rubber Wheels

**Load Capacity Range:**  
500 – 600 lbs.



**Characteristics:** Better load capacity, long lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that easily and quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

### Solid Rubber Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire over plastic hub that is more stable and easier to roll under heavy loads than pneumatic wheels. Sometimes referred to as a semi-pneumatic tire, these wheels are a rugged, maintenance-free (no air pressure to fill and maintain) and are an alternative to pneumatic wheels.

### Pneumatic Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

Like an automotive tire, an air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress creating greater rolling resistance. Pneumatic wheels are ideal for handling fragile loads over rough surfaces.

### Flat Free Hand Truck Wheels

**Load Capacity Range:**  
300 lbs.



**Characteristics:** All of the benefits of a pneumatic wheel without losing air or going flat. This non-marking tire is composed of a dense microcellular polyurethane foam that performs like a pneumatic tire, cushioning the load and rolling over rough surfaces more easily. Upgraded precision ball bearing improves rollability and extends life.

## Wheel Specifications

Wheel Dia.	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Bearing I.D.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114		
6	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0620 WHMP-0620 WHPL-0620		
8	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0820 WHMP-0820 WHPL-0820		
8	2-1/2	Solid Rubber	3/4" Ball	WHSP-0825	5/8" Ball	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830		
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	5/8" Ball	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	5/8" Ball	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4 Microcellular Foam			5/8" Ball (Precision)	WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250		
12	3-1/2	Pneumatic 4.10/3.50-6 Pneumatic 4.10/3.50-6	5/8" Ball 1" Roller	WHPN-1235 WHPN-1235-RB		
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640		