



Order Picking Truck

1200 lbs. Capacity

Convenient 12" long writing shelf for paperwork adds to the versatility of this truck. Bottom shelf has a 1-1/2" retaining lip, and the top shelf is available with a lip, or flush. The 2 swivel and 2 rigid casters feature non-marking 5" diameter polyurethane wheels with ball bearings. Swivel casters have wheel brakes. Top shelf height 35", writing shelf height 39".

Shelf Size	LIP EDGE SHELVES	FLUSH EDGE TOP	Wt.
18 x 32	LGL-1832-WBRK	LG-1832-WBRK	80
24 x 36	LGL-2436-WBRK	LG-2436-WBRK	101
24 x 48	LGL-2448-WBRK	LG-2448-WBRK	120




Model
LGL-2436-WBRK

Order Picking Truck with Storage Pocket

Sloped storage pocket under writing shelf, measures 14" wide x 12-1/2" long x 4-3/4" access height.

Shelf Size	LIP EDGE SHELVES	FLUSH EDGE TOP	Wt.
18 x 32	LGL-1832-WS-P-BK	LG-1832-WS-P-BK	90
24 x 36	LGL-2436-WS-P-BK	LG-2436-WS-P-BK	111
24 x 48	LGL-2448-WS-P-BK	LG-2448-WS-P-BK	130



Storage Pocket

Order Picking Truck with Storage Drawer

Accessory drawer with cylinder lock and 2 keys measures 13" wide x 17" deep x 4-1/2" high, offers secure storage.

Shelf Size	LIP EDGE SHELVES	FLUSH EDGE TOP	Wt.
24 x 36	LGL-2436-WBKDR	LG-2436-WBKDR	116
24 x 48	LGL-2448-WBKDR	LG-2448-WBKDR	145



Storage Drawer

3-Shelf Order Picking Truck


1200 lbs. Capacity

Convenience and versatility of our standard order-picking truck, with the added storage of a 3rd shelf. Bottom shelf has a 1-1/2" retaining lip, and the top 2 shelves are available with a lip or flush. The 2 swivel and 2 rigid casters feature non-marking 5" diameter polyurethane wheels with ball-bearings. Swivel casters have wheel brakes. Top shelf height 35". Writing shelf height 39". Clearance between shelves is 12". Also available with storage pocket measuring 14" wide x 12-1/2" long.

Shelf Size	LIP EDGE SHELVES	FLUSH TOP (& CENTER)	Wt.
18 x 32	3LGL-1832-WBRK	3LG-1832-WBRK	97
24 x 36	3LGL-2436-WBRK	3LG-2436-WBRK	133
24 x 48	3LGL-2448-WBRK	3LG-2448-WBRK	162
WITH STORAGE POCKET			
18 x 32	3LGL1832-WSP-BK	3LG-1832-WSP-BK	106
24 x 36	3LGL2436-WSP-BK	3LG-2436-WSP-BK	142
24 x 48	3LGL2448-WSP-BK	3LG-2448-WSP-BK	171



Model
3LG-2448-WSP-BK



Wheel Selection Guide

Polyurethane Wheels

Load Capacity Range:
300 – 1,000 lbs.



Characteristics: Easier rolling for higher capacities, long lasting, chemical resistant, non-marking and quiet operation.

High strength polyurethane tread liquid cast and mechanically locked to a polymer or cast metal core. A polyurethane tread is superior for industrial, warehouse and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

Phenolic Wheels

Load Capacity Range:
900 – 1,250 lbs.



Characteristics: Best rolling for heavy load capacities, long lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. A cost effective wheel best used for high capacity industrial and warehouse applications. Hard tread wheel offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

Mold-On Rubber Wheels

Load Capacity Range:
500 – 600 lbs.



Characteristics: Better load capacity, long lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that easily and quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

Solid Rubber Wheels

Load Capacity Range:
300 – 400 lbs.



Characteristics: Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire over plastic hub that is more stable and easier to roll under heavy loads than pneumatic wheels. Sometimes referred to as a semi-pneumatic tire, these wheels are a rugged, maintenance-free (no air pressure to fill and maintain) and are an alternative to pneumatic wheels.

Pneumatic Wheels

Load Capacity Range:
300 – 400 lbs.



Characteristics: Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

Like an automotive tire, an air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress creating greater rolling resistance. Pneumatic wheels are ideal for handling fragile loads over rough surfaces.

Flat Free Hand Truck Wheels

Load Capacity Range:
300 lbs.



Characteristics: All of the benefits of a pneumatic wheel without losing air or going flat. This non-marking tire is composed of a dense microcellular polyurethane foam that performs like a pneumatic tire, cushioning the load and rolling over rough surfaces more easily. Upgraded precision ball bearing improves rollability and extends life.

Wheel Specifications

Wheel Dia.	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Bearing I.D.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114		
6	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0620 WHMP-0620 WHPL-0620		
8	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0820 WHMP-0820 WHPL-0820		
8	2-1/2	Solid Rubber	3/4" Ball	WHSP-0825	5/8" Ball	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830		
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	5/8" Ball	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	5/8" Ball	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4 Microcellular Foam			5/8" Ball (Precision)	WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250		
12	3-1/2	Pneumatic 4.10/3.50-6 Pneumatic 4.10/3.50-6	5/8" Ball 1" Roller	WHPN-1235 WHPN-1235-RB		
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640		