



3-Sided Bulk Trucks

Ideal for transporting or staging of bulkier materials. All models have a 12 gauge reinforced deck, and 2 swivel, 2 rigid casters with a pushbar handle on swivel caster end. All-welded units have a powder coated finish and ship fully assembled.

MESH SIDES

13 gauge flattened expanded metal with 1-1/2" angle iron corners and top trim. Available in two heights.

Deck Size D x W	Model No.	Wt.	Model No.	Wt.	
36" Interior Height		8" x 2" Mold-On Rubber 2400 lbs. Cap.		8" x 2" Polyurethane 3600 lbs. Cap.	
24 x 48	CA-2448-8MR	150	CA-2448-8PPY	140	
24 x 60	CA-2460-8MR	169	CA-2460-8PPY	159	
30 x 48	CA-3048-8MR	170	CA-3048-8PPY	160	
30 x 60	CA-3060-8MR	185	CA-3060-8PPY	175	
48" Interior Height		6" x 2" Mold-On Rubber 2000 lbs. Cap.		6" x 2" Polyurethane 3600 lbs. Cap.	
24 x 48	T1-2448-6MR	147	T1-2448-6PY	139	
24 x 60	T1-2460-6MR	163	T1-2460-6PY	155	
30 x 48	T1-3048-6MR	165	T1-3048-6PY	157	
30 x 60	T1-3060-6MR	182	T1-3060-6PY	174	



Mesh Sides

TUBULAR STEEL SIDES

48" interior height, 1.05" O.D. x 14 gauge round steel tubing.

Deck Size D x W	Model No.	Wt.	Model No.	Wt.	
		6" x 2" Mold-On Rubber 2000 lbs. Cap.		6" x 2" Polyurethane 3600 lbs. Cap.	
24 x 36	OT-2436-6MR	118	OT-2436-6PPY	108	
24 x 48	OT-2448-6MR	136	OT-2448-6PPY	126	
24 x 60	OT-2460-6MR	153	OT-2460-6PPY	143	
30 x 48	OT-3048-6MR	149	OT-3048-6PPY	139	
30 x 60	OT-3060-6MR	167	OT-3060-6PPY	157	



Tubular Sides

SLAT-TYPE SIDES

48" interior height, 1-1/2" x 3/16" slats.

Deck Size D x W	Model No.	Wt.	Model No.	Wt.	
		6" x 2" Mold-On Rubber 2000 lbs. Cap.		6" x 2" Polyurethane 3600 lbs. Cap.	
24 x 48	S1-2448-6MR	164	S1-2448-6PY	156	
24 x 60	S1-2460-6MR	182	S1-2460-6PY	174	
30 x 48	S1-3048-6MR	190	S1-3048-6PY	182	
30 x 60	S1-3060-6MR	216	S1-3060-6PY	208	



Slat-Type Sides

SOLID SIDES

48" interior height, 14 gauge solid steel with 1-1/2" angle iron corners and top edge.

Deck Size D x W	Model No.	Wt.	Model No.	Wt.	
		6" x 2" Mold-On Rubber 2000 lbs. Cap.		6" x 2" Polyurethane 3600 lbs. Cap.	
24 x 48	B1-2448-6MR	219	B1-2448-6PY	211	
24 x 60	B1-2460-6MR	244	B1-2460-6PY	236	
30 x 48	B1-3048-6MR	246	B1-3048-6PY	238	
30 x 60	B1-3060-6MR	273	B1-3060-6PY	265	



Solid Sides



3-Sided Shelf Trucks

Heavy 12 gauge shelves are enclosed on 3 sides, 48" high above the deck in sturdy 1-1/2" angle iron corners and top trim. Mesh sides and slat-type sides allow visibility and air circulation, while solid sides offer more durability. 2 swivel, 2 rigid 6" x 2" polyurethane casters with 3600 lbs. capacity. Overall height 57".



Model
T3-3060-6PY
3 Shelf with Mesh Sides

MESH SIDES - 13 gauge flattened expanded metal

SLAT-TYPE SIDES - 1-1/2" x 3/16" slats

SOLID SIDES - 14 gauge sheet steel

	SIZE W x L	2 SHELVES 22-1/2" Clearance Model No.	Wt.	3 SHELVES 15" Clearance Model No.	Wt.
Mesh Sides	24 x 48	T2-2448-6PY	173	T3-2448-6PY	219
	24 x 60	T2-2460-6PY	198	T3-2460-6PY	250
	30 x 48	T2-3048-6PY	200	T3-3048-6PY	251
	30 x 60	T2-3060-6PY	229	T3-3060-6PY	293
Slat Sides	24 x 48	S2-2448-6PY	198	S3-2448-6PY	234
	24 x 60	S2-2460-6PY	226	S3-2460-6PY	272
	30 x 48	S2-3048-6PY	233	S3-3048-6PY	274
	30 x 60	S2-3060-6PY	267	S3-3060-6PY	319
Solid Sides	24 x 48	B2-2448-6PY	253	B3-2448-6PY	295
	24 x 60	B2-2460-6PY	288	B3-2460-6PY	340
	30 x 48	B2-3048-6PY	290	B3-3048-6PY	342
	30 x 60	B2-3060-6PY	328	B3-3060-6PY	392

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR** (2000 lbs. Capacity)



Model
T3-2448-6PYFP60

Forkliftable Order Picking Truck

3600 lbs. Capacity

Large capacity, three shelf truck designed to securely attach to your order picker. Two full width fork pockets on 24" centers and 1-1/2" steel grab bar make attachment easy. Shelves have 19" clearance. Overall height is 69". 2 rigid and 2 swivel 6" polyurethane casters assure smooth rolling, even with a full load of 3600 lbs. 48" length allows the unit to fit down any aisle!

Size W x L	Model No.	Wt.
24 x 48	T3-2448-6PYFP60	258
30 x 48	T3-3048-6PYFP60	295



3-Sided Adjustable Shelf Trucks

Expanded metal on 3 sides extends 48" high above deck to help contain loads and improve visibility and airflow. Upper shelf is adjustable on 3-1/2" centers for versatility, and can be positioned with 1-1/2" lips either up or down. Shelves are 12 gauge steel. 3600 lbs. overall capacity with non-marking, long-lasting 6" x 2" polyurethane casters, 2 swivel, 2 rigid. Overall height is 57". Additional factory installed adjustable shelves are also available.

	DECK SIZE W x L	Model No.	Wt.
Mesh Sides	24 x 48	T2-A-2448-6PY	203
	24 x 60	T2-A-2460-6PY	228
	30 x 48	T2-A-3048-6PY	230
	30 x 60	T2-A-3060-6PY	259
Slat Sides	24 x 48	S2-A-2448-6PY	218
	24 x 60	S2-A-2460-6PY	256
	30 x 48	S2-A-3048-6PY	263
	30 x 60	S2-A-3060-6PY	297
Solid Sides	24 x 48	B2-A-2448-6PY	283
	24 x 60	B2-A-2460-6PY	318
	30 x 48	B2-A-3048-6PY	320
	30 x 60	B2-A-3060-6PY	358

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR**
(2000 lbs. Capacity)



*Model
T2-A-3060-6PY*

Drop-Shelf Trucks

3-sided truck converts in seconds. Upper shelf drops down and out of the way to make room for extra large items, or it can be removed completely. Sides extend 48" above deck, with drop-shelf positioned 30" above deck. Rolls easily on 6" x 2" non-marking polyurethane casters, 2 swivel and 2 rigid. 3600 lbs. capacity.

MESH SIDES - 13 gauge flattened expanded metal

SLAT-TYPE SIDES - 1-1/2" x 3/16" slats

SOLID SIDES - 14 gauge solid steel

	DECK SIZE W x L	SHELF SIZE W x L	Model No.	Wt.
Mesh Sides	24 x 48	21 x 44	T1-2448-6PY-DS	181
	24 x 60	21 x 56	T1-2460-6PY-DS	206
	30 x 48	27 x 44	T1-3048-6PY-DS	209
	30 x 60	27 x 56	T1-3060-6PY-DS	237
Slat Sides	24 x 48	21 x 44	S1-2448-6PY-DS	198
	24 x 60	21 x 56	S1-2460-6PY-DS	225
	30 x 48	27 x 44	S1-3048-6PY-DS	234
	30 x 60	27 x 56	S1-3060-6PY-DS	271
Solid Sides	24 x 48	21 x 44	B1-2448-6PY-DS	253
	24 x 60	21 x 56	B1-2460-6PY-DS	287
	30 x 48	27 x 44	B1-3048-6PY-DS	290
	30 x 60	27 x 56	B1-3060-6PY-DS	328

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR**
(2000 lbs. Capacity)



*Model
T1-3060-6PY-DS*



Release slide bolts to drop upper shelf down and out of the way



Shelf in raised position



Wheel Selection Guide

Polyurethane Wheels

Load Capacity Range:
300 – 1,000 lbs.



Characteristics: Easier rolling for higher capacities, long lasting, chemical resistant, non-marking and quiet operation.

High strength polyurethane tread liquid cast and mechanically locked to a polymer or cast metal core. A polyurethane tread is superior for industrial, warehouse and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

Phenolic Wheels

Load Capacity Range:
900 – 1,250 lbs.



Characteristics: Best rolling for heavy load capacities, long lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. A cost effective wheel best used for high capacity industrial and warehouse applications. Hard tread wheel offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

Mold-On Rubber Wheels

Load Capacity Range:
500 – 600 lbs.



Characteristics: Better load capacity, long lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that easily and quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

Solid Rubber Wheels

Load Capacity Range:
300 – 400 lbs.



Characteristics: Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire over plastic hub that is more stable and easier to roll under heavy loads than pneumatic wheels. Sometimes referred to as a semi-pneumatic tire, these wheels are a rugged, maintenance-free (no air pressure to fill and maintain) and are an alternative to pneumatic wheels.

Pneumatic Wheels

Load Capacity Range:
300 – 400 lbs.



Characteristics: Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

Like an automotive tire, an air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress creating greater rolling resistance. Pneumatic wheels are ideal for handling fragile loads over rough surfaces.

Flat Free Hand Truck Wheels

Load Capacity Range:
300 lbs.



Characteristics: All of the benefits of a pneumatic wheel without losing air or going flat. This non-marking tire is composed of a dense microcellular polyurethane foam that performs like a pneumatic tire, cushioning the load and rolling over rough surfaces more easily. Upgraded precision ball bearing improves rollability and extends life.

Wheel Specifications

Wheel Dia.	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Bearing I.D.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114		
6	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0620 WHMP-0620 WHPL-0620		
8	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0820 WHMP-0820 WHPL-0820		
8	2-1/2	Solid Rubber	3/4" Ball	WHSP-0825	5/8" Ball	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830		
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	5/8" Ball	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	5/8" Ball	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4 Microcellular Foam			5/8" Ball (Precision)	WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250		
12	3-1/2	Pneumatic 4.10/3.50-6 Pneumatic 4.10/3.50-6	5/8" Ball 1" Roller	WHPN-1235 WHPN-1235-RB		
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640		