



Bishamon's Next Generation of Quality Lift Tables Shipped to You in 48 Hours!*



Experience Industry's "Best Engineered" Line of Lift Tables









OPTIMUS™ SPECIFICATIONS						
	L2K		L3K		L5K	
Maximum Load Capacity (lbs)	2000		3000		5000	
Lowered Height (in)	8 1/2		8 5/8		8 3/4	
Maximum Raised Height (in)	38 1/2		42 5/8		48	
Travel (in)	30		34		39 1/4	
Platform Width (in)	28	36 x	28	36 x	32	48
Platform Length (in)	28 × 48	4̂8	48	4 8	x 56	48 × 72
Base Frame Width (in)	24 5/16		24 5/16		28 5/16	
Base Frame Length (in)	49		49		56	
Weight (lbs)	460	490	530	560	730	1030

Design & Engineering

- Leading edge product development utilizing industry's latest advanced analysis techniques.
- Comprehensive fatigue, life-cycle and performance testing
- Designed for performance and durability with lifetime, maintenance free, composite bushings throughout
- Compliant with ANSI MH29.1:2012 "Safety Requirements for Industrial Scissor Lifts"

Safety in Mind

- Meets or exceeds required safety clearances
- Flow limiting safety valve at cylinder
- Contoured scissor legs and large torque tube maximize stiffness and stability
- Hinged maintenance bars powder coated yellow for safety
- Contoured platform corners for operator safety

Additional Features

- Unitized power unit
- Innovative features including easy-view hydraulic reservoir
- Intuitive and user friendly plug & play controls
- Clean, accessible maintenance friendly design

Optimus[™] **Options**

43" Diameter Turntable Platform Foot Operated Controls With Guard

Accordion Bellows Skirting

Semi-Live Portability (L2K only)

Cart Portability With 2 Swivel and 2 Rigid Casters - adds 7" to lowered ht. (L2K & L3K only)

480 VAC Motor w/Low Voltage Controls (L3K & L5K only)



43" Diameter Turntable



Foot Control



Accordion Bellows

Bishamon ▶▶▶ ON-DEMAND

*Bishamon On-Demand Group ships in 48 hours or less!

Optimus Lifts Included are:

L2K-2848

L2K-3648

L2K-TT

L3K-2848 (115 VAC)

L3K-3648 (115 VAC)

L5K-3256 (115 VAC)

Adding options may affect delivery. Consult factory to request a copy of the On-Demand program details.

DISTRIBUTED BY:

Custom Equipment Company Toll Free: 866-333-0728

Fax: 919-847-5765

e-mail: tom@custommhs.com

Secure Website: https://www.custommhs.com



Bishamon Industries Corporation

BIC-OPT-06-13