

PowerStak

PowerStak Series



Narrow mast and offset design provide workers a clear view with no blind spots.



Adjustable fork carriage allows forks to be quickly repositioned to best accommodate loads (straddle only).

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Fork O.D.	Base/Legs I.D./O.D.	Shipping Weight
PPS Series - Fork Over - 21" Overall Fork Width - 24" Load Center							
PPS2200-62NFO-21	2200 lbs	62"	3-1/2"	78 x 31-1/2 x 65"	20-1/2"	N/A	1100 lbs
PPS Series - Fork Over - 27" Overall Fork Width - 24" Load Center							
PPS2200-62NFO-27	2200 lbs	62"	3-1/2"	78 x 31-1/2 x 65"	26-3/4"	N/A	1100 lbs
PPS Series - Adjustable Base - Straddle (40-50" I.D.) - 24" Load Center							
PPS2200-62NAS	2200 lbs	62"	2-5/8"	79 x 48-58 x 68"	12-1/2" - 26-3/4"	40-50" / 48-58"	1200 lbs
PPS2200-101AS	2200 lbs	101"	2-5/8"	73 x 48-58 x 73"	12-1/2" - 26-3/4"	40-50" / 48-58"	1405 lbs
PPS2200-125AS	2200 lbs	125"	2-5/8"	83 x 48-58 x 73"	12-1/2" - 26-3/4"	40-50" / 48-58"	1445 lbs
PPS2200-150AS	2200 lbs	150"	2-5/8"	99 x 48-58 x 73"	12-1/2" - 26-3/4"	40-50" / 48-58"	1545 lbs

Features

- 24 volt DC/700 watt drive motor
- 10" x 3" Polyurethane drive wheel
- Polyurethane load wheels
- Adjustable welded steel forks, 6" wide x 2" thick x 42" long (NFO models have fixed forks)
- 2 x 12 volt amp/hr batteries
- 15 amp internal 115V charger
- Battery discharge indicator
- E-Stop emergency stop switch
- Safety key switch

Options for PPS2200 models:

- Load Backrest
- Forged Steel Forks
- Rubber Drive Wheel
- Spiral Cell Marine Battery 2 x 50 amp/hr
- Battery - 12 volt 70 amp AGM sealed battery

Note: Not all options are available for all models; please contact Sales before ordering.



Ergonomic handle with comfort-grip controls and switch redundancy for left- or right-hand operation.



Auto-reversing "belly bump" switch protects against operator accidents while working in tight quarters.



Straddle model shown



Fork-Over model shown

Distributed By: Custom Equipment Company
 866-333-0728 919-847-5765 fax
 tom@custommhs.com www.custommhs.com

Heavy Duty PowerStak

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Fork O.D.	Base/Legs I.D./O.D.	Shipping Weight
PPS Series - Fixed Base - Straddle (50" I.D.)							
PPS3000-125FS	3000 lbs	125"	2-3/32"	83 x 58 x 77"	8" - 26-3/4"	50-58"	2000 lbs

Features

- 24 volt DC/1000 watt drive motor
- 10" x 4" polyurethane drive wheel
- Tandem polyurethane load wheels
- Adjustable forged steel forks, 4" wide x 2" thick x 42" long
- 2 x 12 volt 150 amp/hr batteries
- 2 x 12 volt 150 amp/hr batteries
- 25 amp internal 115V charger
- Hour meter with battery discharge indicator
- E-Stop emergency stop switch
- Safety key switch



Tandem polyurethane load wheels



Forged forks



PPS3000-125FS shown.

PowerStak LITE

Model Number	Load Capacity	Raised Height	Lowered Height	Dimensions H / W / L	Fork O.D.	Base/Legs I.D./O.D.	Shipping Weight
PPS Series - Fork Over - 21" Overall Fork Width - 24" Load Center							
PPS1500-62NFO-21	1500 lbs	62"	3-3/8"	78 x 29 x 66"	12-1/2" / 26-3/4"	N/A	805 lbs
PPS Series - Fork Over - 27" Overall Fork Width - 24" Load Center							
PPS1500-62NFO-27	1500 lbs	62"	3-3/8"	78 x 29 x 66"	12-1/2" / 26-3/4"	N/A	805 lbs
PPS Series - Adjustable Base - Straddle (38-52" I.D.) - 24" Load Center							
PPS1500-62NAS	1500 lbs	62"	2-5/8"	79 x 46-60 x 69"	12-1/2" / 26-3/4"	38-52" / 46-60"	982 lbs



PPS1500-62NAS shown.



PPS1500-62NFO shown.

Features

- 24 volt DC/350 watt drive motor
- 7" x 2" polyurethane drive wheel
- Polyurethane load wheels
- Adjustable welded steel forks, 6" wide x 2" thick x 42" long (NFO) models have fixed forks
- 2 x 12 volt 55 amp/hr batteries
- 15 amp internal 115V charger
- Battery discharge indicator
- E-Stop emergency stop switch
- Safety key switch

Fully powered PowerStak Counterweight stacker available on page 6