

FORK DECK MAINTENANCE PLATFORM

Turn your fork truck into a personnel lift; Safe, economical access to heights greater than those easily reached by a rolling ladder.

- Rugged steel construction
- Non-skid platform
- 42" high rails with midrails, 4" toeboards and locking gate
- 60" high screen shields operator from fork lift mast
- Safety chain secures platform to mast
- 2" x 7" fork pockets mounted on 29" centers
- 4" swivel casters on base permit easy positioning
- Safety orange powder coat finish
- Ships flat in a box for easy assembly
- Built to ANSI B56.10 standards

Model	L" X W"	Weight
FD-O-C	36" x 36"	135
FD-48-C	36" x 48"	157
FD-40-48	48" x 40"	164

OPTIONAL ACCESSORIES	
Fluorescent Bulb Caddy	26
Tool Tray	14
All welded available	-



1000 lbs capacity

CANTILEVER SERIES

Features:

- 300 lbs. capacity (higher capacities available - contact factory)
- 59 degree slope
- Heavy-duty 1" x 2" rectangular tube frame
- High quality 5" x 2" locking casters
- Available with Rear Guardrail removed for easy walk through
- Powder coat finish
- Ships KD to prevent freight damage and lower freight cost

ADD PLATFORM OVERHANG LENGTH TO MODEL NUMBER WHEN ORDERING

CANTILEVER LADDERS

PLATFORM OVERHANG					14" OVERHANG		28" OVERHANG		35" OVERHANG		42" OVERHANG	
STEPS	PLATFORM HEIGHT	VERTICAL CLEARANCE	PLATFORM WIDTH	MODEL #	WEIGHT	BASE W" x D"	WEIGHT	BASE W" x D"	WEIGHT	BASE W" x D"	WEIGHT	BASE W" x D"
6 STEP	60"	57"	24"	CL-6	468	32 x 46	735	32 x 53	763	32 x 60	791	32 x 67
7 STEP	70"	67"	24"	CL-7	442	32 x 52	695	32 x 52	773	32 x 59	801	32 x 66
8 STEP	80"	77"	24"	CL-8	412	32 x 58	640	32 x 58	779	32 x 58	807	32 x 65
9 STEP	90"	87"	24"	CL-9	405	32 x 65	583	32 x 65	697	32 x 65	811	32 x 65
10 STEP	100"	97"	24"	CL-10	401	32 x 71	554	32 x 71	668	32 x 71	757	32 x 71
11 STEP	110"	107"	24"	CL-11	405	32 x 77	544	32 x 77	633	32 x 77	722	32 x 77
12 STEP	120"	117"	24"	CL-12	409	32 x 84	537	32 x 84	601	32 x 84	690	32 x 84
13 STEP	130"	127"	24"	CL-13	417	40 x 90	520	40 x 90	609	40 x 90	673	40 x 90
14 STEP	140"	137"	24"	CL-14	450	40 x 96	528	40 x 96	592	40 x 96	656	40 x 96
15 STEP	150"	147"	24"	CL-15	458	40 x 103	536	40 x 103	600	40 x 103	664	40 x 103

Weight is a combination of the ladder and counter weight, does not include skidding, add 120 lbs for packaging.

NEW! TRUCK/DOCK ACCESS LADDER



- Great for accessing trucks or docks
- Rugged - base frame and rear vertical are 2" x 1" rectangular tubing
- 21" Deep Top Step standard
- Heavy duty serrated grating step tread
- 10" rear rubber wheels - Great on parking lots or rough surfaces
- Lightweight - lift and roll wheelbarrow portability
- 450 lbs. capacity
- Available in both 59° ladder slope or gradual 50° stairway slope
- No Rear Guardrail standard for easy walk through (includes snap chain)
- Gray powder coat finish
- Built to OSHA and ANSI standards

LADDER SLOPE 59°

MODEL #	TOP STEP HEIGHT	OVERALL HEIGHT	STEP WIDTH	BASE W" x L"	WEIGHT LBS.
TA-5-24	50"	80"	24"	32" x 53"	145
TA-5-36	50"	80"	36"	44" x 53"	170

STAIRWAY LADDER SLOPE 50 DEGREE

MODEL #	TOP STEP HEIGHT	OVERALL HEIGHT	STEP WIDTH	BASE W" x L"	WEIGHT LBS.
SW-TA-5-24	50"	80"	24"	32" x 60"	155
SW-TA-5-36	50"	80"	36"	44" x 60"	180



TANK TOP LIFT

FEATURES:

- Provides easy access to tank trucks, railroad cars or other cantilevered applications
- Great for clearing snow and ice off tops of trailers
- Manually propelled for use on hard level surfaces
- 48" long cantilevered platform
- Hydraulic hand pump raises and lowers platform
- Step and deck tread is open serrated grating, while slip resistant rungs provide access when platform is raised
- Base is 28" wide and 60" long, fixed outriggers spread 69"
- Full rails on both sides with gates at each end of platform
- Recommended Option: 30" extension railing
- Two swivel and two rigid 8" casters for use on hard surfaces
- Two adjustable stabilizing jacks secure lifts to ground
- Available with a fixed platform height
- 300 lbs. load capacity
- Standard finish deep gray enamel paint
- Safety orange powder coat also available - Recommended for outdoor applications


OPTIONAL ACCESSORIES

- AC electric power
- DC electric power
- Air-Hydraulic power
- Tool Tray
- Fluorescent tube holder
- Platform duplex receptacle
- Removable 30" extension railing
- Safety orange powder coat finish

Three available power options:

- Convenient plug in 120V AC with thermal overload protection
- Independent 12V DC deep cycle system complete with battery and charger along with a double solenoid for additional safety
- Air hydraulic power requiring 90 CFM with 90 PSI pressure

Caution: Unless special provisions are made, platforms and lifts must not be used for energized barewire electrical work or operated on inclined surfaces. When this equipment is used, ground personnel should be excluded from the immediate work area. Compliance with unspecified codes should not be assumed.



Shown with options: safety orange paint & 30" extension railing

Model Number	Platform Max	Height Min	Platform Length	Platform Width	Underclearance Height	Weight Lbs.
TT-913	13' 8"	9' 4"	48"	24"	Adjustable 9' to 13'	1525
TT-913F	13' 8"	9' 4"	48"	24"	Non-Adjustable 9' to 13'	1450

SCISSOR LIFTS

FEATURES:

- Manually propelled - Rated Capacity 1000 lbs./four person
- Totally enclosed platform with 42" guardrails, midrails, 4" toeboards and swing-in gate
- Large 3' x 8' platform with serrated grating deck to assure secure footing
- Built-in ladder provides access to platform in fully lowered position
- 8" swivel casters for easy rolling and maneuverability
- Self-storing outriggers extend from base to provide maximum stability (optional on lower height models)
- Leveling jacks secure unit to floor and compensate for uneven surfaces (standard on floor models with raised deck heights above 15', optional on lower height models)
- Deep gray enamel finish
- Meets/exceeds ANSI requirements
- Platform controls: for operator safety both hands are required to change elevation
- Emergency stops:
 - Located on platform for operator use
 - Emergency stop also located on base for use by ground personnel
 - Lockable to prevent unauthorized use



STANDARD FEATURES:

- 120 volt AC power (raise and lower) with thermal overload protection

OPTIONAL POWER:

- 12 volt DC deep cycle system available with battery and charger
- Air-Hydraulic Drive - recommended for hazardous environments
- CAUTION:
 - Unless special provisions are made, platforms and lifts must not be used for energized bare-wire electrical work or operated on inclined surfaces
 - When this equipment is used, ground personnel should be excluded from the immediate work area

OPTIONS/ACCESSORIES:

- Cantilevered platform extensions
- Special voltage electrical systems
- 120 volt outlet on platform
- Safety orange powder coat finish

Custom Designs:

Available to meet your special access problems - contact factory for quotation

NOTE: All base dimensions are 9 by 4 ft. *Add 20" to 4-ft base width for extended stabilizers ** Add 40" to 4-ft base width for extended stabilizers